




« Logical Layer »

The Logic part

- High level ECM services
 - Audit and Log services
 - Workflow service
 - Comment service
 - Transformation service
 - etc.
- Provides business logic
 - Nuxeo Core provides the infrastructure
 - Enterprise Components provide behaviour and features related to content / documents

Architecture Diagram

- Packaged as several separate bundles
- Leverages JEE 5
 - EJB3 SB
 - EJB3 MDB
 - JAAS integration



Nuxeo Service – Typical impl.

- A Nuxeo Runtime Service
 - Leverage NXRuntime extensibility
 - Extension points
 - XML Configuration
 - Leverage NXRuntime platform independance
 - Runs on JBoss
 - Runs on Eclipse RCP
- A EJB3 Facade on top of Nuxeo Service
 - Provides Security and Transaction integration
 - Leverage EJB3 state management
 - Provides remoting support
- Clean & clear API

Nuxeo Services - SPI

- A lot of Nuxeo Services provide SPI interfaces
 - Leverage Runtime to let several providers implement the same features (using extension point / extension contribution)
- Some examples
 - Content Transformation service
 - Workflow engine
 - Relation service
- Most Nuxeo Services leverage NXRuntime for XML configuration and extensibility

Nuxeo 5 and EJB3

- We use the new (JEE5) EJB model: EJB 3
 - Simpler code (one simple class)
 - Annotations instead of XML descriptors
 - Almost POJO! :-)
- Nuxeo 5 uses
 - Session Beans for Services
 - Transaction, Security, Pooling, State management, Remote access
 - Message Driven Beans
 - JMS driven services
 - Entity Beans
 - When RDBMS storage is usefull/efficient (audit log, non-content data, etc.)

Nuxeo Services


- NXWorkflow
 - Provides a WfMC-oriented API
 - Integrates BPM and Document Management
 - Provides a SPI to support several engines
 - Default engine: JBoss jBPM
- NXRelations
 - Provides RDF-based relations management between ressources/documents
 - Provides an SPI (default engine: Jena RDF)
- NXEvent
 - JMS Messaging (default implementation: JBoss Messaging)
 - Relay Core Events
 - Provide an API for messaging

Nuxeo Services

- NXDirectory
 - (Meta-) directory manager (CPSDirectory-inspired)
 - SQL and LDAP support
 - Configuration via XML/EP
 - Usefull to manage any non-content data list (keyword, list of values, for forms, users, groups, units, etc.)
- NXUserManager
 - Provides a UserManager (like CPSUserFolder)
 - Uses NXDirectory directories as user/group datasources
- NXTransforms
 - Content Transformation service
 - Transformers are plugins (extension contributions)

Nuxeo Services

- NXMimeType
 - Pluggable Mime Type detection service
- NXPlatform
 - Default content hierarchy for web application
 - Provide very basic content logic over the core
 - Enable multi-cores instances



Nuxeo Services

- NXFileManager
 - dedicated to « file to document » mapping
 - file (mime-type, location, ...) => document type
 - exposes File management API (upload, download, etc.)
 - for Microsoft Office Helper
 - for Browser Plugins
- NXAudit
 - Customizable audit log
 - Based on NXEvents
- NXJobs
 - Job running service (cron-like)

Nuxeo Services - Cache

- NXServerCache
 - Distributed cache system
 - Intercepts all access and events to Nuxeo Core
 - Fills a JBoss Cache instance with DocumentModels
 - Forward invalidation messages to the cache
- NXClientCache
 - Distributed cache system (client part)
 - Intercepts all access to the DocumentManager
 - Transparently looks up the cache before contacting the server

Nuxeo Services – UI related

- NXTypeManager
 - Provides configuration for UI management of Documents
 - default views
 - basic layout : Widget and Fields Mapping
 - define allowed subtypes

```
<type id="Folder" coretype="Folder">
  <label>Folder</label>
  <icon>/icons/folder.gif</icon>
  <default-view>view_documents</default-view>
  <subtypes>
    <type>Folder</type>
    <type>File</type>
    <type>Note</type>
  </subtypes>
  <layout>
    <widget jsfcomponent="h:inputText" schemaname="dublincore"
      fieldname="title" />
    <widget jsfcomponent="h:inputTextarea" schemaname="dublincore"
      fieldname="description" />
  </layout>
</type>
```


Nuxeo Services – UI related

- NXActionManager
 - UI Action management (CPS-like)
 - Used to define applicative UI actions' links/buttons depending on the context

```
<web-action id="TAB_CONTENT" link="/incl/tabs/document_content.xhtml"
  enabled="true" label="action.view.content"
  icon="/icons/file.gif">
  <filter-id>edit_content</filter-id>
  <action-list-id>VIEW_ACTION_LIST</action-list-id>
  <category>WorkspaceRoot</category>
  <category>Workspace</category>
  <category>SectionRoot</category>
  <category>Section</category>
  <category>Folder</category>
</web-action>
```

Nuxeo Services - 5.1

- NXSearchService
 - Unified and pluggable Full Text Search Service
- NXPlaceFullConfiguration
 - Attache configuration to a content node
 - Subscriptions
 - local themes configuration
 - local creation rules ...
- To be continued... ;-)

Nuxeo Service Layer

- Most of services are not EJB3 dependants
 - they can be used client side (RCP) or server side (JEE)
- Each service exposes an API
 - POJO API for most of them
 - EJB3 API for all
- All services are remote accessibles
 - can be used from any client type

Nuxeo Service Layer

