

Hortonworks Data Platform

HDP Reference Guide

(Dec 21, 2015)

Hortonworks Data Platform: HDP Reference Guide

Copyright © 2012-2015 Hortonworks, Inc. Some rights reserved.

The Hortonworks Data Platform, powered by Apache Hadoop, is a massively scalable and 100% open source platform for storing, processing and analyzing large volumes of data. It is designed to deal with data from many sources and formats in a very quick, easy and cost-effective manner. The Hortonworks Data Platform consists of the essential set of Apache Hadoop projects including MapReduce, Hadoop Distributed File System (HDFS), HCatalog, Pig, Hive, HBase, ZooKeeper and Ambari. Hortonworks is the major contributor of code and patches to many of these projects. These projects have been integrated and tested as part of the Hortonworks Data Platform release process and installation and configuration tools have also been included.

Unlike other providers of platforms built using Apache Hadoop, Hortonworks contributes 100% of our code back to the Apache Software Foundation. The Hortonworks Data Platform is Apache-licensed and completely open source. We sell only expert technical support, [training](#) and partner-enablement services. All of our technology is, and will remain, free and open source.

Please visit the [Hortonworks Data Platform](#) page for more information on Hortonworks technology. For more information on Hortonworks services, please visit either the [Support](#) or [Training](#) page. Feel free to [contact us](#) directly to discuss your specific needs.



Except where otherwise noted, this document is licensed under
Creative Commons Attribution ShareAlike 3.0 License.
<http://creativecommons.org/licenses/by-sa/3.0/legalcode>

Table of Contents

1. Configuring Ports	1
1.1. Accumulo Service Ports	1
1.2. Flume Service Ports	2
1.3. HBase Service Ports	2
1.4. HDFS Service Ports	4
1.5. Hive Service Ports	4
1.6. Hue Service Port	5
1.7. Kafka Service Ports	5
1.8. Kerberos Service Ports	5
1.9. Knox Service Ports	6
1.10. MapReduce Service Ports	6
1.11. MySQL Service Ports	6
1.12. Oozie Service Ports	6
1.13. Ranger Service Ports	7
1.14. Spark Thrift Server Service Ports	7
1.15. Sqoop Service Ports	8
1.16. Storm Service Ports	8
1.17. Tez Ports	9
1.18. YARN Service Ports	9
1.19. ZooKeeper Service Ports	10
2. Controlling HDP Services Manually	12
2.1. Starting HDP Services	12
2.2. Stopping HDP Services	15
3. Deploying HDP In Production Data Centers With Firewalls	18
3.1. Terminology	18
3.2. Mirroring or Proxying	19
3.3. Considerations for choosing a Mirror or Proxy solution	19
3.4. Recommendations for Deploying HDP	20
3.5. RPMs in the HDP repository	20
3.6. Detailed Instructions for Creating Mirrors and Proxies	21
3.6.1. Option I - Mirror server has no access to the Internet	21
3.6.2. Option II - Mirror server has temporary or continuous access to the Internet	24
3.7. Set up a trusted proxy server	29
4. Hadoop Service Accounts	31
5. Supported Database Matrix for the Hortonworks Data Platform	32

List of Tables

1.1. Accumulo Service Ports	1
1.2. Flume Service Ports	2
1.3. HBase Service Ports	3
1.4. HDFS Service Ports	4
1.5. Hive Service Ports	4
1.6. Hue Service Port	5
1.7. Kafka Service Ports	5
1.8. Kerberos Service Ports	5
1.9. Knox Service Ports	6
1.10. MapReduce Service Ports	6
1.11. MySQL Service Ports	6
1.12. Oozie Service Ports	7
1.13. Ranger Service Ports	7
1.14. Spark Thrift Server Service Ports	7
1.15. Sqoop Service Ports	8
1.16. Storm Service Ports	8
1.17. Tez Ports	9
1.18. YARN Service Ports	9
1.19. ZooKeeper Service Ports	10
3.1. Terminology	18
3.2. Hortonworks Yum Repositories	21
3.3. HDP Component Options	23
3.4. Yum Client Options	24
3.5. Yum Client Configuration Commands	25
3.6. \$OS Parameter Values	28
5.1. Supported HDP Databases	32

1. Configuring Ports

Tables in this section specify which ports must be opened for an ecosystem component or service to communicate with other components and services.

Make sure the appropriate ports are open before you install HDP.

1.1. Accumulo Service Ports

The following table lists the default ports used by the various Accumulo services. (**Note:** Neither of these services are used in a standard HDP installation.)

Table 1.1. Accumulo Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Master	Master nodes (Active master and any standby)	9999		The Master thrift server	Yes (client API needs)	master.port.client in accumulo-site.xml
TabletServer	Slave nodes	9997		The TabletServer thrift server	Yes (client API needs)	tserver.port.client in accumulo-site.xml
Garbage Collector	GC nodes (Active GC and any standby)	50091		The GarbageCollector thrift server	No	gc.port.client in accumulo-site.xml
Monitor	Monitor nodes (Active Monitor and any standby)	50095	HTTP(S)	Metrics/ Monitoring of an Accumulo instance	Yes	monitor.port.client in accumulo-site.xml
Monitor log aggregation	Monitor nodes (Active Monitor and any standby)	4560		Log4j socket which accepts logs forwarded from other Accumulo services	No	monitor.port.log4j in accumulo-site.xml
Tracer	Tracer nodes	12234		The Tracer thrift server	Yes (if enabled)	trace.port.client in accumulo-site.xml
Thrift Proxy (optional)	Proxy nodes	42424		The Thrift Proxy server	Yes (if enabled)	port in proxy.properties
TabletServer Replication Service	Slave nodes	10002		TabletServer Thrift service supporting multi-instance Accumulo replication	No	replication.receipt.service.port in accumulo-site.xml
Master Replication Service	Master nodes (Active master and any standby)	10001		Master Thrift service supporting multi-instance Accumulo replication	No	master.replication.coordinator.port in accumulo-site.xml

1.2. Flume Service Ports

The following table lists the default ports used by the various Flume services. (**Note:** Neither of these services are used in a standard HDP installation.)

Table 1.2. Flume Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Flume	Flume Agent	41414	TCP	Flume performance metrics in JSON format	Yes (client API needs)	master.port.client in accumulo-site.xml
Flume	HDFS Sink	8020	TCP	Communication from Flume into the Hadoop cluster's NameNode	Yes (client API needs)	tserver.port.client in accumulo-site.xml
Flume	HDFS Sink	9000	TCP	Communication from Flume into the Hadoop cluster's NameNode	No	gc.port.client in accumulo-site.xml
Flume	HDFS Sink	50010	TCP	Communication from Flume into the Hadoop cluster's HDFS DataNode	No	
Flume	HDFS Sink	50020	TCP	Communication from Flume into the Hadoop cluster's HDFS DataNode	No	
Flume	HDFS Sink	2181	TCP	Communication from Flume into the Hadoop cluster's Zookeeper	No	
Flume	HDFS Sink	16020	TCP	Communication from Flume into the Hadoop cluster's HBase Regionserver	No	
Flume	All Other Sources and Sinks	Variable	Variable	Ports and protocols used by Flume sources and sinks	No	Refer to the flume configuration file(s) for ports actually in use. Ports in use are specified using the port keyword in the Flume configuration file. By default Flume configuration files are located in /etc/flume/conf on Linux and c:\hdp\flume-1.4.0.x.y.z\conf on Windows

1.3. HBase Service Ports

The following table lists the default ports used by the various HBase services.

Table 1.3. HBase Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
HMaster	Master Nodes (HBase Master Node and any back-up HBase Master node)	16000			Yes	<code>hbase.master.port</code>
HMaster Info Web UI	Master Nodes (HBase master Node and back up HBase Master node if any)	16010	http	The port for the HBaseMaster web UI. Set to -1 if you do not want the info server to run.	Yes	<code>hbase.master.info.port</code>
Region Server	All Slave Nodes	16020			Yes (Typically admins, dev/ support teams)	<code>hbase.regionserver.port</code>
Region Server	All Slave Nodes	16030	http		Yes (Typically admins, dev/ support teams)	<code>hbase.regionserver.info.port</code>
HBase REST Server (optional)	All REST Servers	8080	http	The port used by HBase Rest Servers. REST servers are optional, and not installed by default	Yes	<code>hbase.rest.port</code>
HBase REST Server Web UI (optional)	All REST Servers	8085	http	The port used by HBase Rest Servers web UI. REST servers are optional, and not installed by default	Yes (Typically admins, dev/ support teams)	<code>hbase.rest.info.port</code>
HBase Thrift Server (optional)	All Thrift Servers	9090		The port used by HBase Thrift Servers. Thrift servers are optional, and not installed by default	Yes	
HBase Thrift Server Web UI (optional)	All Thrift Servers	9095		The port used by HBase Thrift Servers web UI. Thrift servers are optional, and not installed by default	Yes (Typically admins, dev/ support teams)	<code>hbase.thrift.info.port</code>

1.4. HDFS Service Ports

The following table lists the default ports used by the various HDFS services. (**Note:** Neither of these services are used in a standard HDP installation.)

Table 1.4. HDFS Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
NameNode WebUI	Master Nodes (NameNode and any back-up NameNodes)	50070	http	Web UI to look at current status of HDFS, explore file system	Yes (Typically admins, Dev/Support teams)	dfs.http.address
		50470	https	Secure http service		dfs.https.address
NameNode metadata service		8020/9000	IPC	File system metadata operations	Yes (All clients who directly need to interact with the HDFS)	Embedded in URI specified by fs.defaultFS
DataNode	All Slave Nodes	50075	http	DataNode WebUI to access the status, logs etc.	Yes (Typically admins, Dev/Support teams)	dfs.datanode.http.address
		50475	https	Secure http service		dfs.datanode.https.address
		50010		Data transfer		dfs.datanode.address
		50020	IPC	Metadata operations	No	dfs.datanode.ipc.address
Secondary NameNode	Secondary NameNode and any backup Secondary NameNode	50090	http	Checkpoint for NameNode metadata	No	dfs.secondary.http.address

1.5. Hive Service Ports

The following table lists the default ports used by the various Hive services. (**Note:** Neither of these services are used in a standard HDP installation.)

Table 1.5. Hive Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Hive Server	Hive Server machine (Usually a utility machine)	10000		Service for programmatically (Thrift/JDBC)	Yes (Clients who need to connect to Hive either programmatically)	ENV Variable HIVE_PORT

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
				connecting to Hive	or through UI SQL tools that use JDBC)	
Hive Web UI	Hive Server machine (Usually a utility machine)	9999	http	Web UI to explore Hive schemas	Yes	hive.hwi.listen.port
Hive Metastore		9083	http		Yes (Clients that run Hive, Pig and potentially M/R jobs that use HCatalog)	hive.metastore.uris

1.6. Hue Service Port

The following table lists the default port used by the Hue web listener.

Table 1.6. Hue Service Port

Service	Servers	Default Port Used	Protocol	Description	Need End User Access?	Configuration Parameters
Hue	Node that is running Hue	8888	http	Port used by the Hue web listener to server web pages for Hue	Yes	http_port property in the /etc/hue/conf/hue.ini file

1.7. Kafka Service Ports

The following table lists the default ports used by Kafka.

Table 1.7. Kafka Service Ports

Service	Servers	Default Port	Default Ambari Port	Protocol	Description	Need End User Access?	Configuration Parameters
Kafka	Kafka Server	9092	6667	TCP	The port for Kafka server.		

1.8. Kerberos Service Ports

The following table lists the default port used by the designated Kerberos KDC.

Table 1.8. Kerberos Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
KDC	Kerberos KDC server	88		Port used by the designated KDC		

1.9. Knox Service Ports

The following table lists the default port used by Knox.

Table 1.9. Knox Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Knox	Knox server	8443		Port used by Knox		

1.10. MapReduce Service Ports

The following table lists the default ports used by the various MapReduce services.

Table 1.10. MapReduce Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
MapReduce		10020	http	MapReduce JobHistory server address		mapreduce.jobhistory.address
MapReduce		19888	http	MapReduce JobHistory webapp address		mapreduce.jobhistory.webapp.address
MapReduce		13562	http	MapReduce Shuffle Port		mapreduce.shuffle.port

1.11. MySQL Service Ports

The following table lists the default ports used by the various MySQL services.

Table 1.11. MySQL Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
MySQL	MySQL database server	3306				

1.12. Oozie Service Ports

The following table lists the default ports used by Oozie.

Table 1.12. Oozie Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Oozie	Oozie Server	11000	TCP	The port Oozie server runs.	Yes	OOZIE_HTTP_PORT in oozie_env.sh
Oozie	Oozie Server	11001	TCP	The admin port Oozie server runs.	No	OOZIE_ADMIN_PORT in oozie_env.sh
Oozie	Oozie Server	11443	TCP	The port Oozie server runs when using HTTPS.	Yes	OOZIE_HTTPS_PORT in oozie_env.sh

1.13. Ranger Service Ports

The following table lists the default ports used by Ranger.

Table 1.13. Ranger Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Ranger Admin	Ranger Admin Nodes	6080	HTTP	Port for Ranger Admin web UI.	Yes	ranger.service.http.port (in ranger-admin-site.xml)
Ranger Admin	Ranger Admin Nodes	6182	HTTPS	Port for Ranger Admin web UI (with SSL).	Yes	ranger.service.https.port (in ranger-admin-site.xml)
UNIX Auth Service	Ranger Usersync Node	5151	SSL/TCP	Port for UNIX Auth service.	No	ranger.usersync.port (in ranger-ugsync-site.xml)
Ranger KMS	Ranger KMS Nodes	9292	HTTP	Port for Ranger KMS.	No	ranger.service.http.port (in kms-site.xml)
Ranger KMS	Ranger KMS Nodes	9293	HTTPS	Port for Ranger KMS.	No	ranger.service.https.port (in kms-site.xml)
Solr used by Ranger	Solr	6083,6183	HTTP	Ports for auditing to Solr.	Yes	ranger-admin and all plug-ins

1.14. Spark Thrift Server Service Ports

The following table lists the default ports used by the Spark Thrift Server.

Table 1.14. Spark Thrift Server Service Ports

Service	Servers	Default Ports Used	Default Ambari Port	Protocol	Description	Need End User Access?	Configuration Parameters
Spark Thrift Server	Spark Thrift Server	(none for manually installed cluster)	10015	TCP	The port for the Spark Thrift Server		

1.15. Sqoop Service Ports

The following table lists the default ports used by Sqoop.

Table 1.15. Sqoop Service Ports

Service	Servers	Default Ports	Protocol	Description	Need End User Access?	Configuration Parameters
Sqoop	Metastore	16000	TCP	Connection between Sqoop and the metastore	No	sqoop.metastore.server.port
Sqoop	JDBC Listener	Varies, depends on target database. For example, if moving data from MySQL, TCP port 3306 must be open.	TCP	Outbound port from the Hadoop cluster to the database. Varies depending on Database	No	

1.16. Storm Service Ports

The following table lists the default ports used by Storm.

Table 1.16. Storm Service Ports

Service	Servers	Default Port	Default Ambari Port	Protocol	Description	Need End User Access?	Configuration Parameters
Zookeeper Port		2181			Port used by localhost to talk to ZooKeeper.		storm.zookeeper.port
DRPC Port		3772					drpc.port
DRPC Invocations Port		3773					drpc.invocations.port
Nimbus Thrift Port		6627					nimbus.thrift.port
Supervisor Slots Ports		6700, 6701, 6702, 6703			Defines the amount of workers that can be run on this machine. Each worker is assigned a port to use for communication.		supervisor.slots.ports
Logviewer Port		8000					logviewer.port
UI Port		8080	8744				ui.port

1.17. Tez Ports

The following table lists the default ports used by the various Tez services.

Table 1.17. Tez Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Tez AM, Tez Service		12999		Port to use for AMPoolService status	Yes (Clients who need to submit Hive queries or jobs to Tez AM or Tez Service) Yes	tez.ampool.ws.port
		10030	http	Address on which to run the ClientRMProtocol proxy.		tez.ampool.address

1.18. YARN Service Ports

The following table lists the default ports used by the various YARN services.

Table 1.18. YARN Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
Resource Manager WebUI	Master Nodes (Resource Manager and any back-up Resource Manager node)	8088	http	Web UI for Resource Manager	Yes	yarn.resourcemanager.webapp.address
Resource Manager	Master Nodes (Resource Manager Node)	8050	IPC	For application submissions	Yes (All clients who need to submit the YARN applications including Hive, Hive server, Pig)	Embedded in URI specified by yarn.resourcemanager.address
Resource Manager	Master Nodes (Resource Manager Node)	8025	http	For application submissions	Yes (All clients who need to submit the YARN applications including Hive, Hive server, Pig)	yarn.resourcemanager.resource-tracker.address
Scheduler	Master Nodes (Resource Manager Node)	8030	http	Scheduler Address	Yes (Typically admins, Dev/	yarn.resourcemanager.scheduler.address

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
					Support teams)	
Resource Manager	Master Nodes (Resource Manager Node)	8141	http	Scheduler Address	Yes (Typically admins, Dev/ Support teams)	yarn.resourcemanager.admin.address
NodeManager	Master Nodes (NodeManager) and Slave Nodes	45454	http	NodeManager Address	Yes (Typically admins, Dev/ Support teams)	yarn.nodemanager.address
Timeline Server	Master Nodes	10200	http	Timeline Server Address	Yes (Typically admins, Dev/ Support teams)	yarn.timeline-service.address
Timeline Server	Master Nodes	8188	http	Timeline Server Webapp Address	Yes (Typically admins, Dev/ Support teams)	yarn.timeline-service.webapp.address
Timeline Server	Master Nodes	8190	https	Timeline Server Webapp https Address	Yes (Typically admins, Dev/ Support teams)	yarn.timeline-service.webapp.https.address
Job History Service	Master Nodes	19888	https	Job History Service	Yes (Typically admins, Dev/ Support teams)	yarn.log.server.url

1.19. ZooKeeper Service Ports

Table 1.19. ZooKeeper Service Ports

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
ZooKeeper Server	All ZooKeeper Nodes	2888		Port used by ZooKeeper peers to talk to each other. See here for more information.	No	hbase.zookeeper.peerport
ZooKeeper Server	All ZooKeeper Nodes	3888		Port used by ZooKeeper peers to talk to each other. See	No	hbase.zookeeper.leaderport

Service	Servers	Default Ports Used	Protocol	Description	Need End User Access?	Configuration Parameters
				here for more information.		
ZooKeeper Server	All ZooKeeper Nodes	2181		Property from ZooKeeper's config zoo.cfg. The port at which the clients will connect.	No	hbase.zookeeper.property.clientPort

2. Controlling HDP Services Manually

In this document:

- [Starting HDP Services](#)
- [Stopping HDP Services](#)

2.1. Starting HDP Services

Start the Hadoop services in the following order:

- Ranger
- Knox
- ZooKeeper
- HDFS
- YARN
- HBase
- Hive Metastore
- HiveServer2
- WebHCat
- Oozie
- Storm
- Kafka

Instructions

1. Start Ranger. Execute the following commands on the Ranger host machine:

```
sudo service ranger-admin start
sudo service ranger-usersync start
```

2. Start Knox. When starting the gateway with the script below, the process runs in the background. The log output is written to `/var/log/knox` and a PID (process ID) is written to `/var/run/knox`. Execute this command on the Knox host machine.

```
su -l knox -c "/usr/hdp/current/knox-server/bin/gateway.sh start"
```



Note

If Knox has been stopped without using `gateway.sh stop`, you must start the service using `gateway.sh clean`. The clean option removes all log files in `/var/log/knox`.

3. Start ZooKeeper. Execute this command on the ZooKeeper host machine(s):

```
su - zookeeper -c "export ZOO_CFG_DIR=/usr/hdp/current/zookeeper-server/conf ; export ZOO_CFG=zoo.cfg; source /usr/hdp/current/zookeeper-server/conf/zookeeper-env.sh ; /usr/hdp/current/zookeeper-server/bin/zkServer.sh start"
```

4. Start HDFS

- If you are running NameNode HA (High Availability), start the JournalNodes by executing these commands on the JournalNode host machines:

```
su $HDFS_USER  
/usr/hdp/current/hadoop-hdfs-journalnode/./hadoop/sbin/hadoop-daemon.sh  
start journalnode
```

where \$HDFS_USER is the HDFS user. For example, hdfs.

- Execute this command on the NameNode host machine(s):

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh start namenode"
```

- If you are running NameNode HA, start the Zookeeper Failover Controller (ZKFC) by executing the following command on all NameNode machines. The starting sequence of the ZKFCs determines which NameNode will become Active.

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh start zkfc"
```

- If you are not running NameNode HA, execute the following command on the Secondary NameNode host machine. If you are running NameNode HA, the Standby NameNode takes on the role of the Secondary NameNode.

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh start secondarynamenode"
```

- Execute these commands on all DataNodes:

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-datanode/./hadoop/sbin/  
hadoop-daemon.sh start datanode"
```

5. Start YARN

- Execute this command on the ResourceManager host machine(s):

```
su -l yarn -c "/usr/hdp/current/hadoop-yarn-resourcemanager/sbin/yarn-  
daemon.sh start resourcemanager"
```

- Execute this command on the History Server host machine:

```
su -l yarn -c "/usr/hdp/current/hadoop-mapreduce-historyserver/sbin/mr-  
jobhistory-daemon.sh start historyserver"
```

- Execute this command on all NodeManagers:

```
su -l yarn -c "/usr/hdp/current/hadoop-yarn-nodemanager/sbin/yarn-daemon.  
sh start nodemanager"
```

6. Start HBase

- Execute this command on the HBase Master host machine:

```
su -l hbase -c "/usr/hdp/current/hbase-master/bin/hbase-daemon.sh start master; sleep 25"
```

- Execute this command on all RegionServers:

```
su -l hbase -c "/usr/hdp/current/hbase-regionserver/bin/hbase-daemon.sh start regionserver"
```

7. Start the Hive Metastore. On the Hive Metastore host machine, execute the following commands:

```
su $HIVE_USER  
nohup /usr/hdp/current/hive-metastore/bin/hive --service metastore>/var/log/hive/hive.out 2>/var/log/hive/hive.log &
```

Where \$HIVE_USER is the Hive user. For example, hive.

8. Start HiveServer2. On the Hive Server2 host machine, execute the following commands:

```
su $HIVE_USER nohup /usr/hdp/current/hive-server2/bin/hiveserver2 -hiveconf hive.metastore.uris=/tmp/hiveserver2HD.out 2 /tmp/hiveserver2HD.log
```

Where \$HIVE_USER is the Hive user. For example, hive.

9. Start WebHCat. On the WebHCat host machine, execute the following command:

```
su -l hcat -c "/usr/hdp/current/hive-webhcat/sbin/webhcat_server.sh start"
```

- 10 Start Oozie. Execute the following command on the Oozie host machine:

```
su -l oozie -c "/usr/hdp/current/oozie-server/bin/oozied.sh start"
```

- 11 Start Storm services using a process controller, such as supervisorctl. See "Installing and Configuring Apache Storm" in the [Non-Ambari Cluster Installation Guide](#). For example, to start the storm-nimbus service:

```
sudo /usr/bin/supervisorctl  
storm-drpc RUNNING pid 9801, uptime 0:05:05  
storm-nimbus STOPPED Dec 01 06:18 PM  
storm-ui RUNNING pid 9800, uptime 0:05:05  
supervisor> start storm-nimbus  
storm-nimbus: started
```

where \$STORM_USER is the operating system user that installed Storm. For example, storm.

- 12 Start Kafka with the following commands:

```
su $KAFKA_USER  
/usr/hdp/current/kafka-broker/bin/kafka start
```

where \$KAFKA_USER is the operating system user that installed Kafka. For example, kafka.

2.2. Stopping HDP Services

Before performing any upgrades or uninstalling software, stop all of the Hadoop services in the following order:

- Ranger
- Knox
- Oozie
- WebHCat
- HiveServer2
- Hive Metastore
- HBase
- YARN
- HDFS
- Zookeeper
- Storm
- Kafka

Instructions

1. Stop Ranger. Execute the following commands on the Ranger host machine:

```
sudo service ranger-admin stop
sudo service ranger-usersync stop
```

2. Stop Knox. Execute the following command on the Knox host machine.

```
su -l knox -c "/usr/hdp/current/knox-server/bin/gateway.sh stop"
```

3. Stop Oozie. Execute the following command on the Oozie host machine.

```
su -l oozie -c "/usr/hdp/current/oozie-server/bin/oozied.sh stop"
```

4. Stop WebHCat. On the WebHCat host machine, execute the following command:

```
su -l hcat -c "/usr/hdp/current/hive-webhcat/sbin/webhcat_server.sh stop"
```

5. Stop Hive. Execute this command on the Hive Metastore and Hive Server2 host machine.

```
ps aux | awk '{print $1,$2}' | grep hive | awk '{print $2}' | xargs kill >/dev/null 2>&1
```

6. Stop HBase

- Execute this command on all RegionServers:

```
su -l hbase -c "/usr/hdp/current/hbase-regionserver/bin/hbase-daemon.sh  
stop regionserver"
```

- Execute this command on the HBase Master host machine:

```
su -l hbase -c "/usr/hdp/current/hbase-master/bin/hbase-daemon.sh stop  
master"
```

7. Stop YARN

- Execute this command on all NodeManagers:

```
su -l yarn -c "/usr/hdp/current/hadoop-yarn-nodemanager/sbin/yarn-daemon.  
sh stop nodemanager"
```

- Execute this command on the History Server host machine:

```
su -l yarn -c "/usr/hdp/current/hadoop-mapreduce-historyserver/sbin/mr-  
jobhistory-daemon.sh stop historyserver"
```

- Execute this command on the ResourceManager host machine(s):

```
su -l yarn -c "/usr/hdp/current/hadoop-yarn-resourcemanager/sbin/yarn-  
daemon.sh stop resourcemanager"
```

8. Stop HDFS

- Execute this command on all DataNodes:

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-datanode/./hadoop/sbin/  
hadoop-daemon.sh stop datanode"
```

- If you are not running NameNode HA (High Availability), stop the Secondary NameNode by executing this command on the Secondary NameNode host machine:

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh stop secondarynamenode"
```

- Execute this command on the NameNode host machine(s):

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh stop namenode"
```

- If you are running NameNode HA, stop the Zookeeper Failover Controllers (ZKFC) by executing this command on the NameNode host machines:

```
su -l hdfs -c "/usr/hdp/current/hadoop-hdfs-namenode/./hadoop/sbin/  
hadoop-daemon.sh stop zkfc"
```

- If you are running NameNode HA, stop the JournalNodes by executing these commands on the JournalNode host machines:

```
su $HDFS_USER  
/usr/hdp/current/hadoop-hdfs-journalnode/./hadoop/sbin/hadoop-daemon.sh  
stop journalnode
```

where \$HDFS_USER is the HDFS user. For example, hdfs.

9. Stop ZooKeeper. Execute this command on the ZooKeeper host machine(s):

```
su - zookeeper -c "export ZOOCFGDIR=/usr/hdp/current/zookeeper-server/
conf ; export ZOOCFG=zoo.cfg; source /usr/hdp/current/zookeeper-server/conf/
zookeeper-env.sh ; /usr/hdp/current/zookeeper-server/bin/zkServer.sh stop"
```

10 Start Storm services using a process controller, such as supervisord. See "Installing and Configuring Apache Storm" in the [Non-Ambari Cluster Installation Guide](#). For example, to stop the storm-nimbus service:

```
sudo /usr/bin/supervisorctl
storm-drpc RUNNING pid 9801, uptime 0:03:20
storm-nimbus RUNNING pid 9802, uptime 0:03:20
storm-ui RUNNING pid 9800, uptime 0:03:20
supervisor> stop storm-nimbus
storm-nimbus: stopped
```

where \$STORM_USER is the operating system user that installed Storm. For example, storm.

11 Stop Kafka. Execute this command on the Kafka host machine(s):

```
su $KAFKA_USER
/usr/hdp/current/kafka-broker/bin/kafka stop
```

where \$KAFKA_USER is the operating system user that installed Kafka. For example, kafka.

3. Deploying HDP In Production Data Centers With Firewalls

A typical Hortonworks Data Platform (HDP) install requires access to the Internet in order to fetch software packages from a remote repository. Because corporate networks typically have various levels of firewalls, these firewalls may limit or restrict Internet access, making it impossible for your cluster nodes to access the HDP repository during the install process.

The solution for this is to either:

- Create a local mirror repository inside your firewall hosted on a local mirror server inside your firewall; or
- Provide a trusted proxy server inside your firewall that can access the hosted repositories.



Note

Many of the descriptions in this section assume you are using RHEL/Centos/Oracle Linux. If you are using SLES, please adjust the commands and directories accordingly.

This document will cover these two options in detail, discuss the trade-offs, provide configuration guidelines, and will also provide recommendations for your deployment strategy.

In general, before installing Hortonworks Data Platform in a production data center, it is best to ensure that both the Data Center Security team and the Data Center Networking team are informed and engaged to assist with these aspects of the deployment.

3.1. Terminology

The table below lists the various terms used throughout this section.

Table 3.1. Terminology

Item	Description
Yum Package Manager (yum)	A package management tool that fetches and installs software packages and performs automatic dependency resolution.
Local Mirror Repository	The yum repository hosted on your Local Mirror Server that will serve the HDP software.
Local Mirror Server	The server in your network that will host the Local Mirror Repository. This server must be accessible from all hosts in your cluster where you will install HDP.
HDP Repositories	A set of repositories hosted by Hortonworks that contains the HDP software packages. HDP software packages include the HDP Repository and the HDP-UTILS Repository.
HDP Repository Tarball	A tarball image that contains the complete contents of the HDP Repositories.

3.2. Mirroring or Proxying

HDP uses yum or zypper to install software, and this software is obtained from the HDP Repositories. If your firewall prevents Internet access, you must mirror or proxy the HDP Repositories in your Data Center.

Mirroring a repository involves copying the entire repository and all its contents onto a local server and enabling an HTTPD service on that server to serve the repository locally. Once the local mirror server setup is complete, the *.repo configuration files on every cluster node must be updated, so that the given package names are associated with the local mirror server instead of the remote repository server.

There are two options for creating a local mirror server. Each of these options is explained in detail in a later section.

- **Mirror server has no access to Internet at all:** Use a web browser on your workstation to download the HDP Repository Tarball, move the tarball to the selected mirror server using scp or an USB drive, and extract it to create the repository on the local mirror server.
- **Mirror server has temporary access to Internet:** Temporarily configure a server to have Internet access, download a copy of the HDP Repository to this server using the reposync command, then reconfigure the server so that it is back behind the firewall.



Note

Option I is probably the least effort, and in some respects, is the most secure deployment option.

Option III is best if you want to be able to update your Hadoop installation periodically from the Hortonworks Repositories.

- **Trusted proxy server:** Proxying a repository involves setting up a standard HTTP proxy on a local server to forward repository access requests to the remote repository server and route responses back to the original requestor. Effectively, the proxy server makes the repository server accessible to all clients, by acting as an intermediary.

Once the proxy is configured, change the `/etc/yum.conf` file on every cluster node, so that when the client attempts to access the repository during installation, the request goes through the local proxy server instead of going directly to the remote repository server.

3.3. Considerations for choosing a Mirror or Proxy solution

The following table lists some benefits provided by these alternative deployment strategies:

Advantages of repository mirroring	Advantages of creating a proxy
Minimizes network access (after the initial investment of copying the repository to local storage). The install process is therefore faster, reliable, and more cost effective (reduced WAN bandwidth minimizes the data center	Avoids the need for long term management of the repository files (including periodic updates for upgrades, new versions, and bug fixes). Almost all data centers already have a setup of well-known proxies. In such cases,

Advantages of repository mirroring	Advantages of creating a proxy
costs). Allows security-conscious data centers to qualify a fixed set of repository files. It also ensures that the remote server will not change these repository files. Large data centers may already have existing repository mirror servers for the purpose of OS upgrades and software maintenance. You can easily add the HDP Repositories to these existing servers.	you can simply add the local proxy server to the existing proxies configurations. This approach is easier compared to creating local mirror servers in data centers with no mirror server setup. The network access is same as that required when using a mirror repository, but the source repository handles file management.

However, each of the above approaches are also known to have the following disadvantages:

- Mirrors have to be managed for updates, upgrades, new versions, and bug fixes.
- Proxy servers rely on the repository provider to not change the underlying files without notice.
- Caching proxies are necessary, because non-caching proxies do not decrease WAN traffic and do not speed up the install process.

3.4. Recommendations for Deploying HDP

This section provides information on the various components of the Apache Hadoop ecosystem.

In many data centers, using a mirror for the HDP Repositories can be the best deployment strategy. The HDP Repositories are small and easily mirrored, allowing you secure control over the contents of the Hadoop packages accepted for use in your data center.



Note

The installer pulls many packages from the base OS repositories (repos). If you do not have a complete base OS available to all your machines at the time of installation, you may run into issues. If you encounter problems with base OS repos being unavailable, please contact your system administrator to arrange for these additional repos to be proxied or mirrored.

3.5. RPMs in the HDP repository

In the HDP repository, you will find two different source RPM for each component.

For example, for Hadoop, you should find the following two RPMs:

- `hadoop-x.x.x.el6.src.rpm`
- `hadoop-source-x.x.x.el6.i386.rpm`

Two different packages serve the following purpose:

- The `src` package is used to re-create the binary in a given environment. You can use the `src` package of a particular component if you want to rebuild RPM for that component.
- The source package on the other hand, is used for reference or debugging purpose. The source package is particularly useful when you want to examine the source code of a particular component in a deployed cluster.

3.6. Detailed Instructions for Creating Mirrors and Proxies

3.6.1. Option I - Mirror server has no access to the Internet

Complete the following instructions to set up a mirror server that has no access to the Internet:

1. Check Your Prerequisites.

Select a mirror server host with the following characteristics:

- This server runs on either CentOS (v5.x, v6.x), RHEL (v5.x, v6.x), Oracle Linux(v5.x, v6.x), SLES 11, or Ubuntu 12, and has several GB of storage available.
- This server and the cluster nodes are all running the same OS.



Note

To support repository mirroring for heterogeneous clusters requires a more complex procedure than the one documented here.

- The firewall lets all cluster nodes (the servers on which you want to install HDP) access this server

2. Install the Repos.

- Use a workstation with access to the Internet and download the tarball image of the appropriate Hortonworks yum repository.

Table 3.2. Hortonworks Yum Repositories

Cluster OS	HDP Repository Tarballs
RHEL/CentOs/Oracle Linux 6.x	wget http://public-repo-1.hortonworks.com/HDP/centos6/2.x/updates/2.3.4.0/HDP-2.3.4.0-centos6-rpm.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/centos6/HDP-UTILS-1.1.0.20-centos6.tar.gz
RHEL/CentOs/Oracle Linux 7.x	wget http://public-repo-1.hortonworks.com/HDP/centos7/2.x/updates/2.3.4.0/HDP-2.3.4.0-centos7-rpm.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/centos7/HDP-UTILS-1.1.0.20-centos7.tar.gz
SLES 11 SP3	wget http://public-repo-1.hortonworks.com/HDP/suse11sp3/2.x/updates/2.3.4.0/HDP-2.3.4.0-suse11sp3-rpm.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/suse11sp3/HDP-UTILS-1.1.0.20-suse11sp3.tar.gz

Cluster OS	HDP Repository Tarballs
Ubuntu 12.04	wget http://public-repo-1.hortonworks.com/HDP/ubuntu12/2.x/updates/2.3.4.0/HDP-2.3.4.0-ubuntu12-deb.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/ubuntu12/HDP-UTILS-1.1.0.20-ubuntu12.tar.gz
Ubuntu 14	wget http://public-repo-1.hortonworks.com/HDP/ubuntu14/2.x/updates/2.3.4.0/HDP-2.3.4.0-ubuntu14-deb.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/ubuntu14/HDP-UTILS-1.1.0.20-ubuntu14.tar.gz
Debian 6	wget http://public-repo-1.hortonworks.com/HDP/debian6/2.x/updates/2.3.4.0/HDP-2.3.4.0-debian6-deb.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/debian6/HDP-UTILS-1.1.0.20-debian6.tar.gz
Debian 7	wget http://public-repo-1.hortonworks.com/HDP/debian7/2.x/updates/2.3.4.0/HDP-2.3.4.0-debian7-deb.tar.gz wget http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.20/repos/debian7/HDP-UTILS-1.1.0.20-debian7.tar.gz

b. Create an HTTP server.

- On the mirror server, install an HTTP server (such as Apache httpd) using the instructions provided [here](#).
- Activate this web server.
- Ensure that the firewall settings (if any) allow inbound HTTP access from your cluster nodes to your mirror server.



Note

If you are using EC2, make sure that SELinux is disabled.

If you are using EC2, make sure that SELinux is disabled.

c. On your mirror server, create a directory for your web server.

- For example, from a shell window, type:

- **For RHEL/CentOS/Oracle:**

```
mkdir -p /var/www/html/hdp/
```

- **For SLES:**

```
mkdir -p /srv/www/htdocs/rpms
```

- **For Ubuntu:**

```
mkdir -p /var/www/html/hdp/
```

- If you are using a symlink, enable the `followsymlinks` on your web server.
- d. Copy the HDP Repository Tarball to the directory created in step 3, and untar it.
- e. Verify the configuration.

- The configuration is successful, if you can access the above directory through your web browser.

To test this out, browse to the following location: `http://$yourwebserver/hdp/$os/HDP-2.3.4.0/`.

You should see directory listing for all the HDP components along with the RPMs at: `$os/HDP-2.3.4.0`.



Note

If you are installing a 2.x.0 release, use: `http://$yourwebserver/hdp/$os/2.x/GA`

If you are installing a 2.x.x release, use: `http://$yourwebserver/hdp/$os/2.x/updates`

where

- `$os` can be `centos5`, `centos6`, `suse11`, or `ubuntu12`. Use the following options table for `$os` parameter:

Table 3.3. HDP Component Options

Operating System	Value
CentOS 5	centos5
RHEL 5	
Oracle Linux 5	
CentOS 6	centos6
RHEL 6	
Oracle Linux	
SLES 11	suse11
Ubuntu 12	ubuntu12

- f. Configure the yum clients on all the nodes in your cluster.

- Fetch the yum configuration file from your mirror server.

```
http://$yourwebserver/hdp/$os/2.x/updates/2.3.4.0/hdp.repo
```

- Store the `hdp.repo` file to a temporary location.
- Edit the `hdp.repo` file changing the value of the `base url` property to point to your local repositories based on your cluster OS.

where

- \$yourwebserver is the FQDN of your local mirror server.
- \$os can be centos5, centos6, suse11, or ubuntu12. Use the following options table for \$os parameter:

Table 3.4. Yum Client Options

Operating System	Value
CentOS 5	centos5
RHEL 5	
Oracle Linux 5	
CentOS 6	centos6
RHEL 6	
Oracle Linux 6	
Ubuntu 12	ubuntu12

- Use scp or pdsh to copy the client yum configuration file to `/etc/yum.repos.d/` directory on every node in the cluster.
- [Conditional]: If you have multiple repositories configured in your environment, deploy the following plugin on all the nodes in your cluster.
- Install the plugin.
 - **For RHEL and CentOS v5.x**

```
yum install yum-priorities
```

- **For RHEL and CentOS v6.x**

```
yum install yum-plugin-priorities
```

- Edit the `/etc/yum/pluginconf.d/priorities.conf` file to add the following:

```
[main]
enabled=1
gpgcheck=0
```

3.6.2. Option II - Mirror server has temporary or continuous access to the Internet

Complete the following instructions to set up a mirror server that has temporary access to the Internet:

1. Check Your Prerequisites.

Select a local mirror server host with the following characteristics:

- This server runs on either CentOS/RHEL/Oracle Linux 5.x or 6.x, or Ubuntu 12, and has several GB of storage available.

- The local mirror server and the cluster nodes must have the same OS. If they are not running CentOS or RHEL, the mirror server must not be a member of the Hadoop cluster.



Note

To support repository mirroring for heterogeneous clusters requires a more complex procedure than the one documented here.

To support repository mirroring for heterogeneous clusters requires a more complex procedure than the one documented here.

- The firewall allows all cluster nodes (the servers on which you want to install HDP) to access this server.
- Ensure that the mirror server has yum installed.
- Add the yum-utils and createrepo packages on the mirror server.

```
yum install yum-utils createrepo
```

2. Install the Repos.

- Temporarily reconfigure your firewall to allow Internet access from your mirror server host.
- Execute the following command to download the appropriate Hortonworks yum client configuration file and save it in `/etc/yum.repos.d/` directory on the mirror server host.

Table 3.5. Yum Client Configuration Commands

Cluster OS	HDP Repository Tarballs
RHEL/CentOS/Oracle Linux 6.x	<code>wget http://public-repo-1.hortonworks.com/HDP/centos6/2.x/updates/2.3.4.0/hdp.repo -O /etc/yum.repos.d/hdp.repo</code>
RHEL/CentOS/Oracle Linux 7.x	<code>wget http://public-repo-1.hortonworks.com/HDP/centos7/2.x/updates/2.3.4.0/hdp.repo -O /etc/yum.repos.d/hdp.repo</code>
SLES 11 SP3	<code>wget http://public-repo-1.hortonworks.com/HDP/suse11sp3/2.x/updates/2.3.4.0/hdp.repo -O /etc/zypp/repos.d/hdp.repo</code>
Ubuntu 12.04	<code>wget http://public-repo-1.hortonworks.com/HDP/ubuntu12/2.x/updates/2.3.4.0/hdp.list -O /etc/apt/sources.list.d/hdp.list</code>
Ubuntu 14	<code>wget http://public-repo-1.hortonworks.com/HDP/ubuntu14/2.x/updates/2.3.4.0/hdp.list -O /etc/apt/sources.list.d/hdp.list</code>
Debian 6	<code>wget http://public-repo-1.hortonworks.com/HDP/debian6/2.x/</code>

Cluster OS	HDP Repository Tarballs
	updates/2.3.4.0/hdp.list -0 /etc/apt/sources.list.d/hdp.list
Debian 7	wget http://public-repo-1.hortonworks.com/HDP/debian7/2.x/updates/2.3.4.0/hdp.list -0 /etc/apt/sources.list.d/hdp.list

- Create an HTTP server.
- On the mirror server, install an HTTP server (such as Apache httpd using the instructions provided)
- Activate this web server.
- Ensure that the firewall settings (if any) allow inbound HTTP access from your cluster nodes to your mirror server.



Note

If you are using EC2, make sure that SELinux is disabled.

- Optional - If your mirror server uses SLES, modify the default-server.conf file to enable the docs root folder listing.

```
sed -e s/Options None/Options Indexes MultiViews/ig /etc/apache2/default-server.conf /tmp/tempfile.tmp
mv /tmp/tempfile.tmp /etc/apache2/default-server.conf
```

- On your mirror server, create a directory for your web server.
- For example, from a shell window, type:
 - **For RHEL/CentOS/Oracle:**

```
mkdir -p /var/www/html/hdp/
```
 - **For SLES:**

```
mkdir -p /srv/www/htdocs/rpms
```
 - **For Ubuntu and Debian:**

```
mkdir -p /var/www/html/hdp/
```
- If you are using a symlink, enable the followsymlinks on your web server.
- Copy the contents of entire HDP repository for your desired OS from the remote yum server to your local mirror server.
- Continuing the previous example, from a shell window, type:
 - **For RHEL/CentOS/Oracle/Ubuntu:**

```
cd /var/www/html/hdp
```
 - **For SLES:**

```
cd /srv/www/htdocs/rpms
```

Then for all hosts, type:

- **HDP Repository**

```
reposync -r HDP reposync -r HDP-2.3.4.0 reposync -r HDP-UTILS-1.1.0.20
```

You should see both an HDP-2.3.4.0 directory and an HDP-UTILS-1.1.0.20 directory, each with several subdirectories.

- Generate appropriate metadata.

This step defines each directory as a yum repository. From a shell window, type:

- For RHEL/CentOS/Oracle:

- **HDP Repository:**

```
createrepo /var/www/html/hdp/HDP-2.3.4.0 createrepo /var/www/html/hdp/HDP-UTILS-1.1.0.20
```

- For SLES:

- **HDP Repository:**

```
createrepo /srv/www/htdocs/rpms/hdp/HDP
```

You should see a new folder called repodata inside both HDP directories.

- Verify the configuration.
 - The configuration is successful, if you can access the above directory through your web browser.

To test this out, browse to the following location:

- HDP: `http://$yourwebserver/hdp/HDP-2.3.4.0/`
- You should now see directory listing for all the HDP components.
- At this point, you can disable external Internet access for the mirror server, so that the mirror server is again entirely within your data center firewall.
- Depending on your cluster OS, configure the yum clients on all the nodes in your cluster
 - Edit the repo files, changing the value of the `baseurl` property to the local mirror URL.
 - Edit the `/etc/yum.repos.d/hdp.repo` file, changing the value of the `baseurl` property to point to your local repositories based on your cluster OS.

```

name=Hortonworks Data Platform Version - HDP-2.x baseurl=http://
$yourwebserver/hdp/$os/2.x/GA
gpgcheck=1
gpgkey=http://public-repo-1.hortonworks.com/HDP/$os/RPM-GPG-KEY/RPM-
GPG-KEY-Jenkins
enabled=1
priority=1

[HDP-UTILS-1.1.0.20]
name=Hortonworks Data Platform Utils Version - HDP-UTILS-1.1.0.20
baseurl=http://$yourwebserver/HDP-UTILS-1.1.0.20/repos/$os
gpgcheck=1
gpgkey=http://public-repo-1.hortonworks.com/HDP/$os/RPM-GPG-KEY/RPM-
GPG-KEY-Jenkins
enabled=1
priority=1

[HDP-2.1.5.0]
name=Hortonworks Data Platform HDP-2.3.4.0 baseurl=http://
$yourwebserver/hdp/$os /2.x/updates/2.3.4.0
gpgcheck=1
gpgkey=http://public-repo-1.hortonworks.com/HDP/$os/RPM-GPG-KEY/RPM-
GPG-KEY-Jenkins
enabled=1
priority=1

```

where

- \$yourwebserver is the FQDN of your local mirror server.
- \$os can be centos5, centos6, or suse11. Use the following options table for \$os parameter:

Table 3.6. \$OS Parameter Values

Operating System	Value
CentOS 5	centos5
RHEL 5	
Oracle Linux 5	
CentOS 6	centos6
RHEL 6	
Oracle Linux 6	
SLES 11	suse11
Ubuntu12	ubuntu12

- Copy the yum/zypper client configuration file to all nodes in your cluster.
- RHEL/CentOS/Oracle Linux:

Use scp or pdsh to copy the client yum configuration file to `/etc/yum.repos.d/` directory on every node in the cluster.

- For SLES:

On every node, invoke the following command:

- **HDP Repository:**

```
zypper addrepo -r http://$yourwebserver/hdp/suse11sp3/2.x/updates/  
2.3.4.0/hdp.repo
```

- For Ubuntu:

On every node, invoke the following command:

- **HDP Repository:**

```
sudo add-apt-repository deb http://$yourwebserver/hdp/ubuntu12/2.  
x/hdp.list
```

- **Optional - Ambari Repository:**

```
sudo add-apt-repository deb http://$yourwebserver/hdp/ambari/  
ubuntu12/1.x/updates/1.7.0/ambari.list
```

- If using Ambari, verify the configuration by deploying Ambari server on one of the cluster nodes.

```
yum install ambari-server
```

- If your cluster runs CentOS, Oracle, or RHEL and if you have multiple repositories configured in your environment, deploy the following plugin on all the nodes in your cluster.

- Install the plugin.

- **For RHEL and CentOS v5.x**

```
yum install yum-priorities
```

- **For RHEL and CentOS v6.x**

```
yum install yum-plugin-priorities
```

- Edit the `/etc/yum/pluginconf.d/priorities.conf` file to add the following:

```
[main]  
enabled=1  
gpgcheck=0
```

3.7. Set up a trusted proxy server

Complete the following instructions to set up a trusted proxy server:

1. Check Your Prerequisites.

Select a mirror server host with the following characteristics:

- This server runs on either CentOS/RHEL/Oracle Linux (5.x or 6.x), SLES 11, or Ubuntu 12, and has several GB of storage available.

- The firewall allows all cluster nodes (the servers on which you want to install HDP) to access this server, and allows this server to access the Internet (at least those Internet servers for the repositories to be proxied)Install the Repos

2. Create a caching HTTP Proxy server on the selected host.

- It is beyond the scope of this document to show how to set up an HTTP PROXY server, given the many variations that may be required, depending on your data center's network security policy. If you choose to use the Apache HTTPD server, it starts by installing *httpd*, using the instructions provided [here](#) , and then adding the *mod_proxy* and *mod_cache* modules, as stated [here](#). Please engage your network security specialists to correctly set up the proxy server.
- Activate this proxy server and configure its cache storage location.
- Ensure that the firewall settings (if any) allow inbound HTTP access from your cluster nodes to your mirror server, and outbound access to the desired repo sites, including: public-repo-1.hortonworks.com.

If you are using EC2, make sure that SELinux is disabled.

- Depending on your cluster OS, configure the yum clients on all the nodes in your cluster.

The following description is taken from the CentOS documentation. On each cluster node, add the following lines to the `/etc/yum.conf` file. (As an example, the settings below will enable yum to use the proxy server mycache.mydomain.com, connecting to port 3128, with the following credentials: yum-user/query.

- ```
proxy server:port number
proxy=http://mycache.mydomain.com:3128

account details for secure yum proxy connections
proxy_username=yum-user
proxy_password=qwerty
```
- Once all nodes have their `/etc/yum.conf` file updated with appropriate configuration info, you can proceed with the HDP installation just as though the nodes had direct access to the Internet repositories.
- If this proxy configuration does not seem to work, try adding a `/` at the end of the proxy URL. For example:  

```
proxy=http://mycache.mydomain.com:3128/
```

## 4. Hadoop Service Accounts

To configure Hadoop service accounts, see the "Create System Users and Groups" section of the "Getting Ready to Install" chapter of the [HDP Installation Guide for Non-Ambari Managed Clusters](#).

## 5. Supported Database Matrix for the Hortonworks Data Platform

This section contains certification information on supported databases for the Hortonworks Data Platform (HDP).



### Important

It is required that you optimize relational databases that are used with each component for **high availability** by using the best practices for the database you choose to use.

The following table identifies the supported databases for HDP.

**Table 5.1. Supported HDP Databases**

| Operating System                                                                                                                            | Component       | Database                                                                                                                                                                                                                                                       | Database                                                                                                                                                                                                                                                       | Database                                                                                                                                                                                                                                                  | Database                                                                                                                                                                                                                                                   | Other           |
|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 64-bit versions                                                                                                                             |                 | PostgreSQL 8.x                                                                                                                                                                                                                                                 | PostgreSQL 9.x                                                                                                                                                                                                                                                 | MySQL 5.x                                                                                                                                                                                                                                                 | Oracle 11g R2, 12c                                                                                                                                                                                                                                         |                 |
| RHEL/CentOS/Oracle Linux 6.x, RHEL/CentOS/Oracle Linux 7.x, SLES 11 SP3, Debian 6 and Ubuntu 12.04 (HDP 2.3 first maintenance release only) | Hive / HCatalog | Supported. For instructions on how to configure this database for the Hive metastore, refer to the "Installing Hive->Configuring Hive for an External Database->Using Hive with PostgreSQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hive metastore, refer to the "Installing Hive->Configuring Hive for an External Database->Using Hive with PostgreSQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hive metastore, refer to the "Installing Hive->Configuring Hive for an External Database->Using Hive with MySQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hive metastore, refer to the "Installing Hive->Configuring Hive for an External Database->Using Hive with Oracle" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . |                 |
|                                                                                                                                             | Oozie           | Supported. For instructions on how to configure this database for the Oozie, refer to the "Installing Oozie->Configuring Oozie for an External Database->Using Oozie with PostgreSQL"                                                                          | Supported. For instructions on how to configure this database for Oozie, refer to the "Installing Hive->Configuring Oozie for an External Database->Using Oozie with                                                                                           | Supported. For instructions on how to configure this database for Oozie, refer to the "Installing Oozie->Configuring Oozie for an External Database->Using Oozie with MySQL" section in <a href="#">Non-Ambari Cluster</a>                                | Supported. For instructions on how to configure this database for Oozie, refer to the "Installing Oozie->Configuring Oozie for an External Database->Using Oozie with Oracle"                                                                              | Derby (default) |

| Operating System | Component | Database                                                                                                                                                                                                                                     | Database                                                                                                                                                                                                                                         | Database                                                                                                                                                                                                                                              | Database                                                                                                                                                                                                                                               | Other            |
|------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
|                  |           | section in <a href="#">Non-Ambari Cluster Installation Guide</a> .                                                                                                                                                                           | PostgreSQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> .                                                                                                                                                                   | <a href="#">Installation Guide</a> .                                                                                                                                                                                                                  | section in <a href="#">Non-Ambari Cluster Installation Guide</a> .                                                                                                                                                                                     |                  |
|                  | Hue       | Supported. For instructions on how to configure this database for Hue, refer to the "Installing Hue->Configuring Hue for an External Database->Using Hue with PostgreSQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hue, refer to the "Installing Hue->Configuring Hue for an External Database->Using Hue with PostgreSQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hue metastore, refer to the "Installing Hue->Configuring Hue for an External Database->Using Hue with MySQL" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | Supported. For instructions on how to configure this database for the Hue metastore, refer to the "Installing Hue->Configuring Hue for an External Database->Using Hue with Oracle" section in <a href="#">Non-Ambari Cluster Installation Guide</a> . | SQLite (default) |
|                  | Ranger    | Default. For instructions on how to configure this database for Ranger, see "Installing Ranger" in <a href="#">Non-Ambari Cluster Installation Guide</a> , or see <a href="#">Installing Ranger Over Ambari</a> .                            | Supported. For instructions on how to configure this database for Ranger, see "Installing Ranger" in <a href="#">Non-Ambari Cluster Installation Guide</a> , or see <a href="#">Installing Ranger Over Ambari</a> .                              | Supported. For instructions on how to configure this database for Ranger, see "Installing Ranger" in <a href="#">Non-Ambari Cluster Installation Guide</a> , or see <a href="#">Installing Ranger Over Ambari</a> .                                   | Supported. For instructions on how to configure this database for Ranger, see "Installing Ranger" in <a href="#">Non-Ambari Cluster Installation Guide</a> , or see <a href="#">Installing Ranger Over Ambari</a> .                                    |                  |