



Using ECL Watch

Boca Raton Documentation Team



Using ECL Watch

Boca Raton Documentation Team

Copyright © 2016 HPCC Systems®. All rights reserved

We welcome your comments and feedback about this document via email to <docfeedback@hpccsystems.com>

Please include **Documentation Feedback** in the subject line and reference the document name, page numbers, and current Version Number in the text of the message.

LexisNexis and the Knowledge Burst logo are registered trademarks of Reed Elsevier Properties Inc., used under license.

HPCC Systems® is a registered trademark of LexisNexis Risk Data Management Inc.

Other products, logos, and services may be trademarks or registered trademarks of their respective companies.

All names and example data used in this manual are fictitious. Any similarity to actual persons, living or dead, is purely coincidental.

2016 Version 6.2.0-1

Introducing ECL Watch	4
Introduction	4
ECL Watch Home Page	5
Activity	6
ECL Event Scheduler	15
Interface in ECL Watch	16
Search Results	19
ECL Workunits	21
ECL Workunits Page	22
Using the ECL Playground	41
Files	48
Files	49
DFU Workunits Page	58
Landing Zones	65
Spray/Despray	68
XRef	80
Queries	83
Queries Page in ECL Watch	83
Operations	94
Topology	95
Disk Usage	99
Operations: Target Clusters	100
Preflight System Servers	101
Preflight Thor	104
Users Permissions	107
User Administration	107
Plug-ins	126
Ganglia in ECL Watch	127
Nagios in ECL Watch	129
Advanced Menu	131
Access the Advanced menu	132
User Details	132
Resources	135

Introducing ECL Watch

Introduction


ECL Watch is a service that runs on the Enterprise Services Platform (ESP), a middleware component on the HPCC Platform.

ECL Watch provides an interface to the HPCC system and allows you to view information and interrogate nodes to confirm all expected processes are running. It is a plug-in that is useful for Systems Administrators to check processes, examine topology, and view logs. It is useful to ECL Programmers to monitor the status of jobs and files, and other pertinent information. This provides a simple view into the system and a means to perform Workunit and data files maintenance.

ECL Watch Home Page

Click on the **ECL Watch** home page link in the navigation bar at the top of the ECL Watch page to find the **Activity**, **Scheduler**, and **Search Results** links. You can access the respective pages from the links or tabs along the top of the ECL Watch home page.

Figure 1. ECL Watch home page link



There are several icons used throughout ECL Watch. The following table describes most of the icons that you will encounter.

Icon	Definition
	System cluster
	System cluster paused
	System cluster not found
	Workunit Compiled, Completed
	Workunit Running, Compiling, Debug Running
	Workunit Failed, Aborted
	Workunit Blocked, Scheduled, Wait, Uploading Files, Debug Paused, Paused
	Workunit Archived
	Workunit Aborting
	Workunit Submitted
	Workunit Deleted.
	Workunit Unknown State

Activity


The Activity tab displays activity on all clusters in the environment. The Activity page provides access to Cluster Job Queue administration tasks such as: monitoring progress, setting priority, moving a job up or down in the queue, pausing a job, aborting a job, and pausing or resuming a queue.

When you access the ECL Watch URL, the ECL Watch Home Page displays the Activity tab. To access the Activity tab from any other page in ECL Watch click on the **ECL Watch** image at the top of any page, as shown above.

Cluster Activity

Information about your systems' clusters, and any activity on those clusters can be accessed from the ECL Watch Activity tab. Select the **Activity** tab link below the **ECL Watch** image in the navigation sub-menu. This displays the Cluster Activity tab.

Figure 2. Clusters Activity




Target/Wuid	Graph	State	Owner	Job Name
hthor		hthor.agent: queue paused; paused b...		
thor				
W20160119-092755	graph1-10	running [mythor] (1 min)	Franklin	GenData
W20160119-092807		queued(1) [blocked on thor.thor]	Franklin	GenData
W20160119-092740		blocked	Franklin	GenData
roxie				

All the system clusters display. If there is any activity on a cluster there is an icon next to the cluster to indicate some activity. In the above example the icon to expand the Thor cluster indicates there is some activity on the Thor cluster. Click the icon to expand the cluster to see the activity on that cluster.

Cluster Action Buttons

Figure 3. Cluster Action Buttons



Check the box next to a cluster to enable the Cluster Action buttons. The Cluster Action buttons will then allow you to perform the following actions on the selected cluster's job queue.

Pause

Pauses the cluster's job queue. The currently running job will complete, but no other jobs will execute until the queue is resumed.

Resume


Resumes a paused job queue. Any waiting jobs will resume execution in order.

Clear

Removes all workunits from the job queue. The removed workunits' state is then set to aborted. Any workunits that were waiting in the queue can be resubmitted manually later, if desired.

Cluster Workunit Activity

Figure 4. Workunit Activity Buttons



Workunit Action Buttons

Check the box next to a Workunit to select it and enable the Workunit Action buttons.

The enabled Workunit Action buttons will then allow you to perform the following actions on the selected Workunit(s).

Open

Opens a (workunit) tab for the selected workunit.

Pause

Press the **Pause** button to complete the current subgraph and then put the job into a paused state.

Pause Now

Press the **Pause Now** button to interrupt the current subgraph (abort it) and put the job into a paused state.

Resume

Resumes processing of any paused job.

Abort

Aborts a running job. An aborted job cannot be resumed.

High, Normal, Low

Figure 5. Priority

The screenshot shows the ECL Watch interface with the 'Activity' tab selected. The toolbar includes buttons for Refresh, Pause, Resume, Clear, Open, Stop, Abort, High, Normal, and Low. A red circle highlights the 'High', 'Normal', and 'Low' buttons. Another red circle highlights the selected job 'W20160119-135240' in the list. The table lists jobs with columns for Owner, Job Name, and Status.

Owner	Job Name	Status
Franklin	GenData	Paused [on thor.thor]
Franklin	GenData	Paused [on thor.thor]
Franklin	GenData	Paused [on thor.thor]
Franklin	GenData	Paused [on thor.thor]
Franklin	GenData	Paused [on thor.thor]
Franklin	GenData	Paused [on thor.thor]

You can raise or lower the priority of the job in the queue. Select the job, then press one of the appropriate buttons, **High** or **Low**. Typically all jobs are Normal priority by default.

Press the **High** button to raise the priority of the select job to High. Press the **Low** button to lower the priority of the processing job.

Top, Bottom, Up, Down

Figure 6. Queue Position

Owner	Job Name
Franklin	GenData

You can change the position of a job in the queue using the Top, Bottom, Up, and Down buttons.

Select the workunit to move, that will enable the action buttons.


Press the **Top** button to move the select job to the top of the processing queue. Press the **Up** button to move the job up one position in the queue. Press the **Down** button to move the job down one position in the queue. Press the **Bottom** button to move the job down to the bottom of the queue.

Cluster Information

You can access more information about your Thor clusters from the main Activity tab.

Select the target cluster from the main **Activity** tab, by checking the box next to it.


Figure 7. Open Cluster



This enables the **Open** action button. Press the Open action button to open a new tab for that cluster.


The cluster tab displays the groups on that cluster. Check the box next to the cluster group, and press the open button.

Figure 8. Open Cluster Groups



Open up the cluster group tab (for example, mythor), and select the group from the Groups tab to see the activity information on that cluster group.

Figure 9. Cluster Activity tabs



On that cluster group tab, you can access the information about that cluster. There are three tabs on that cluster group tab. The **Summary** tab provides a snapshot of that group.

Alternatively, you can click the link on the cluster name to examine.

The Cluster Usage Tab

The **Usage** tab provides access to a usage graph. The usage tab provides information about the cluster usage.

Figure 10. Usage Graph




To display the usage graph, you can enter some values in the in the fields displayed on the initial usage tab. Optionally, you can just accept the default, the values for the last 30 days. Then press the **Get Usage Graph** button to display the graph.

The Graph shows the cluster usage over time. More information about the cluster usage is specified using a color code. The column on the right breaks down the overall usage as well as the percentage during standard business hours and non-business hours. You can change these values using the fields above the chart, then press the **Get Usage Graph** button again.

Cluster Log File

The **Log File** tab is where you can view that cluster group's log.

Figure 11. Cluster Log File




The screenshot shows the ECL Watch interface with the 'Log File' tab selected. The log entries are as follows:

Time	Event ID	Timestamp	Process ID	Log Message
00000001	2014-06-27	16:32:27.071	2943	2943 "Opened log file //192.168.26.164"
00000002	2014-06-27	16:32:27.072	2943	2943 "Build community_5.1.0-trunk0[he"
00000003	2014-06-27	16:32:27.072	2943	2943 "calling initClientProcess Port 2000"
00000004	2014-06-27	16:32:27.073	2943	2943 "Found file 'thorgroup', using to f"
00000005	2014-06-27	16:32:27.074	2943	2943 "Global memory size = 1124 MB"
00000006	2014-06-27	16:32:27.074	2943	2943 "RoxieMemManager: setting memory limit to 1124 MB"

There are several log display options that you can use to filter the log file. You can filter by rows, pages, or by time. Use the filter options on the Log File tab to filter the displayed log. You can also download the log file to view offline.

Auto Refresh

Figure 12. Auto Refresh



The figure consists of two screenshots of the ECL Watch 'Activity' page. The left screenshot shows the 'Auto Refresh' button in its 'Enabled' state, with a red circle highlighting the button. The right screenshot shows the 'Auto Refresh' button in its 'Disabled' state, with a red circle highlighting the button.

The **Activity** page displays active ECL or DFU workunits either running or in the queue on your cluster. To refresh the list, press the **Refresh** button. Auto Refresh shows the list in real-time, but this feature is disabled by default.

To enable Auto Refresh, toggle the Auto Refresh button.

In an environment with a large number of active users, Auto Refresh could impact performance of your ESP server.

ECL Event Scheduler

The Event Scheduler page provides an interface to the ECL Scheduler. The ECL Scheduler interface allows you to see a list of scheduled workunits. It can also trigger an event. An Event is a case-insensitive string constant naming the event to trap.

ECL Scheduling provides a means of automating processes within ECL code or to chain processes together to work in sequence. For example, you can write ECL code that watches a landing zone for the arrival of a file, and when it arrives, sprays it to Thor, processes it, builds an index, and then adds it to a superfile.

ECL Scheduling is event-based. The ECL Scheduler monitors a Schedule list containing registered Workunits and Events and executes any Workunits associated with an Event when that Event is triggered.

Your ECL Code can execute when an Event is triggered, or can trigger an Event. If you submit code containing a **WHEN** clause, the Event and Workunit registers in the Schedule list. When that Event triggers, the Workunit compiles and executes. When the Workunit completes, ECL Scheduler removes it from the Schedule list.

For example, if you submit a Workunit using **WHEN('Event1','MyEvent', COUNT(2))** in the appropriate place, it will execute twice (the value of **COUNT**) before the ECL Scheduler removes it from the Schedule list and the Workunit is marked as completed.


For more details about both **WHEN** or **NOTIFY** or any ECL Language functions or keywords please see the ECL Language reference. A copy of which can be found online at <http://hpccsystems.com/download/docs/learning-ecl> on the HPCC Systems® web site.

Interface in ECL Watch

To access the ECL Scheduler interface in ECL Watch, click on the **Event Scheduler** link in the navigation sub-menu. The Scheduler interface displays and you can see the scheduled workunits, if any.

The list of scheduled workunits has two significant columns, the **EventName** and the **EventText**.

Figure 13. ECL Scheduler Interface



Workunit	Cluster	Job Name	Event Name
W20130410-091423	thor		CountToTen
W20130715-124455	thor		timetogo


The **EventName** is a created when scheduling a workunit. The **EventText** is an accompanying sub event.

You can trigger an event by entering the **EventName** and **Event Text** in the entry boxes and then pressing the **PushEvent** button. This is the same as triggering an event using NOTIFY.

Scheduler Workunit List

You can search scheduled workunits by cluster or event name. To filter by cluster or event name, click on the **Filter** Action button. The Filter sub-menu displays. Fill in values for the filter criteria, Eventname or Cluster, then press the **Apply** button. When you specify any Filter options, the Filter Action button displays *Filter Set*.

Figure 14. Workunits in the Scheduler Interface



Workunit	Cluster
W20130410-091423	thor
W20130715-124455	thor
W20140213-134640	thor
W20140213-135633	thor

You can sort the workunits by clicking on the column header.

To view the workunit details, click on the workunit ID (WUID) link for the workunit.

Pushing Events

The Event Scheduler allow you to trigger or "push" an event to help manage and test your scheduled jobs.

1. Press the **PushEvent** action button.

The Push Event dialog opens.

2. Enter the EventName:

The EventName is a case-insensitive string constant naming the event to trap.

See Also: EVENT

3. Enter the EventText:

The EventText is case-insensitive string constant naming the specific type of event to trap. It may contain * and ? to wildcard-match.

See Also: EVENT


4. Press the **Apply** button

This is the equivalent of

```
NOTIFY(EVENT(EventName,EventText));
```

See Also: NOTIFY, EVENT

Figure 15. PushEvent



Search Results

The **Search Results** tab displays when you perform a search. The search capabilities of ECL Watch are a very powerful tool.

Global Search

The global search box can be found on the navigation bar at the top of the ECL Watch page.

Figure 16. Global Search box



You can search ECL Workunits, DFU Workunits, Logical Files, and Queries using the global search box. The global search box also supports wild cards. To limit or filter your search results you can use keywords as displayed in the empty search box.

file: Preface the search string with *file*: to search Logical Files.

wuid: Preface the search string with *wuid*: to search only Workunit ids.

ecl: Preface the search string with *ecl*: to search only the ECL workunits.

dfu: Preface the search string with *dfu*: to search only DFU workunits.


query: Preface the search string with *query*: to search only published queries.

Examples of using the global search:

Enter *W201510** into the search box, and it will return all of the workunits from October 2015.

Enter *file:keys* into the search box, and it will return all of the logical files that contain "keys".

Figure 17. Global Search Example



ECL Workunits

ECL Watch provides information about ECL jobs and workunits. Links to pages that contain information about ECL workunits appear in the navigation bar along top of the ECL Watch page. There you will find links to ECL Workunits, simply labelled as Workunits, and you will also find the link to the ECL Playground. Not only can you find information about workunits there, but you can perform operations on workunits.

ECL Workunits Page

The ECL Workunits page contains a list of all the ECL workunits on your system. It provides access to more details about the workunits. You can also perform actions on the selected workunit using the Workunit Action buttons.

To access the workunits page click on the **ECL** icon, then click the **Workunits** link from the navigation sub-menu.

Figure 18. ECL Files

The page displays the ECL workunits on your system. Choose the **Workunits** Navigation tab to display the workunits.

Figure 19. ECL Watch Browse Workunits



Wuid	Owner	Job Name	Cluster	Roxie Cluster	State	Total Thor Time
W20130425-145253			thor		completed	56.740
W20130425-144924			hthor		completed	0.000
W20130424-122215		hello	hthor		completed	0.000
W20130423-093425		hello	hthor		completed	0.000
W20130422-162036		hello	hthor		completed	0.000
W20130422-162024		hello	hthor		completed	0.000

To further examine a workunit or to perform some action on it, you must select it. You can select the workunit by checking the check box. You can also open a work unit by double-clicking on the workunit.

Figure 20. Select ECL Workunit



Wuid	Owner	Job Name	Cluster	Roxie Cluster	State	Total Thor Time
W20130325-163432	Lock	build_index	thor	...	completed	3.566
W20130426-101917			thor	...	failed	0.000
W20130325-173531	user		thor	...	completed	0.466
W20130325-172901	user		thor	...	completed	0.463
W20130325-171413	hpccu		hthor	...	completed	0.000

When you select a workunit, the Action buttons are enabled. You can also use the Context Menu when you right-click on a workunit to perform an action on it.

You can select multiple workunits by checking the check box next to each workunit. You can also click-and-drag over the workunit check boxes to select multiple workunits. When you select multiple workunits, each workunit will open its own tab.


The Action buttons allow you to perform actions on the selected workunits.

- Press the **Open** button to open the selected workunit(s).
- Press the **Delete** button to delete selected workunit(s).
- Press the **Set to Failed** button to set the state of the selected workunit(s) to failed.
- Press the **Abort** button to stop a selected workunit that is running and abort the job.
- Press the **Protect** button to lock the selected workunit(s). This prevents it from archiving by the Sasha server.
- Press the **Unprotect** button to unlock the selected locked workunit(s).
- Press the **Reschedule** button to change a selected scheduled workunit.
- Press the **Deschedule** button to stop a selected scheduled workunit from running.
- Press the **Filter** button to display additional filter options. These options filter the displayed list of workunits.

Filter Options

You can filter the workunits displayed on the Workunits tab by clicking on the **Filter** Action button. The Filter sub-menu displays. Fill in values to specify the filter criteria, then press the **Apply** button.

Figure 21. The Filter sub-menu



The workunit filter options allow you to filter workunits using the specified criteria. Workunits can be filtered by:

- **Archived Only** - when checked, this filter will search only archived workunits.
- **WUID** - filter workunits for specific workunit ID (wuid).
- **Owner** - filter workunits for specific owners. Supports wildcards.
- **Job Name** - filter workunits by job name. Supports wildcards.
- **Cluster** - filter workunits by cluster. Select the cluster from the drop list.
- **State** - filter workunits by State. Select the state from the drop list.
- **ECL** - filter workunits by specific ECL. For example, `:=dataset`. Supports wildcards.
- **Logical File** - filter workunits by Logical File name, or some portion of it. Supports wildcards.


- **Logical File Type** - filter workunits by Logical File type. Select the Logical file type from the drop list.
- **From date** - filter workunits from a specific date and/or time. Select the date and time from the drop list.
- **To date** - filter workunits up to a specific date and/or time. Select the date and time from the drop list.
- **Last N Days** - filter workunits for a certain number (N) of days. Enter a number in this field.

Some filter fields support wild card filtering. Wildcards can substitute for one or more characters when filtering data in the filter. The wild card characters are *, and ?. Where * can substituted for all possible characters, and a ? can be substituted for any single character.

Note: Filter criteria are not case sensitive.

When you specify any Filter options, the Filter Action button displays *Filter Set*.

Figure 22. Filter Set



A screenshot of the ECL Watch interface. At the top, there is a toolbar with buttons for 'Name', 'Add To Superfile', 'Desplay', 'Filter Set' (which is circled in red), and 'File'. Below the toolbar is a table with columns: 'Name', 'Cluster', 'Records', 'Size', 'Parts', and 'Modified (UTC/'). The table contains two rows of data. The first row has 'Name' 'thor', 'Records' 127,924, 'Size' 8,104, 'Parts' 50, and 'Modified' 2016-03-07 16:33:33. The second row has 'Name' 'thor', 'Records' 127,924, 'Size' 8,104, 'Parts' 50, and 'Modified' 2016-03-07 16:33:33.

Name	Cluster	Records	Size	Parts	Modified (UTC/)
thor		127,924	8,104	50	2016-03-07 16:33:33
thor		127,924	8,104	50	2016-03-07 16:33:33

Sorting Columns

You can sort a column by clicking on the column heading. Click once for ascending, click again to toggle to descending. The direction of the arrow indicates the sort order.


Figure 23. Sort by column

	Wuid	Owner	Job Name
	W20130425-145253	earl	CleanActor
	W20130425-144924	earl	File_OriginalPerson
	W20130424-122215	earl	LayoutActors
	W20130423-093425	earl	CleanActor
	W20130422-162036	earl	CleanActor
	W20130422-162024	franklin	Layout_People
	W20130422-162014	franklin	CleanActor
	W20130422-122527	sort	ActorsInMovies

Context Menu

You can right-click on a workunit to get a context menu of actions, including filter options. These are the same set of actions that you could perform from the Action buttons.


Figure 24. Context menu



Workunit Details

The Workunit Details page provides more information about the workunit. You can see more specific information about the selected workunit by selecting the various Workunit Details tabs.

Figure 25. Workunit Details




The Workunit Details Action Buttons allow you to perform actions on the selected workunit. Press the corresponding Action button to allow you to perform the following actions.

- **Refresh** - Redisplays the workunit details.
- **Save** - Saves any changes to the workunit.
- **Delete** - Deletes the workunit.
- **Restore** - Restores an archived workunit. (Workunits are archived by Sasha).
- **Set To Failed** - Changes the workunit state to failed.
- **Abort** - Stops a running workunit and aborts the job.
- **Recover** - Resubmits the workunit without resetting the workflow. This resumes processing from the same point in the process where it ended previously.
- **Resubmit** - Resubmits the workunit. This resets the workflow and starts it over from the beginning.
- **Clone** - Creates a new copy of the workunit. The new workunit is now owned by the user who cloned it.
- **Publish** - Publishes the workunit as a published query.
- **Z.A.P.** - Packages up workunit and system information into a Zip file that can be shared. This is useful for troubleshooting and bug reporting.
- **Slave Logs** - Download the logs for the specified Thor cluster. This is useful for troubleshooting any Thor issues.

Publish Action Button

Click on the Publish action button to publish a query.

Figure 26. Publish Menu



Fill in the values for the Job Name, the Remote Dali, Source Process, Priority (optional), and you can add a comment. After you fill in the required values you can press the **Submit** button to submit your query.


Options for ECL Publish

- **Job Name:** The name of the job to publish. Auto-populated if you choose to publish from the workunit details page.
- **Remote Dali:** The IP or hostname of the DALI to be used to resolve remote files. (optional)
- **Source Process:** Process cluster from which to copy files. (optional)
- **Comment:** If desired, add a comment. The comment displays on the published queries details page.
- **Priority:** Sets the priority for the query. Values can be LOW, HIGH, SLA, or NONE. NONE will clear current setting.
- **Allow Foreign Files:** Check the box to allow the use of foreign files in a Roxie query. If a Roxie query references foreign files and this is not enabled, publish will fail.
- **Update Super Files:** Use when a query uses foreign superfiles or a remote Dali. When such a query is published the superfiles are copied from the remote Dali. If superfiles already exist locally, then the current definition is overwritten only when this box is checked. If it is not checked, the current definition will not change.

Z.A.P. Utility


The Zipped Analysis Package (Z.A.P.) button is a utility for collecting system information and encapsulating it into a shareable package. It is a useful tool for reporting errors, inconsistencies, or other unexpected behavior. When there is such an occurrence, this utility packages up information to send for further analysis.

Figure 27. Z.A.P. Button



To use the Z.A.P. utility, press the Z.A.P. button on the workunit details page from the appropriate workunit. The button opens the Zipped Analysis Package dialog.

Figure 28. The Zipped Analysis Package Dialog




Fill in the corresponding values under Description, History, and Timings in the Z.A.P. dialog. Optionally, you can password protect the ZAP package and choose to include slave logs. Press the **Apply** button when finished. The Z.A.P. utility generates a zip file with all the appropriate information for troubleshooting.

You can find the generated zip file in your browser's designated download directory. You can now send this file to the person handling your support request, or you can upload the file into the issue tracking system. Before distributing the file, verify that the file does not contain any sensitive data, such as personally identifiable information (PII).

Slave Logs

Figure 29. The Slave Logs Dialog




The **Slave Logs** action button opens a dialog where you can choose to download the logs for a specified Thor cluster. You can select the cluster, a specific Slave number, and the log file format (plain or compressed). This is useful for troubleshooting any Thor issues.

Outputs tab


Click on the Outputs tab to see all results.

Figure 30. Outputs



Click on the **Result #** link to open a tab and display the results.

Figure 31. Results Tab



You can filter the result set. Press the **Filter** action button to further filter down the results.


Press the **Download** action buttons to download the output files. The output files are available in 3 formats.

- **GZIP**
- **ZIP**
- **XLS:** Download the output in an Excel spreadsheet format.

Visualizations

You can see visual representations of select workunits. Visualizations are available from the workunit **Outputs** tab. The Visualize tab provides a number of chart types you can generate if you have included additional resources in your ECL code via the enhanced manifest mechanism (such as an index web page).

Figure 32. Visualization




To access Visualizations, click on the Outputs tab from the selected workunit details page, then select the **Visualize** tab. You can view different visualization types by clicking on the drop list on the Visualize tab. Click on the **Mappings** drop menu, to change the parameters.

Inputs tab

Click on the **Inputs** tab to see the workunit's input files. The input files are the source files that make up the workunit.

Figure 33. Inputs




The input files are displayed as a link. You can double-click the link to open a tab for each input file. You can select more than one input file and press the open button.

The **Usage** header indicates how many times a file was used in the workunit.

Timers tab

Click on the **Timers** tab to see the workunit timings.

Figure 34. Timers




Timers depict everything that happened with the workunit and for how long. Timers include graphs which also provide more information as to the processing of the workunit. The graphical heat map indicates by a darker color where more time was needed, while the lighter the color indicates that portion took less time.

Graphs tab

Click on the **Graphs** tab to see the graphs produced by the workunit.

Figure 35. GRAPHS




The Graphs tab shows a list of each graph and the heat map. Double click on the heat map to go to the corresponding portion of the graph.

Timers tab

Click on the **Timers** tab to see the workunit timings.

Figure 36. Timers




Timers depict everything that happened with the workunit and for how long. Timers include graphs which also provide more information as to the processing. The Heat map indicates by a darker color where more time was needed, while the lighter the color indicates that portion took less time.

Usage: how many times a file was used in the work unit.

Stats

On the workunit Timers tab is another tab for Stats. The Stats tab is a visual representation of all the workunit timings.

Figure 37. Stats



Select the timer values from the drop list on the Stats tab to view the various charts and graphs.

Workflows tab

The workflows tab only exists if you have an attribute scheduled. There are multiple workflows when your code contains more than one WHEN statement.

Counts: How many "events" are scheduled to happen.

Remain: How many "events" remain to occur.

Queries tab

Queries will only appear in the work unit details if the work unit is a published QUERY. Displays what queries were published from that work unit. Same as the queries tab: suspend, unsuspend, activate or deactivate, delete tabs with out any data.

Helpers tab

The Helpers tab display several helpful elements. Which show the ECL. The work unit XML. Archived query, The DLL. S. O., Thor log, ECL Agent log, and Thor slave log. The relevant logs files. If a Roxy log only logs the relevant sections for the selected work unit.

From a workunit, when you look at the log, it only shows the portion of the log that pertains to that workunit.

ECL Tab

Shows the ECL code for that workunit. It is the same thing as the Helpers ECL link.

XML tab

The workunits XML record as stored in Dali.

Using the ECL Playground

ECL Playground is a tool hosted on an ESP server. A page runs in your browser, allowing you to access and execute self-contained ECL code on your HPCC system without the use of any other tools. The ECL Playground then shows you the results and the graph in your browser. The view is very similar to what the ECL IDE displays.

Accessing ECL Playground


ECL Playground is installed with the HPCC platform. You can access it through the ECL Watch page.

1. In your browser, go to the **ECL Watch** URL. For example, <http://nnn.nnn.nnn.nnn:8010>, where nnn.nnn.nnn.nnn is your ESP server node's IP address.

 Your IP address could be different from the ones provided in the example images. Please use the IP address of **your** node.

2. From ECL Watch, click on the **ECL** icon, then click the **Playground** link from the navigation sub-menu.

Figure 38. ECL Playground link




The ECL Playground displays.

Introducing the ECL Playground

The ECL Playground page is a work area where you can see and run self-contained ECL code. You can see the code, submit it, and see the results. You can even change the code and resubmit it to instantly see the new results right in your browser. This is an ideal tool for the user who is not an ECL programming expert who wants to change some of the ECL code and see the results.


Figure 39. The ECL Playground



The ECL Playground page is divided into areas. The top portion contains the *Editor* area and the *Graph Viewer*. The Sample code drop list is at the top right. The bottom portion of the page displays the results.

The ECL Playground comes with a set of ready to run sample ECL code. The drop list contains code samples. Select any one of these samples and it loads in the editor.

Figure 40. Sample drop list




The selected code displays in the *Editor* area. You can then submit it as-is, or modify and submit. The results display at the bottom portion of the page.

Running ECL Code

To run the selected sample code, choose a target cluster from the drop list, then press the **Submit** button.

A successful run displays the word **completed** as the status and the results display in the results viewer. You can also view the graph in the upper right.


Figure 41. Success



A completed job generates a graph. You can examine the graph in greater detail by double-clicking the graph to zoom in. You can also zoom in with the mouse wheel. A double-click on a blank area of the graph will zoom out. You can use the scroll bars on the border of the graph to navigate or you can drag the graph with your mouse.

Selecting a node in the graph highlights the relevant section of the code in the Editor. This is helpful in troubleshooting or modifying code since it shows you the code that corresponds to a node in the graph.

Figure 42. Error




The status area displays the job status. If a job fails, errors display in the result viewer and the code is highlighted in red in the *Editor*. If there are warnings they are displayed in yellow.

Analyze the results

When running ECL Code that has multiple results, each result is on a separate tab. Select a tab to see that set of results. You can also change number of results displayed or page through the results with the links at the bottom.

Figure 43. Multiple results




ECL from a Workunit

You can access ECL code from inside a Workunit Details page in ECL Watch.


1. Select **Workunits** from the ECL Watch  menu.

Figure 44. Browse Workunits



2. Click on a workunit hyperlink to open the Workunit Details page.
3. Click on the **ECL** tab to view the workunit's ECL code.

Figure 45. ECL link



Files

This chapter contains sections dealing with HPCC Platform Files, found on the **Files** link in ECL Watch.

In an HPCC platform, data files are partitioned across nodes. The file parts, referenced using Logical Filenames, are stored in the Distributed File Utility. This allows the collection of file parts to be referenced as a single entity.


Files

The **Files** page contains features relating to the process of getting data files on to your cluster, managing these files and also the workunits associated with them. Click on the **Files** icon for access to the Files features. You can also perform actions on selected files and superfiles using the Workunit Action buttons.

Logical Files Page

To access the Files page click on the **Files** icon, then click the **Logical Files** link from the navigation sub-menu.


Figure 46. Logical Files



You can browse or search for logical files from this page using the Filter drop menu.


Note: Filter criteria are not case sensitive.

Figure 47. Logical Files Page



To see details for a particular file, or to perform some action on it you must select it. You can select a file or files by checking the check box. You can also click and drag your mouse over a group of check boxes, to select multiple files.

Figure 48. Select Files



There are three columns with icons to indicate some file attributes. There is also an icon that appears next to the Logical Name that indicates what type of file it is.

	Locked File
	Compressed File
	Key File (index)
	Logical file
	Superfile

You can also sort a column by clicking on the column heading. Click once for ascending, click again to toggle to descending. The arrow shows the sort order.

Once you have selected a file or files, the Action Buttons are enabled. You can perform actions on selected files.

- Press the **Open** button to open the Logical Files Details page(s).
- Press the **Delete** button to delete file(s).
- Press the **Remote Copy** button to open the dialog where you can copy files from a foreign HPCC Platform. You will need premission to access the foreign Dali server.
- Press the **Copy** button to copy a file. You can modify some of the copy options from the drop menu.
- Press the **Rename** button to rename a logical file. You can modify some rename options from the drop menu.
- Press the **Add To Superfile** button to create and add file(s) to a superfile.
- Press the **Despray** button to despray the file. You can modify some despray options from the drop menu.


- Press the **Filter** button to display additional filter options. Use these options to filter the list.
- Press the Tree image button (to the right of the Filter button) to view files by scope in a tree view.

You can press the **Open** button to open a tab with the details for each selected file.

Remote Copy

Press the **Remote Copy** button to open the dialog where you can copy files to or from a foreign dali.

Figure 49. Remote Copy Dialog



Fill in the values for the Source file, and the Target destination, check any appropriate options then press the **Submit** button.


Copy File

Press the **Copy** button to display the copy drop menu, with additional file copy options.

Sorting Columns

You can sort a column by clicking on the column heading. Click once for ascending, click again to toggle to descending. The direction of the arrow indicates the sort order.

Figure 50. Logical File sort by column




		Logical Name	Owner	Description
		thor_data400::key::bizlinkfull...	duPhed...	
		thor_data400::key::bizlinkfull...	duPhed...	
		thor_data400::key::bizlinkfull...	duPhed...	

Logical Files Filter Options

You can filter the logical files displayed on the Logical Files tab by clicking on the **Filter** Action button. The Filter sub-menu displays. Fill in values to specify the filter criteria, then press the **Apply** button.

Figure 51. Logical Files Filter sub-menu




The logical file filter options allow you to filter files using the specified criteria. Logical files can be filtered by:

- **Name** - filter files by name. Supports wildcards.
- **Description** - filter files by description. Supports wildcards.
- **Owner** - filter files by owners. Supports wildcards.
- **Index** - include only Index files if checked.
- **Cluster** - filter files by cluster. Select the cluster from the drop list.
- **From Sizes** - filter files from a specific size.
- **To Sizes** - filter files up to a specific size.
- **File Type** - filter files by type.
- **From date** - filter files from a specific date and/or time. Select the date and time from the drop list.
- **To date** - filter files up to a specific date and/or time. Select the date and time from the drop list.

Note: Filter criteria are not case sensitive.

When you specify any Filter options, the Filter Action button displays *Filter Set*.

Figure 52. Logical Files Filter Set




The screenshot shows a user interface for managing logical files. At the top, there are buttons for 'To Superfile', 'Display', and 'Filter Set'. The 'Filter Set' button is highlighted with a red oval. Below the buttons is a table with the following data:

Cluster	Records	Size	Parts	Modified (UTC)
thor	1	508	50	2016-03-14 20:5
thor	1	508	50	2016-03-14 20:5

Logical Files Details

The Logical Files Detail page shows specific details for the file selected. You select the file to view by clicking the appropriate tab from the Navigation Tabs at the top of the page.

Figure 53. Logical Files Detail Page



The Logical File details summary appears in the main File Details portion of the files page. You can view other file details using the **File Details Tabs** at the top portion of the Page.

- Select the **Summary** tab to view a summary of the file details.
- Select the **Contents** tab to view file contents.
- Select the **ECL** tab to view the ECL code.
- Select the **DEF** tab to view the ECL definitions.
- Select the **XML** tab to view the XML representation of the logical file.
- Select the **File Parts** tab to view information about the various file parts.
- Select the **Queries** tab to see which queries use which logical files.
- Select the **Workunit** tab to view the corresponding workunit details. Note that the workunit tab shows you the same information that you would see if you selected it through the workunit link.

On the File Details Summary tab, you can perform some actions on the selected file.

- Press the **Refresh** button to refresh the file details.
- Press the **Save** button to save any changes you make to the file details.
- Press the **Delete** button to delete the file.
- Press the **Copy** button to copy a file. You can also modify some file attributes from the drop menu.
- Press the **Rename** button to provide a name and rename the file.
- Press the **Despray** button to despray the file. You can also modify some despray options from the drop menu.

Superfiles

A superfile is a managed list of subfiles (Logical Files) treated as a single logical entity. When a file is a superfile, the **Summary** tab displays the superfile details, such as each subfile. Select a superfile from the Logical Files list, then press the Open action button. This displays the superfile details page.

Figure 54. Superfile Details page

The screenshot shows the ECL Watch interface with the 'Logical Files' tab selected. A subfile named '.records::superfile' is open. The toolbar includes 'Refresh', 'Save', and 'Delete Superfile' buttons. The main area displays a table of subfiles:

	Logical Name	Owner	Description	Records	Size	Pa
<input type="checkbox"/>	::headerfile	Admin		6		
<input type="checkbox"/>	::recordfile	Admin		891		
<input checked="" type="checkbox"/>	::originalperson	Pan		841,400	104,333...	2
<input type="checkbox"/>	::recordfile3	Admin		594		


On the superfile details page you can:

- See the list of subfiles in the superfile. Click on any subfile hyperlink to see details for that subfile.
- See the details of the subfiles.
- Press the **Save** button to save any changes to the superfile.
- Press the **Delete Superfile** button to delete the entire superfile.
- Press the **Remove Subfile(s)** button to remove any selected subfile from the superfile.

DFU Workunits Page


The DFU Workunits page contains a list of all the DFU workunits on your system. It provides access to more details about the workunits. You can also perform actions on the selected workunit using the Workunit Action buttons.

Figure 55. Files Link



To access the DFU workunits page, click on the **Files** link on the navigation pane, then click the **Workunits** link from the navigation sub-menu. This action opens the DFU Workunits page. The page displays the DFU Workunits on your system.


Figure 56. Browse DFU Workunits

A screenshot of the DFU Workunits page. The page has a header with 'EclWatch' and 'Enterprise Serv...'. Below the header is a 'Navigation Tabs' section with a 'Workunits' link. To the right are 'Action Buttons' for Refresh, Open, Delete, Set To Failed, Protect, and Unprotect. A 'Filter Drop Menu' is also present. The main content is a table titled 'DFU Workunits' with columns: ID, Type, Owner, Job Name, Cluster, State, and % Comp. The table lists several workunits, each with a checkmark icon and a link to its details. A red callout box highlights the 'DFU Workunits' table title.

ID	Type	Owner	Job Name	Cluster	State	% Comp
D20130604-132326	Spray (Import)			thor	finished	100
D20130516-150648	Spray (Import)		s-from-20-de-duped- version	thor	finished	100
D20130429-113452	Copy		jd::certification::full_test_dl roxie	thor	finished	100
D20130408-160235	Spray (Import)	originalperson		thor	finished	100
D20120831-140239	Copy	tk::sandbox		thor	finished	100
D20120831-135059	Copy	tk::sandbox		thor	finished	100
D20120828-114037	Spray (Import)	mynewsgroupmessages		thor	finished	100
D20120806-120017	Spray (Import)	originalperson		thor	finished	100

To further examine a workunit or to perform some action on it you must select it. You can select the workunit by checking the check box. You can also double-click on the workunit to select and open it in a new tab.

Figure 57. Select DFU Workunit



	ID	Type	Owner	Job Name
<input type="checkbox"/>	D20130325-172116	Spray (Import)	...	people
<input checked="" type="checkbox"/>	D20130325-171351	Spray (Import)	...	imper
<input checked="" type="checkbox"/>	D20130325-171328	Spray (Import)	...	namespaces
<input type="checkbox"/>	D20130325-170736	Spray (Import)	...	people
<input type="checkbox"/>	D20130325-170720	Spray (Import)	...	namespaces
<input type="checkbox"/>	D20130325-170301	Spray (Import)	...	people

You can select multiple workunits by checking the check box next to each workunit. You can also click-and-drag over a group of workunit check boxes to select multiple workunits.

The enabled Action buttons now allow you to perform some actions on the selected workunits.

- Press the **Refresh** button to refresh the list.
- Press the **Open** button to open the workunit(s) details tab.
- Press the **Delete** button to delete selected workunit(s).
- Press **Set to Failed** button to set the workunit(s) state to failed.
- Press the **Protect** button to lock the workunit(s). This prevents it from archiving by the Sasha server.
- Press the **Unprotect** button to unlock the selected protected workunit(s).
- Press the **Filter** button to display additional filter/search options.

Note: Filter criteria are not case sensitive.


When you select a workunit you can then press the **Open** action button to view the workunit details. You can also double-click on a particular workunit to open the details tab.

When you select and then open multiple units, they will each open their own tab.

DFU Workunits Filter Options

You can filter the workunits displayed on the Workunits tab by clicking on the **Filter** Action button. The Filter submenu displays. Fill in values to specify the filter criteria, then press the **Apply** button.

Figure 58. The DFU Workunit Filter




The DFU Workunit filter options allow you to filter workunits using the specified criteria. Workunits can be filtered by:

- **Archived Only** - when checked, this filter will search only archived workunits.
- **Owner** - filter workunits for specific owners. Supports wildcards.
- **Job Name** - filter workunits by job name. Supports wildcards.
- **Cluster** - filter workunits by cluster. Select the cluster from the drop list.
- **State** - filter workunits by state. Select the state from the drop list.

Note: Filter criteria are not case sensitive.

When you specify any Filter options, the Filter Action button displays *Filter Set*.

Figure 59. DFU Filter Set



Sorting Columns

You can sort a column by clicking on the column heading. Click once for ascending, click again to toggle to descending. The direction of the arrow indicates the sort order.

Figure 60. DFU Workunit Sort by column


A screenshot of a software interface titled 'Workunits'. At the top, there are buttons for 'Refresh', 'Open', 'Delete', 'Set To Failed', 'Protect', 'Unprotect', and 'Filter'. A red oval highlights the 'Owner' column header in the table. The table has columns for 'ID', 'Type', 'Owner', and 'Job Name'. The 'Owner' column header has a blue background and a small downward-pointing arrow. The table contains seven rows of data. Each row has a checkbox in the first column and a lock icon in the second column. The 'ID' column contains links: 'D20130325-170720', 'D20130325-173508', 'D20130325-173246', 'D20130325-173231', 'D20130325-172753', and 'D20130325-172741'. The 'Type' column shows 'Spray (Import)' for all rows. The 'Owner' column shows 'sort' for the first row and 'jprichard' for the others. The 'Job Name' column shows 'namespaces' for all rows.

		Type	Owner	Job Name
<input type="checkbox"/>		D20130325-170720	Spray (Import)	sort
<input type="checkbox"/>		D20130325-173508	Spray (Import)	jprichard
<input type="checkbox"/>		D20130325-173246	Spray (Import)	jprichard
<input type="checkbox"/>		D20130325-173231	Spray (Import)	jprichard
<input type="checkbox"/>		D20130325-172753	Spray (Import)	jprichard
<input type="checkbox"/>		D20130325-172741	Spray (Import)	earl

DFU Workunit Details Page

When you open the selected workunit(s) you will see the workunit details. The Workunit Details tab provides information about a workunit. You can see more information about workunit details by selecting the various Workunit Details tabs. You can also perform actions on the selected workunits using the Workunit Action buttons.

Figure 61. Workunit Details



Additional Workunit details are located in the Workunit Details section of the page. Job name, queue, command, time, completion percentage, along with specific process messages display here.


You can use the Workunit Action buttons on the Active Workunit tab to perform actions on the selected workunit. Press the appropriate Workunit Action button to perform the following actions.

- Press the **Refresh** button to refresh the workunit details.
- Press the **Save** button to save the workunit.
- Press the **Delete** button to delete the workunit.
- Press the **Abort** button to abort a running workunit.
- Press the **Resubmit** button to resubmit the workunit (not yet implemented).
- Press the **Modify** button to modify the workunit (not yet implemented).

XML Tab

The XML Tab on the workunit details page allows you to see the XML representation of the workunit.


Figure 62. Workunit Detail XML tab



Source Tab

The Source Tab on the workunit details page allows you to view the source file(s) of the DFU workunit.


Figure 63. Workunit Detail Source tab



Target Tab

The Target Tab on the workunit details page allows you to view the target of the DFU workunit.


Figure 64. Workunit Detail Target tab



Landing Zones

To access the Landing Zones page click on the **Files** icon, then click the **Landing Zones** link from the navigation sub-menu. The Landing Zone link displays the Landing Zones page. The Landing Zone Page shows you each landing zone you have configured for your cluster and its contents.

Figure 65. Landing Zone Page



	Name	Size	Date
<input type="checkbox"/>	mydropzone		
<input type="checkbox"/>	Desert.jpg	845941	2013-06-05 10:41:05
<input type="checkbox"/>	Penguins.jpg	777835	2013-06-05 10:41:05
<input type="checkbox"/>	Tulips.jpg	620888	2013-06-05 10:41:05
<input checked="" type="checkbox"/>	full_test_distributed	94000000	2013-06-05 11:05:19
<input type="checkbox"/>	jimicecream_name_password	57344	2013-06-05 10:43:55
<input type="checkbox"/>	t2.txt	384	2013-05-30 10:03:58

Click on the arrow next to a drop zone container to expand. The files on the drop zone display. You can choose to upload, download, or delete any files on the drop zone using the landing zone action buttons. You can also spray files to a cluster from this page.

Upload files

You can upload files to your landing zone from the Landing Zone page.


1. Press the **Upload** action button.



The upload utility in ECL Watch is limited by the browser's file size limitation. This is typically 4 GB. For production systems, we recommend a secure copy protocol (scp) utility.

2. Choose the file from the window that displays.
3. Verify the file and dropzone are correct in the **Info Dialog** that displays.

Figure 66. Info Dialog



4. Press the **Start** button to begin the upload.

The file progress indicator shows as the file uploads. When upload is complete, the window closes.

Download files

You can download files from your landing zone to your computer.

1. From the Landing Zone page, select a file (or files) to download by checking the box next to it.
2. Press the **Download** button to download the file.

The file will download to your browser's download directory as specified in your browser settings.

Delete files

You can delete files from your landing zone.


1. From the Landing Zone page, select a file (or files) to delete by checking the box next to it.
2. Press the **Delete** action button to delete the file from your landing zone.

Hex Preview

The Hex Preview shows the contents of a file on the landing zone in hexadecimal form. If the file is large, then only the first 32k display. Hex preview is designed for fixed length files, although it can also work for delimited files but may be limited in that regards.

1. Select a file by checking the box next to it.
2. Press the **Hex Preview** action button to display the selected file(s) in a hex format.

Figure 67. Hex Preview



The screenshot shows a software interface for viewing file contents. At the top, there are tabs for 'Landing Zone Files' and 'OriginalPerson' (which is selected, indicated by a yellow border). Below the tabs, there are two input fields: 'Width: 16' and 'EBCDIC: '. The main area displays a table of data. The columns are labeled with row numbers (1 to 18) and various file records. The data is presented in two columns: one for ASCII characters and one for their corresponding hexadecimal values. For example, record 1 shows '0000 Cherianne K' with hex values 43 68 65 72 69 61 6E 6E 65 20 20 20 20 20 20 4B. The table continues with other records, including 'hatchatourian', 'N', '5453069 B', 'OULDER RIDGE RD', '# 25A', 'HAWKINS', 'WIMuye', 'sser Raple', 'e', 'X', '2074755 SWAMP', 'RD', 'DISTRICT HEIGH', 'MDRoselin', 'Viceconte', and '0100'. The 'EBCDIC' checkbox is checked, indicating the data is being displayed in EBCDIC format.

1	0000	Cherianne	K	43	68	65	72	69	61	6E	6E	65	20	20	20	20	20	20	4B
2	0010	hatchatourian		68	61	74	63	68	61	74	6F	75	72	69	61	6E	20	20	20
3	0020		N	20	20	20	20	20	20	20	20	4E	20	20	20	20	20	20	20
4	0030		5453069 B	20	20	20	20	20	20	20	35	34	35	33	30	36	39	20	42
5	0040	OLDER RIDGE RD		4F	55	4C	44	45	52	20	52	49	44	47	45	20	52	44	20
6	0050	# 25A		23	20	32	35	41	20	20	20	20	20	20	20	20	20	20	20
7	0060		HAWKINS	20	20	20	20	20	20	48	41	57	4B	49	4E	53	20	20	20
8	0070		WIMuye	20	20	20	20	20	20	20	20	20	20	57	49	4D	75	79	65
9	0080	sser	Raple	73	73	65	72	20	20	20	20	20	20	20	52	61	70	6C	65
10	0090	e		65	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
11	00a0	X		20	20	20	20	58	20	20	20	20	20	20	20	20	20	20	20
12	00b0	2074755	SWAMP	20	20	20	32	30	37	34	37	35	35	20	53	57	41	4D	50
13	00c0	RD		20	52	44	20	20	20	20	20	20	20	20	20	20	20	20	20
14	00d0			20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
15	00e0	DISTRICT	HEIGH	20	20	44	49	53	54	52	49	43	54	20	48	45	49	47	48
16	00f0	T	MDRoselin	54	20	20	20	20	20	4D	44	52	6F	73	65	6C	69	6E	20
17	0100		Viceconte	20	20	20	20	20	20	20	56	69	63	65	63	6F	6E	74	65
18	0310			0	00	00	00	00	00	00	00	20	20	20	20	20	20	20	20

You can adjust the width of the view on the hex preview page using the spinbox controls on the **Width** box.

If you have an EBCDIC file check the box next to **EBCDIC:** for it to display properly.


Spray/Despray

This section details how to Spray and Despray a data file to your cluster using ECL Watch. The spray function is integrated into the Landing Zone page as detailed in the Upload Files section .

In order to spray a file to your cluster you must first upload the file to your landing zone. The file upload steps are detailed in the preceding section.

With the file successfully uploaded to the landing zone you can choose the file to spray from the Landing Zone page. Once selected the Spray buttons become enabled.

Figure 68. Landing Zone Page



Landing Zone Files			
	Name	Size	Date
<input type="checkbox"/>	mydropzone		
<input type="checkbox"/>	Desert.jpg	845941	2013-06-05 10:41:05
<input type="checkbox"/>	Penguins.jpg	777835	2013-06-05 10:41:05
<input type="checkbox"/>	Tulips.jpg	620888	2013-06-05 10:41:05
<input checked="" type="checkbox"/>	full_test_distributed	94000000	2013-06-05 11:05:19
<input type="checkbox"/>	jimicecream_name_password	57344	2013-06-05 10:43:55
<input type="checkbox"/>	t2.txt	384	2013-05-30 10:03:58

Spray Data to a Cluster

With the **Spray:** Action buttons enabled, you press the appropriate button for the Spray you wish to perform. Fill in the appropriate values when prompted to complete the spray.


Spray Files

One way you can spray files to your clusters is from the **Landing Zone** page in ECL Watch.

1. Select the file from your drop zone by checking the box next to it.
2. Select the appropriate drop menu option for the type of spray you want.

For example, to spray a delimited file, select the **Delimited** action button.

Figure 69. Landing Zone Spray



3. Fill in the values as appropriate for the spray.
4. Press the **Spray** button to spray the file(s).

Spray multiple files

You can choose to spray multiple files with the multi-file spray feature. This is useful for spraying a number of files of the same type using the same spray options.

Fixed (length) files can have different record lengths and XML files can have different row tags which must be specified individually for each file. To specify these differences select the files you want to spray and the spray type. You will then see the files listed. Enter the record length or row tag information for each file if using the Fixed or XML spray types, then check all other applicable options and Spray.

Spray Fixed

- Click on the **Files** icon, then click the **Landing Zones** link from the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the Spray: **Fixed** action button.

The **Spray Fixed** dialog displays.

- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Scope	The prefix for the logical file
Target Name	The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.
Record Length	The size of each record.

Options:

Overwrite	Check this box to overwrite files of the same name.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).
This option is only available on systems where replication has been enabled.	
Compress	Check this box to compress the files.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Spray Delimited

- Click on the **Files** icon, then click the **Landing Zones** link from the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the **Spray: Delimited** action button.

The **Spray Delimited** page displays.
- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Scope	The prefix for the logical file
Target Name	The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.

Options:

Format	Select the format from the dropdown
Max Record Length	The length of longest record in the file.
Separators	The character(s) used as a separator in the source file.
Omit Separator	Check this box to omit the separator.
Escape	A null-terminated string containing the CSV escape characters.
Line Terminators	The character(s) used as a line terminators in the source file.
Quote	The character used as a quote in the source file.
Overwrite	Check this box to overwrite files of the same name.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.

Compress	Check this box to compress the files.
Quoted Terminator	Check this box to indicate that the terminator character can be included in a quoted field. If unchecked, it allows quicker partitioning of the file (avoiding a complete file scan).

Record Structure Present Flag indicating whether to derive the record structure from the header of the file.

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Spray XML

- Click on the **Files** icon, then click the **Landing Zones** link from the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the **Spray: XML** action button.

The **Spray XML** dialog displays.

- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Scope	The prefix for the logical file
Target Name	The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.
Row Tag	The tag name of the row delimiter. Required.

Options:

Format	Select the format from the dropdown
Max Record Length	The length of longest record in the file.
Overwrite	Check this box to overwrite files of the same name.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.

Compress	Check this box to compress the files.
-----------------	---------------------------------------

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Spray JSON

- Click on the **Files** icon, then click the **Landing Zones** link from the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the **Spray: JSON** action button.

The dialog displays.
- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Scope	The prefix for the logical file
Target Name	The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.
Row Path	The path specifier to the JSON content. The default takes the root level content as an array of objects to be treated as rows.

Options:

Format	Select the format from the dropdown
Max Record Length	The length of longest record in the file.
Overwrite	Check this box to overwrite files of the same name.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.

Compress	Check this box to compress the files.
-----------------	---------------------------------------

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Spray Variable

- Click on the **Files** icon, then click the **Landing Zones** link on the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the Spray: **Variable** action button.

The Spray **Variable** dialog displays.
- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Scope	The prefix for the logical file
Target Name	The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.

Options:

Source Type	Select the source type from the drop list. Values: recfmv, recfmvb, Variable, or Variable Big-endian.
Overwrite	Check this box to overwrite files of the same name.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.

Compress	Check this box to compress the files.
-----------------	---------------------------------------

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Spray Blob

- Click on the **Files** icon, then click the **Landing Zones** link on the navigation sub-menu.
- Click on the arrow next to your dropzone to expand the list.

The files on your drop zone display.
- Check the checkboxes for the file(s) you want to spray, then press the Spray: **BLOB** action button.

The Spray **BLOB** dialog displays.
- Fill in relevant details:

Target

Group	Select the name of cluster to spray to. You can only select a cluster in your environment.
Target Name	The logical target name to create. Required. You must provide a target name.
Source Path	The path to the file. This is pre-filled with the name of the selected source file(s) on the landing zone, but can be changed. Supports wildcards.

Options:

Blob Prefix	The prefix for the file.
Overwrite	Check this box to overwrite files of the same name.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.


Compress	Check this box to compress the files.
Fail if no source file	Check this box to allow the spray to fail if no source file is found.

- Press the **Spray** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each spray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Desprays

- Locate the file(s) to despray in the list of files, then Press the the **Despray** action button.



- Provide **Destination** information.

Drop Zone

Use the drop list to select the machine to despray to. The items in the list are landing zones defined in the system's configuration.

IP Address

This is prefilled based upon the selected machine.

Path

Provide the complete file path of the destination including file name and extention.

Split Prefix

Prefix

Overwrite

Check this box to overwrite a file with the same name if it exists.

Use Single Connection

Check this box to use a single network connection to despray.

- Press the **Despray** button.

A DFU Workunit tab for each job opens. You can see the progress of each despray operation on the tab. If a job fails, information related to the cause of the failure also displays.

Copy

- Click on the **Files** icon, then click the Logical Files button on the navigation bar.
- Select the file(s) to copy in the list of files, then click on the **Copy** action button.
- Fill in **Destination** and **Options** information.

Target:

Group Select the name of cluster to copy to. You can only select a cluster in your environment.

Target Name The logical filename to create. This is pre-filled with the name of the source file on the landing zone, but can be changed.

Options:

Replicate Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).

This option is only available on systems where replication has been enabled.

Wrap Check this box to keep the number of parts the same and wrap if the target cluster is smaller than the original.

No Split Check this box to prevent splitting file parts to multiple target parts.

Overwrite Check this box to overwrite files of the same name.

Compress Check this box to compress the files.

Retain Superfile Structure Check this box to retain the superfile structure.

Preserve Compression Check this box to preserve the compression of the original file when copying

- Press the **Copy** button.

A **DFU Workunit** tab displays for each job. You can see the progress of each copy operation on the tab. If a job fails, information related to the cause of the failure also displays.

Remote Copy

Remote Copy allows you to copy data from a cluster outside your environment to one in your environment.

- Click on the **Files** icon, then click the Logical Files button on the navigation bar.
- Click on the **Remote Copy** link

The **Copy File** page displays.

- Fill in **Source**, **Destination**, and **Options** information.

Source:

Dali	The Dali Server in the remote environment
User ID	The Username to use to authenticate on the Remote environment (if needed)
Password	The password to use to authenticate on the Remote environment (if needed)
Logical File	The logical filename in the remote environment.

Destination:

Group	Select the name of cluster to copy to. You can only select a cluster in your environment.
Logical Name	The logical name for the copied file.

Options:

Replicate	Check this box to create backup copies of all file parts in the backup directory (by convention on the secondary drive of the node following in the cluster).
This option is only available on systems where replication has been enabled.	
Wrap	Check this box to keep the number of parts the same and wrap if the target cluster is smaller than the original.
Overwrite	Check this box to overwrite files of the same name.
Compress	Check this box to compress the files.
No Split	Check this box to prevent splitting file parts to multiple target parts.
Retain Superfile Structure	Check this box to retain the superfile structure.

- Press the **Submit** button.

A **DFU Workunit** tab displays. You can see the progress of the copy operation on the tab. If a job fails, information related to the cause of the failure also displays.

- Press the **Refresh** button periodically until the status of your request indicates it is **Finished** or click on the **View Progress** hyperlink to see a progress indicator.

XRef

Under the **Files** Icon on the navigation sub-menu there is a link for XRef. This link will take you to the XRef Clusters page. On the XRef clusters page you can run the XREF utility.

Figure 70. XRef Clusters page

The screenshot shows the XRef Clusters page. At the top is a table with columns: Name, Last Run, Last Message, Available Reports, and Action. Two entries are listed: 'SuperFiles' and 'mythor'. Both entries show 'Not Run' in the Last Message column and 'Not generated yet.' in the Available Reports column. The 'Action' column for each entry contains a 'Generate' button. Below the table is a 'GLOSSARY' section with three entries:

Name	Last Run	Last Message	Available Reports	Action
SuperFiles		Not Run	Not generated yet.	Generate
mythor		Not Run	Not generated yet.	Generate

GLOSSARY

Found File A found file has all of its parts on disk that are not referenced in the Dali server. All the file parts are accounted for so they can be added back to the Dali server. They can also be deleted from the cluster, if required.

Orphan File An orphan file has partial file parts on disk. However, a full set of parts is not available to construct a complete logical file. These partial file parts, therefore, do not have a reference in the Dali server.

Lost File A logical file that is missing at least one file part on both the primary and replicated locations in storage. The logical file is still referenced in the Dali server. Deleting the file removes the reference from the Dali server and any remaining parts on disk.

The XREF utility provides the ability to find "orphaned" and "lost and found" files. These "orphan" are files which are found on the nodes but not registered in the Distributed File System.

Found File A found file has partial file parts on disk that are not referenced in the Dali server. All the file parts are accounted for so they can be added back to the Dali server. They can also be deleted from the cluster, if required.

Orphan File An orphan file has partial file parts on disk. However, a full set of parts is not available to construct a complete logical file. These partial file parts, therefore, do not have a reference in the Dali server.

Lost File A logical file that is missing at least one file part on both the primary and replicated locations in storage. The logical file is still referenced in the Dali server. Deleting the file removes the reference from the Dali server and any remaining parts on disk.



On a large system, we suggest limiting the number of users who can Generate XREF reports by setting DfuXrefAccess access to FULL for only those users.

To generate a list:

- Press the **Generate** button.



Sasha Server typically runs Xref at the times scheduled when deployed.

To view results:

- Click on one of the hyperlinks (Found Files, Orphan Files, Lost Files, Directories, or Errors/Warnings).

Working with XREF results:

After XRef completes you will see a list of available reports. Click on one of the links to see the results page of each type.

Figure 71. XRef Errors

Name	Last Run	Last Message	Available Reports	Action
SuperFiles	2013-06-04T15:41:16	Generated [2 superfiles, 2 subfiles]	Errors/Warnings	Generate
mythor	2013-06-04T17:27:17	Generated [24 files]	Found Files Orphan Files Lost Files Directories Errors/Warnings	Generate

GLOSSARY

Found File A found file has all of its parts on disk that are not referenced in the Dali server. All the file parts are accounted for so they can be added back to the Dali server. They can also be deleted from the cluster, if required.

Orphan File An orphan file has partial file parts on disk. However, a full set of parts is not available to construct a complete logical file. These partial file parts, therefore, do not have a reference in the Dali server.

Lost File A logical file that is missing at least one file part on both the primary and replicated locations in storage. The logical file is still referenced in the Dali server. Deleting the file removes the reference from the Dali server and any

The Orphan and Lost Files pages list any Orphan or Lost files. Orphan and Lost files are difficult to recover, unless you have copies of missing parts needed to reconstruct the file (for example, if a missing part is on a hard drive that was replaced.)

Figure 72. XRef: Delete Lost Files

<input type="checkbox"/>	Name	Modified	Total Parts	Size	Primary Lost	Replicate Lost
<input checked="" type="checkbox"/>	certification::full_test_distributed	2013-05-30T12:58:48	1		1	1
<input checked="" type="checkbox"/>	certification::full_test_distributed_index	2013-05-23T16:32:04	2		1	2

[Select All / None](#)

[Delete](#)

Typically, these files are deleted. To Delete, check the boxes next to files you want to delete, then press the Delete button.


Found files can and usually are reattached.

Figure 73. XRef: Attach Found Files

Found files on 'mythor' cluster:

	Name	Modified	Parts	Size
<input type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/jim"	2013-05-17T14:31:49	1	780831
<input checked="" type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/certification/___Index_2_of_2	2013-05-23T16:32:03	1	32768
<input type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/certification/full___1of_1	2013-05-30T12:58:48	1	94000000

Delete **Attach**



The screenshot shows a table titled "Found files on 'mythor' cluster:". The table has four columns: "Name", "Modified", "Parts", and "Size". There are three rows of data:

	Name	Modified	Parts	Size
<input type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/jim"	2013-05-17T14:31:49	1	780831
<input checked="" type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/certification/___Index_2_of_2	2013-05-23T16:32:03	1	32768
<input type="checkbox"/>	/var/lib/HPCCSystems/hpcc-data/thor/certification/full___1of_1	2013-05-30T12:58:48	1	94000000

At the bottom of the interface are two buttons: "Delete" and "Attach". The "Attach" button is highlighted with a blue border and a mouse cursor is hovering over it.


Check the boxes next to files you want to reattach, then press the Attach button.

Queries

The link for the Published Queries (icon) header provides more information and details about queries on available targets.

Click on the Published Queries (icon) hyperlink to display the published queries and package maps on that cluster.


Figure 74. Query Link



Queries Page in ECL Watch

The Queries page lists published queries for each target cluster. On this page you can see the published queries . You can also perform some actions on the selected queries.

Figure 75. Browse Query Sets



	■	■	■	ID	Name	Target
	■	■	■	deeee.1	deeee	thor
	■	■	■	fernando1.1	fernando1	thor
	■	■	■	fetchpeoplebyzipservi...	fetchpeoplebyzipservice	thor
	■	■	■	fetchneonleahyzipservi...	fetchneonleahyzipservi...	thor

The Queries interface provides some information at a glance, there are three columns on the left side of each listed query. These three columns provide information about these queries.

	Indicates a paused query
	Indicates an activated query
	Indicates a query suspended by the system

The queries page also provides other information at a glance:

- the query ID
- the query name
- the target
- the workunit id (WUID)
- the dll
- Published by


All the above available at a glance on the main queries page, with further actions that can be performed from the action buttons along the top of the tab. You can sort a column by clicking on the column heading. Click once for ascending, click again to toggle to descending. The direction of the arrow indicates the sort order.

To see the details page for a particular query, or to perform some action on it you must select it. You can select a query or queries by checking the check box. You can also open a particular query by double clicking on it.

Queries Tab

When you select the Published Queries hyperlink you open the Queries tab. This tab displays published queries on the system. The Action buttons allow you to perform operations on the published queries selected.

Figure 76. Published Query Action buttons



Open Opens the selected query (or queries).

Delete Deletes the selected query (or queries).


Suspend Suspends the selected active query (or queries).

Unsuspend Unsuspends the selected suspended query (or queries).

Activate Activates the selected query (or queries). This assigns a query to the active alias with the same name as the query.

Deactivate Deactivates the selected active query (or queries) by removing the active query alias from the given queryset.

Filter	Allows you to filter the queries for the criteria you enter. When the Filter is applied the action button displays Filter Set . This icon indicates that the published queries displayed are filtered.
---------------	---



You can filter for several query attributes. You can filter by:

- ID
- Name
- Published by
- WUID
- Cluster
- Logical File Name
- Libraries Used
- Suspended queries.
- Active queries.

The Filter also supports wild cards.

Options	Provides the option to search/display queries on a single node or all nodes. Using this option can improve performance if you have a large multi-node cluster.
----------------	--


Query Details

To examine the Query Details page, you select and open the query or queries. This opens a tab containing the query details. From the query details page you can get more information about the specific query. You can also perform some actions on that query. There are several tabs with additional information about the selected query.

Query Summary Tab

The default query tab opened when you select a query is the Summary tab. The summary tab shows you some detail information about the query.

Figure 77. Query detail page



The screenshot shows the 'Queries' interface with the 'fetchpeoplebyzipservice2.1' query selected. The 'Summary' tab is active. The query details are as follows:

Name:	fetchpeoplebyzipservice2
Query Set:	thor
Priority:	
Published By:	EmilyKate
Suspended:	<input type="checkbox"/>

Below the table, there are action buttons: Refresh, Save, and Delete.

There are a few actions that you can perform on the query from this tab. Press the action buttons for the desired activity for the selected query.

Refresh Refreshes the information displayed for the selected query.

Save Saves the selected query (or queries).


Delete Deletes the selected query (or queries).

Errors Tab

For each selected query there is an Errors tab. The Errors tab displays any errors that may have been encountered during the compiling and publishing of that query. If there aren't any errors the errors tab will be blank. If there are

errors, you can further examine any specific error by checking the box and selecting it, and then press the open action button. You could also just double click on the selected error.


Figure 78. Query Error



Graphs Tab


The graphs tab provides access to graphical interpretations of the query. This can be helpful in visualizing how the query ran. The graphs tab displays a list of any graphs generated by the selected query, along with some additional information like timing. To display a specific graph, you must select it, and choose to open it, or you can double click on listed graph.

Figure 79. Graphs list



Opening a graph will open a new tab showing the selected graph(s).

Figure 80. Graphs




When you open a graph the visible area splits into three smaller sections each displaying some relevant component of the query graph. Notice the myriad of graph controls, and tabs in the border area of each tab. Manipulate these controls to view different aspects of the graphs.

The Advanced action button on the main graph control area, provides access to even more advanced graphing options.

Logical Files Tab

The Published queries details page provides a link to the queries Logical Files tab. The Logical Files tab shows all logical files that are used by the query. To view the logical file details for any file listed, select one or more files by checking the checkbox and press the Open action button. Tabs for each file selected opens where you can view and make changes to the file(s) without the need to go back to the logical files page.

Figure 81. Queries:Logical Files Tab




The above image shows the list of Logical files on the Logical Files tab. To view more detail about a logical file listed here, check the box next to the file, and then press the **Open** action button. You can also just double click on the logical file you want to view.

Using ECL Watch Queries

Once open, you can select any of the tabs to see Summary, Contents, ECL, DEF, XML, File Parts, Queries, or the Workunit.

Figure 82. Queries:Logical Files:Contents Tab




The screenshot shows the 'Contents' tab of the 'Logical Files' section for the query 'fetchpeoplebyzipservice.2'. The table lists 14 rows of data with the following columns: #, firstname, lastname, middlename, zip, and street. The data is as follows:

#	firstname	lastname	middlename	zip	street
1	CHERIANNE	KHATCHATORIAN	N	545...	69 BOULDER RIDGE RD # 25A
2	MUYESSER	RAPLEE	X	207...	55 SWAMP RD
3	ROSELIN	VICECONTE		978...	107 HILL TER
4	INDA	PROVINES		729...	290 W MOUNT PLEASANT AVE
5	INDERDEEP	LAURENCE	D	323...	44 PROSPECT PL
6	CHRYSTINE	MANGIAPANE		800...	1806 1ST AVE APT 8F
7	ADELENE	STOCK	R	199...	1117 FARM RD
8	MENDY	RUFENBLANCHETTE		296...	3 W 63RD ST APT 4C
9	LANNIE	AMERANTES	I	253...	200 W 20TH ST APT 909
10	TARE	GONYEAU	T	799...	6 CANDLE CT
11	FINNEY	ARISTILDE	P	312...	222 1ST AVE APT 2B
12	OREOLUWA	MARTHALER		042...	176 CLAREMONT GDNS
13	SURGE	ABBOTTKREPP	D	440...	22 LE PARC CT
14	DAVE	MCJURY		984...	510 COOPER RD

Test Pages

The Test Pages tab provides a number of resources you can use to test your query including SOAP/JSON/WSDL and the legacy WS-ECL form, as well as other tabs showing useful information or sample details about the query.

Figure 83. Test Pages tab




Information available from the Test pages tab.

- **SOAP** This tab provides an interactive interface to submit the query (with input data) and see the response in XML format.
- **JSON** This tab provides an interactive interface to submit the query (with input data) and see the response in JSON format.
- **WSDL** This tab provides a WSDL definition describing the functionality offered by the query (web service).
- **Request Schema** This tab provides a schema in XSD format describing a request for the query (web service).
- **Response Schema** This tab provides a schema in XSD format describing a response from the query (web service).
- **Sample Request** This tab provides a sample request for the query (web service) in XML Format.
- **Sample Response** This tab provides a sample response from the query (web service) in XML Format.
- **Parameter XML** This tab provides Parameterized XML representation of the query interface.
- **Legacy Form** This tab provides a form that can be used to submit a query and get a response. This is similar to the WsECL form.
- **Links** Provides a list of useful links such as: the Form, a sample REST URL, sample request, sample response, parameter XML, SOAP POST, WSDL, XSD, and the result schema.

The Workunits link

The Published queries details page provides a link to the workunits page. This tab is a shortcut that takes you to the same workunits tab you can get to through the ECL workunits menu.

Figure 84. Queries Workunit




This is the same as the **ECL Workunits** page from the navigation sub-menu Workunits link. You can perform the same operations here. Notice that there are some other familiar tabs here as well, for example the Graphs tab, both from the Queries details page, and from the workunit tab nested here.

Package Maps

From the Queries icon link, you can access the package maps page. Press the **Package Maps** button on the navigation sub-menu bar, to access to the Package Maps on your cluster.


Figure 85. Package Maps



The package maps page, displays all the package maps loaded on your cluster. You can Add, Activate, Deactivate, or Open a package map. To examine a package map, select a package map from the list.

You can select the **Validate Package Map** tab to validate a package map.

Figure 86. Validate Package Maps




Choose the **Target** and **Process** from the drop lists on the Validate Package Map tab.

Press the **Validate** button to validate the package map. The result is shown on the **Validate Active Package Map** tab. You can also Validate the package content, on the **Validate Package Content** tab.

Operations

The Operations link provides access to several components useful for the day-to-day operation of your system, and some system administration access as well.

Figure 87. Operations Menu



There are links to Target Clusters, Cluster Processes, and System Servers. These links open pages with more information about the specific topology for the selected clusters. These pages are helpful in certifying that your system is up and running properly.


There are also some system administration type links such as, Users, Groups, Permissions, and Resources. These links allow you to perform some system administration tasks through ECL watch.

Topology

The Topology page provides a visual tree display with information about your clusters, services, and nodes.

Click on the **Topology** link from the Operations navigation sub-menu to access the topology page.

Figure 88. Topology Page




Targets

The **Targets** Action button displays your clusters by type.

Click on the arrow to the left of the Cluster folder/object to expand. The expanded view displays.

Figure 89. Expanded View




The expanded view displays the objects and nodes in the selected container. Select the node or object to display more information or to access the logs. The Summary, Configuration, and Log tabs on the left side of the page display the relevant information for the selected component.

Services

Press the **Services** Action button to display information on the various services running on your cluster.

Click on the arrow to the left of the service you wish to expand. The expanded view displays.

Figure 90. Expanded Services




The services view provides a service oriented tree view that provides access to the services. Expand the tree, and select the component to view the Summary, Configuration, or Logs tabs for the selected component.

Machines

Press the **Machines** Action button for more information on the various machines or nodes running in your cluster(s).

Figure 91. Machines View




The **Machines** action button opens a node oriented view of the tree. Expand the nodes to see the services on each node. Select the component to view the Summary, Configuration, or Logs tabs for that selected component.

Disk Usage

When you click on the Operations link, it opens the Disk Usage page by default. The Disk Usage page provides information about the available space on your system, and what is using that space.

Figure 92. Disk Usage



The screenshot shows a web-based interface for monitoring disk usage. At the top, there is a navigation bar with tabs: Disk Usage (which is selected and highlighted in blue), Target Clusters, Cluster Processes, System Servers, Security, and Resources. Below the navigation bar is a toolbar with a Refresh button and a Filter button, which is circled in red. The main content area is a table with the following data:


Grouping	File Counts	Total Size	Largest File	Largest Size	Smalles
Thor:in:imdb:actors.list	3	1,263,305,...	thor::in::imdb::actors.list	731,640,773	tutorial:...
gpan	8	1,542,667,...	temp::imdb::actorsinmovies	1,081,189,...	tutorial:...
Emil:rate	18	4,517,094,...	nearestneighbor::all::fields	2,241,164,...	dm:...

You can search or filter the results, using the **Filter** action button.

Operations: Target Clusters

The Target Clusters link from the navigation sub-menu bar, on the Operations page, opens the link to the Target Clusters page. This page provides machine information on the clusters you have set up on your machine.


Figure 93. Target Clusters



Preflight System Servers

1. Click on the **Operations** icon then click on the **System Servers** link.

Figure 94. System Servers link




A screen similar to the following displays.

Figure 95. System Servers page

	Name	Queue	Computer	Network
Dali Servers				
<input checked="" type="checkbox"/>	mydali		localhost	192.168.1.101
DFU Servers				
<input checked="" type="checkbox"/>	mydfu	dfuqueue	localhost	192.168.1.101
Drop Zones				
<input type="checkbox"/>	mydropzone		localhost	192.168.1.101
ECL Agents				
<input checked="" type="checkbox"/>	myeclagent		localhost	192.168.1.101

2. Press the **Submit** button at the bottom of this page to start preflight.

Figure 96. Submit



EXPECTED RESULTS:

After pressing Submit, a screen similar to the following displays.

Figure 97. System Component Information

Machine Information

	Location	Component	Condition	State	Up Time	Processes Down	
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/myesp	Esp [myesp]	Normal	Ready	09:38	-	60%
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/myeclscheduler	Ecl Scheduler [myeclscheduler]	Normal	Ready	11:32	-	60%
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/myeclagent	Agent Exec [myeclagent]	Normal	Ready	11:35	-	60%
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/myeclccserver	Ecl CC Server [myeclccserver]	Normal	Ready	11:33	-	60%
<input checked="" type="checkbox"/>	10.239.219.4 /var/lib/HPCCSystems/mysasha	Sasha Server [mysasha]	Normal	Ready	11:51	-	60%
<input checked="" type="checkbox"/>	10.239.219.4 /var/lib/HPCCSystems/mydali	Dali Server [mydali]	Normal	Ready	11:54	-	60%
<input checked="" type="checkbox"/>	10.239.219.5 /var/lib/HPCCSystems/mydfuserver	Dfu Server [mydfuserver]	Normal	Ready	11:29	-	60%
<input checked="" type="checkbox"/> Select All / None							
Fetched: 11/11/11 14:13:09							
Action:	Machine Information						
<input checked="" type="checkbox"/>	Get processor information	Warn if CPU usage is over	95				

This screen displays information on several system components. This information indicates whether several components are actually running appropriately. The resulting page shows useful information about each component. The component name, the condition, the component state, how long the component has been up and running, the amount of disk usage, memory usage and other information is available at a glance.

Using ECL Watch Operations

If there are any failed components, they are highlighted in orange, indicating they are not ready.

Figure 98. Failed Component


Machine Information

	Location	Component	Condition	State	Up Time	Processes Down	/	/mnt/disk1	Physical Memory
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/mydali	Dali Server [mydali]	Normal	Ready	76 day(s) 00:50:02	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/mydfuserver	Dfu Server [mydfuserver]	Warning	Unknown		mydfuserver	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/myeclagent	Ecl Agent [myeclagent]	Normal	Ready	-	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/myeclagent	Agent Exec [myeclagent]	Normal	Ready	76 day(s) 00:50:00	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/myeclccserver	Ecl CC Server [myeclccserver]	Normal	Ready	76 day(s) 00:49:59	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/myeclscheduler	Ecl Scheduler [myeclscheduler]	Normal	Ready	76 day(s) 00:49:57	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/myesp	Esp [myesp]	Normal	Ready	76 day(s) 00:48:10	-	43%	97%	96%
<input checked="" type="checkbox"/>	10.239.219.2 /var/lib/HPCCSystems/mysasha	Sasha Server [mysasha]	Normal	Ready	76 day(s) 00:49:54	-	43%	97%	96%

Preflight Thor


1. Click on the **Operations** icon then click on the **Cluster Processes** link.

Figure 99. Cluster Processes Link




2. Click on the **mythor** link.

Figure 100. mythor link



3. Check the **Select All** checkbox (if necessary).
4. Press the **Submit** button to start preflight.

Figure 101. Submit



EXPECTED RESULTS:

After pressing Submit, a screen similar to the following should display.

Figure 102. ESP mythor system component information

	Location	Component	Slave Number	Condition	State	Up Time	Processes Down	/	/mnt/disk
<input checked="" type="checkbox"/>	10.239.219.4 /var/lib/HPCCSystems/mythor	Thor Slave [mythor]	2	Normal	Ready	03:17:11	-	51%	99%
<input checked="" type="checkbox"/>	10.239.219.5 /var/lib/HPCCSystems/mythor	Thor Slave [mythor]	1	Normal	Ready	03:17:11	-	51%	99%
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/mythor	Thor Master		Normal	Ready	03:17:11	-	51%	99%

This screen displays information on your Thor cluster. This information can help to indicate if everything is operating normally or can help to point out any potential concerns.

If your system has more than 1 Thor cluster, repeat these steps for each cluster.

Using ECL Watch Operations

If there are any failed nodes or notable alerts, they are highlighted in orange. The orange alerts usually require some additional attention.

Figure 103. Failed Component


Thor Cluster 'mythor'

	Location	Component	Slave Number	Condition	State	Up Time	Processes Down	/	Mount/disk1	Physical Memory
<input checked="" type="checkbox"/>	10.239.219.6 /var/lib/HPCCSystems/mythor	Thor Slave [mythor]	3	Warning	Unknown		mythor...	16%	95%	90%
<input checked="" type="checkbox"/>	10.239.219.5 /var/lib/HPCCSystems/mythor	Thor Slave [mythor]	2	Normal	Ready	04:32	-	52%	99%	97%
<input checked="" type="checkbox"/>	10.239.219.4 /var/lib/HPCCSystems/mythor	Thor Slave [mythor]	1	Normal	Ready	04:32	-	52%	99%	98%
<input checked="" type="checkbox"/>	10.239.219.3 /var/lib/HPCCSystems/mythor	Thor Master		Normal	Ready	04:32	-	51%	99%	97%

Select All / None
Fetched: 11/08/12 11:28:41

Action: Machine Information ▾

Get processor information Warn if CPU usage is over 95 %
 Get storage information Warn if available memory is under 5 %
 Local File Systems Only
 Get software information Warn if available disk space is under 5 %
 Show processes using filter Additional processes to filter:
 Auto Refresh every 0 mins.



Users Permissions

User Administration


There are User Administration features available through ECL Watch.

Security Administration using ECL Watch

Administrator rights are needed to manage permissions. Once you have administrator access rights, open ECL Watch in your browser using the following URL:

- **http://nnn.nnn.nnn.nnn:pppp** (where nnn.nnn.nnn.nnn is your ESP Server's IP Address and pppp is the port. The default port is 8010).

Security administration is controlled using the **Security** area of ECL Watch. To access the Security area click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.




There are three areas where permissions may be set:

- **Users**. Shows all the users currently setup. Use this area to add or delete a user, edit a user's details, set/reset a user's password and view the permissions currently assigned to a user.
- **Groups**. Shows all the groups currently setup. Use this area to add or delete a group, view and edit the members of a group, view and edit the permissions that have been set for a group.
- **Permissions**. Shows the features of the HPCC System where permissions may be set. Use this area to view the permissions currently set for any area of the HPCC System, or to add groups and users and set/modify their permission for a specific feature

	NOTE: Use caution when setting any explicit deny permission setting. The most restrictive permission always applies.
---	--


Information about your account

To find out more information about your account, in ECL Watch click on the **Logged In As:** link at the top of the ECL Watch page.



1. Click on the **Logged In As:** link.

A User Details tab with your account information displays.

A screenshot of a 'User Details' window. The title bar says 'User Details'. The window contains a 'Save' button at the top left. Below it is a section for a user named 'FranklinX'. The fields are as follows:

Username:	FranklinX
First Name:	Franklin
Last Name:	Xavier
Old Password:	<input type="text"/>
New Password:	<input type="text"/>
Confirm Password:	<input type="text"/>
Password Expiration:	2016-06-26

2. Confirm the User Name that you are logged in as.

Note that Administrator rights are needed to manage users and permissions.

Ensure you are using an account with Administrator rights if you intend to manage users or permissions.

3. Verify the password expiration date, or if password is set to expire.

You can also change your password here, if desired.


Setting and modifying user permissions

In a security-enabled environment, access to ECL Watch and its features is controlled using a login and password. The **Users** area enables you to control who has access to ECL Watch and the features of your HPCC System to which they have access. Permissions can be set for users based on their individual needs and users can also be added to groups which have already been set up. Use the **Users** menu item to:

- Add a new user (**note**: the Username cannot be changed)
- Delete a user
- Add a user to a group
- Change a user's password
- Modify the details/permissions of an individual user

Adding and editing users


To access the user administration sections click on the **Operations** icon, then click the **Security** link from the navigation sub-menu. Click on the **Users** tab to add or edit users.



All current users are identified in the list by their Username and Full Name.

To add a new user to the list of authenticated users:

To add a new user you must have Administrator level access.



1. Press the **Add** button.

The add user dialog displays.

2. Enter a **Username**.

This is the login name to use ECL Watch, ECL IDE, WsECL, etc.

3. Enter the **First Name** and **Last Name** of the user.

This information helps to easily identify the user and is displayed in the **Full Name** field on the main **Users** window.

4. Enter a **Password** for the user and then confirm it in the **Retype Password** field.

NOTE: The password must conform to the policy of your security manager server.

5. Press the **Add** button.

A successful addition opens a new tab where you can verify the new user's information.

6. Press the **Save** button.

Once added, the new user displays in the list and you can modify details and set permissions as required.

To modify a user's details:


Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users tab**.

The users display in a list.

2. Select the user (or users) to modify. Click on the **Username** link to open the users' details tab.

To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.



A tab opens for each user selected. On each user's tab there are several sub-tabs.

The user's details are on the **Summary** tab.

3. Modify the user's details as required (if more than one user selected, repeat for each user).

Note: The **Username** cannot be changed.

4. Press the **Save** button.

A confirmation message displays.

To add a user to a group:


Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users** tab.

The users display in a list.

2. Select the user (or users) to modify. Click on the **Username** link to open the users' details tab.

To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.




A tab opens for each user selected. On each user's tab there are several sub-tabs.

The user's details are on the **Summary** tab.

3. Click on the tab for the user to modify (if more than one user selected, repeat for each user).

On the user's tab there are several sub-tabs.



Click on the **Member Of** sub-tab to modify that user's groups.

4. On the **Member Of** tab for that user, a list of the available groups display.


To add the user to the group, check the box next to the desired group.

5. The changes are automatically saved. Close the tab.

To promote a user to an Administrator

To modify a user's credentials you must have Administrator level access. To promote a user to an HPCC Administrator, add the user to the **Administrators** group.

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.




1. Click on the **Users tab**.

The users display in a list.

2. Select the user (or users) to promote. Click on the **Username** link to open the users' details tab.

To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.




A tab opens for each user selected. On each user's tab there are several sub-tabs.

The user's details are on the **Summary** tab.

3. Click on the tab for the user to modify (if more than one user selected, repeat for each user).

On the user's tab there are several sub-tabs.

Click on the **Member Of** sub-tab.



4. Select **Administrators** by placing a check in box.

NOTE: The name of the default Administrator group could vary. For example, in Active Directory, it is "Administrators", in OpenLDAP it is "Directory Administrators".

5. The changes are automatically saved. Close the tab(s).

To delete a user from a group:

To delete a user from a group you must have Administrator level access.


Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users** tab.

The users display in a list.

2. Select the user (or users) to remove. Click on the **Username** link to open the users' details tabs.


To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.



A tab opens for each user selected. On each user's tab there are several sub-tabs.

3. Click on the tab of the user to modify (if multiple users selected, repeat for each user).

On the user's tab there are several sub-tabs.



Click on the **Member Of** sub-tab to modify that user's groups.

4. On the **Member Of** tab for that user, there is a list of the available groups.

There is a check in the box next to each group that user belongs to.

To remove that user from a group, uncheck the box next to the desired group.

5. The changes are automatically saved. Close the tab.

To change a user's password:


Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users tab**.

The users display in a list.

2. Select the user (or users) to modify. Click on the **Username** link to open the users' details tab.

To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.



A tab opens for each user selected. On that tab there are several sub-tabs.

The user details are on the **Summary** tab.

3. Select the **Summary** tab.
4. Change the password in the **Password** and **Retype New Password** fields as required on the User details summary tab (if multiple users selected, repeat for each user).

Note: The **Username** cannot be changed.

5. Press the **Save** button.

A confirmation message displays.

To delete a user from the list of authenticated users:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users** tab.

The users display in a list.

2. Check the box to the left of the user(s) you want to remove.

Note: These users will no longer have access to ECL Watch.

3. Press the **Delete** action button.

Confirmation displays.

Setting permissions for an individual user

There may be occasions when you need to modify the permissions for individual users. For example, users may have individual security needs that are not completely covered in any group or, there may be occasions when a user requires temporary access to an HPCC feature. Permissions set in this area of ECL Watch only affect the user you choose. Most individual permissions you set here overwrite ones set in any group to which the user belongs, except in the case of an explicit deny.

To set permissions for an individual user:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Users** tab.


The users display in a list.

2. Select the user (or users) to modify. Click on the **Username** link to open the users' details tab.

To select multiple users, check the box next to the Username to select. This enables the Users action buttons. Press the **Open** action button.

3. Click on the tab of the username to modify (if multiple users selected, repeat for each user).

On the user's tab there are several sub-tabs.



The screenshot shows the ECL Watch User Details interface. At the top, there are tabs for 'Users', 'Groups', and 'Permissions'. Below these are three user cards: 'BuildersGroup', 'DDuck', and 'FranklinX'. Under the 'Permissions' tab, there are sub-tabs: 'Summary', 'Member Of', 'Active Permissions' (which is highlighted with a red oval), and 'Available Permissions'. A tooltip 'Permissions' and 'Inherited permission: StateGroup' is visible. Below the tabs is a table with columns: 'Resource', 'Permissions', 'Allow Access', 'Allow Read', 'Allow Write', and 'Allow Execute'. The table lists various system resources and their permissions. The 'Active Permissions' tab shows checkboxes for each permission type (Allow Access, Allow Read, Allow Write, Allow Execute) for each resource. The 'Available Permissions' tab shows a list of permission sets that can be applied.

Resource	Permissions	Allow Access	Allow Read	Allow Write	Allow Execute
FileScope	hpcinternal:dduck	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	ClusterTopologyAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	ConfigAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	EclDirectAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	FileDesprayAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	FileDkcAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
SMC Feature	FileIOAccess	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Click on the **Active Permissions** sub-tab to view the user's current permissions.

4. Click on the **Available Permissions** tab to see all the sets of permissions that are available to apply to that user.

When you select permissions from the Available Permissions tab, they display and can be set in the Active Permissions tab.

5. Click on the arrow next to the resource to display the permissions that can be set for that resource.

Resource	Allow Access	Allow Read	Allow Write	Allow Full	Deny Access	Deny Read
▶ Workunit Scopes						
▶ Esp Features for EclDirectAccess						
Access to EclDirectAccess	<input type="checkbox"/>					
▶ Esp Features for WsEcl						
▶ Esp Features for SMC						
◀ File Scopes						
filenew1	<input type="checkbox"/>					

The list of permission groups currently set for this user and the ones the user has inherited are also listed. Click the arrow to allow setting the individual resource settings.

6. There may be more than one resource setting available in each group, be sure to set the permissions for each setting as required.

7. Check the boxes that **allow** and **deny** access as required for the user.

Resource	Allow Access	Allow Read	Allow Write	Allow Full
▶ Esp Features for SMC				
Access to cluster topology	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Access to super computer environment	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Access to DFU	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to DFU exceptions	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to DFU workunits	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to DFU XRef	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



NOTE: Use caution when setting any explicit **deny** permission setting. The most restrictive permission always applies.

8. The changes are automatically saved. Close the tab.

Setting and modifying group permissions


Setting up groups ensures that all users with the same permission needs have the same permission settings. You can give users the access they require to the feature areas of HPCC that they need. There is no limit to the number of groups you can create. You can create as many groups as you need to control access for all your users regardless of their tasks.

Use the **Groups** menu item to:

- Add a new group.
- Delete a group.
- Add members to a group.
- Modify the permissions for a group.

Adding and editing groups

When adding or changing the permissions for a group, all members of that group are given those permission settings. So it is important to be sure that you are giving or denying access to features appropriate for the members of that group. If you need to make a change for a single user (or small number of users), it is probably better to make that change for each individual user as illustrated in the previous sections.




To modify groups, click on the **Operations** icon, then click the **Security** link from the navigation sub-menu. Click on the **Groups** tab.

To add a new group:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Groups** tab.
2. Press the **Add** action button button.



This opens a dialog where you can enter the name for the group.

3. Enter a **Group Name**.
4. Enter the fully qualified Distinguished Name for the owner of the group **Managed By** field.
5. Enter a description of the group. (optional)
6. Press the **Add** button.

This opens a new tab for the group and several sub tabs

The **Summary** sub-tab displays the group name.

The **Members** tab displays the list of users, check the box next to each user to add to the group.

The **Active Group Permissions** tab displays the permissions applied to the group.

The **Available Group Permissions** tab displays all the available permissions, selecting from the Available Permissions applies them to the Active Group Permissions.

You can set the permissions and add members to this group from the respective sub-tabs on that group tab.

To delete a group:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Groups** tab.
2. Locate the group in the list and check the checkbox next to it.
3. Press the **Delete** action button.

4. Press the **OK** confirmation button.

The group no longer displays in the list.

To add new members to a group:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Groups** tab.
2. Locate the group in the list and check the box next to it.
3. Press **Open** action button.

This opens a new tab for the group.

The sub-tabs display: **Summary**, **Members**, **Active Group Permissions**, and **Available Group Permissions**.

4. Select the **Members** tab.

The members tab displays a list of all users on the system. The users that belong to the selected group have a check in the box next to them.

5. Check the box(es) to the left of the users you want to add to the group.
6. The changes are automatically saved. Close the tab.

To delete members from a group:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.

1. Click on the **Groups** tab.
2. Locate the group in the list and check the box next to it.
3. Press the **Open** action button.

This opens a new tab for the group.

The Groups tab has several sub-tabs: **Summary**, **Members**, **Active Group Permissions** and **Available Group Permissions**.

4. Select the **Members** tab.

The Members tab displays a list of all users on the system. The users that belong to the selected group have a check in the box next to them.

5. Uncheck the box(es) to the left for all users you want to delete from the group.
6. The changes are automatically saved. Close the tab.

Setting permissions for a group

By default, all users are members of the **Authenticated Users** group. The **Authenticated Users** group has access rights to almost all resources. To set up more restricted controls, you should create specific groups with more restricted permissions.


You can then create groups with only those access rights you wish to grant. This approach allows the most flexibility since a single User ID can have multiple group memberships.

As a best practice, you should use **Allow** instead of **Deny** to control access. Denies should be used only as an exception, when possible. If you wish to deny a user access to some specific control, a good practice would be to create a group for that, place the user(s) in that group, then you can deny access to that group.

Remember the most restrictive control takes precedence. For example, if a user is in a group that has deny permission to file access, and the user is in another group where file access is allowed, that user will still not have file access.


To set permissions for a group:

Click on the **Operations** icon, then click the **Security** link from the navigation sub-menu.



1. Click the **Groups** tab.
2. Locate the group in the list and check the box next to it.
3. Press the **Open** action button.

This opens a new tab for the group.



The group tab displays the sub-tabs: **Summary**, **Members**, **Active Group Permissions** and **Available Group Permissions**.

4. Select the **Available Group Permissions** sub-tab. This displays all the available permission resources.
5. Click on the arrow to the left of the **Resource** to expand and expose the permission sets for the resources.

The groups permission resources display.

6. There may be more than one resource setting available in each group, be sure to set the permissions for each setting as required.
7. Check the boxes for **allow** and **deny** as required for the group.

The screenshot shows the 'Group Permissions' tab selected in the ECL Watch interface. The 'Resource' column lists several items, and the 'Allow Full' column for 'Access to DFU' is circled in red, indicating it is selected. The 'Allow' column for 'Access to DFU' also contains a checkmark.

Resource	Allow Access	Allow Read	Allow Write	Allow Full	Deny Access	Deny Read
Workunit Scopes	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Esp Features for EclDirectAccess	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Esp Features for WsEcl	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
▲ Esp Features for SMC	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to cluster topology	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to super computer environment	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to DFU	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Access to DFU exceptions	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



NOTE: Use caution when setting any explicit **deny** permission setting. The most restrictive permission always applies.

8. There may be more than one resource setting available, select the resource(s) you require from the drop list.
Repeat for each applicable resource.
9. The changes are automatically saved. Close the tab.

Plug-ins

You can add functionality to ECL Watch by installing plug-ins. These plug-ins are designed to integrate into the ECL Watch interface. After you install an approved plug-in, the plug-in icon displays in the navigation bar at the top of the ECL Watch page to provide access to the plug-in(s). Click on the plug-in icon to view the plug-ins page in ECL Watch.


Figure 104. ECL Watch Plug-in icon



Ganglia in ECL Watch

With the HPCC Systems® Ganglia-monitoring plug-in installed, you can view the Ganglia statistics and graphs through the ECL Watch interface. The default monitoring displays several key statistics, but you can customize and configure the views.


Figure 105. Ganglia in ECL Watch



Customize Monitoring

The default Ganglia page has a tab for Custom Monitoring where you can easily add custom monitoring components.


Figure 106. Ganglia Custom Monitoring



To customize the monitoring page;

1. Select the **Custom Monitoring** tab.
2. Press the **Metrics** button.
3. Use the drop menus to display the various graphing utilities.

Figure 107. Customize the Metrics



Installing Ganglia in ECL Watch


In order to use Ganglia in ECL Watch, you need to have Ganglia installed on your HPCC System. For details on installing Ganglia for ECL Watch, refer to the *HPCC Monitoring and Reporting* manual.

Nagios in ECL Watch

ECL Watch is set up for monitoring your system with Nagios. ECL Watch has an API that can interface with Nagios and provide Nagios monitoring right in ECL Watch. Nagios escalations can be pointed to any ECL Watch version 5.4 (and later) and are viewable directly in ECL Watch.

By default all ECL Watch services defined in the environment.xml will receive notifications generated using *hpcc-nagios-tools*. You can override that if not desired. The ECL Watch instances need not be in the cluster that is being monitored.

Figure 108. Nagios in ECL Watch




Once you have Nagios configured for your environment, you can see at a glance if there are any alerts. Along the top banner of the ECL Watch window, you will see a small indicator light. The light is darkened (gray) if there is no system data being reported, typically indicative that your system is not yet configured for monitoring.

The light is green when all systems are reporting normal. The light is yellow when there is warning. The light turns red when there is an alert. All the alerts are configurable through the Nagios configuration.

By default ECL Watch monitoring maintains the latest update for 30 minutes. This means that once Nagios stops escalations to ECL Watch any status, including Normal will expire from the list. Nagios escalations notification behavior and frequency is configurable, refer to the Nagios documentation for more information. An empty list could indicate 'no data' or 'no outages', by default no alerts generate when everything is up and running.

To delve further into any warnings or alerts, you can press the indicator light at the top. You can also access the *Primary Monitoring* page by pressing the **Operations** link, then press the **Monitoring** link in the navigation sub-menu.

Figure 109. Nagios in ECL Watch




This displays the all the messages and alerts reported to the monitoring system. For more information on a specific message, press the arrow next to the message you want.

Advanced Menu

There is a section at the top right on the navigation bar with some useful information and features. This section shows you who you are logged in as (if your system has authentication enabled). The Advanced menu is located on the right hand side of the navigation bar. There are several items that you can access from the advanced menu.

Figure 110. Advanced menu



There may be a number displayed on the menu link. A number displayed next to it indicates how many errors and warnings have been generated during your session. Click on the advanced menu to display a list of features.

Access the Advanced menu

You access the advanced menu items from the advanced menu link at the top right corner of ECL Watch.

The **Set Banner** link allows you to set a custom banner message at the top of your browser window when you open ECL Watch. You can use this feature to send messages to users.

The **Error/Warning(s)** link displays a tab showing you Errors, Warnings, and Information messages. You can filter this page by checking the boxes at the bottom of the tab. A copy facility is also provided.

The **Open Legacy ECL Watch** link opens a tab to the previous version of ECL Watch. The legacy version of ECL Watch is deprecated; this link is only available for a limited time to help in the transition.

The **Additional Resources** link opens a tab to the HPCC Systems® download page, where you can browse and download additional HPCC resources: documentation, white papers, training videos, wiki pages, the red book and other HPCC related source code.

The **Release Notes** link opens a tab with the relevant release notes for the version of HPCC that you are using. Read the release notes for more information specific to the release you are working on.

The **Configuration** link opens for viewing the xml version of the configuration file in use on your system.

The **About** link opens a dialog to display some information about the version of the HPCC platform and graph controls installed on your server.


User Details

The LOGGED IN AS link shows information about the current user on a cluster configured for authentication.

1. Click on the **LOGGED IN AS:** link.

The User Details window opens. The default window opens on the Summary tab.

Figure 111. User Details window



2. From The User Details page Summary tab, you can Confirm the User Name that you are logged in as.

You can change your password.

Note that Administrator rights are needed to manage users and permissions.

Ensure you are using an account with Administrator rights if you intend to manage users or permissions.

3. Verify the password expiration date, or if password is set to expire.

Change Password

If authentication is enabled on your HPCC system, you can change your password, right from the User Details window.

1. Click on the **LOGGED IN AS:** link.

The User Details window opens. The default window opens on the Summary tab. There are fields on the Summary tab where you can change your password.

2. Enter your desired new password.

Make sure it meets whatever criteria your system may have for passwords.

3. Confirm your new password.

Make sure that it matches the password you entered in the previous field.

4. Press the Save button. It is in the upper left portion of the window.

Permission groups

The second tab on the User Details window labelled Member Of, displays a list of groups. The groups your account belongs to, are indicated with a checkmark.

You must be an administrator to modify any of group settings.

User Permissions tab

The third tab on the User Details window labelled **User Permissions**, displays a list of permission settings. Note that Administrator rights are needed to manage users and permissions. Ensure you are using an account with Administrator rights if you intend to manage users or permissions.

This is where you can access the user permissions area. A more detailed description of the user permissions settings is covered in the User Permissions section.

Resources

The resources link can be found under the Operations Icon link. The resources link in ECL Watch provides a link to the HPCC Systems® web portal. Visit the HPCC Systems® Web Portal at <http://hpccsystems.com/> for software updates, plug-ins, support, documentation, and more. This is where you can find resources useful for running and maintaining HPCC on the web portal.

You can also get to the resources link on the HPCC Systems® web portal page, by clicking on the **Additional Resources** link found on the sub-menu of at the top right hand side of navigation bar.

ECL Watch provides a link to the HPCC portal's download page: <http://hpccsystems.com/download>. This is the page where you can download Installation packages, virtual images, source code, documentation, and tutorials.