



THE WINDOWS SANDBOX PARADOX

Nullcon 2015

James Forshaw @tiraniddo

Obligatory Background Slide


- Researcher in Google's Project Zero
- Specialize in Windows, especially local privilege escalation
- Never met a logical vulnerability I didn't like

What I'm Going to Talk About



<https://www.flickr.com/photos/23258385@N04/2237739552/>


Let's Write a Sandbox



<https://openclipart.org/detail/101707/happy-pencil-by-jonata>

Sandboxing Requirement #1


- Easy to get in, hard to get out



<http://upload.wikimedia.org/wikipedia/commons/d/d9/GravityPotential.jpg>

Sandboxing Requirement #2

- Protects the user's data from disclosure



<https://openclipart.org/detail/190821/cles-de-serrure---lock-keys-by-enolynn-190821>

Sandboxing Requirement #3

- Work within the limits of the OS



http://upload.wikimedia.org/wikipedia/commons/8/8b/MUTCD_R2-1.svg


Sandboxing Requirement #4

- Sandboxed application is usable
 - Limited Performance Impact




<http://pixabay.com/p-305189/>

Typical User-Mode Approach



Object Security Descriptor



Access Tokens

The screenshot shows the 'chrome.exe:2716 Properties' dialog box with the 'Security' tab selected. The 'User' field displays 'WIN-32RI1CK49EL\user' and the 'SID' field displays 'S-1-5-21-3711643808-3202222375-1035956708-1001'. The 'Groups' list includes 'BUILTIN\Administrators', 'BUILTIN\Users', 'CONSOLE LOGON', 'Everyone', 'LOCAL', 'Logon SID (S-1-5-5-0-5071873)', 'Mandatory Label\Medium Mandatory Level', and 'NT AUTHORITY\Authenticated Users'. The 'Privileges' list includes 'SeChangeNotifyPrivilege', 'SeIncreaseWorkingSetPrivilege', 'SeShutdownPrivilege', 'SeTimeZonePrivilege', and 'SeUndockPrivilege'. Arrows point from labels on the left to these specific fields.

User Security Identifier

Groups


Mandatory Label

Privileges


| Group | Flags |
|--|-----------|
| BUILTIN\Administrators | Deny |
| BUILTIN\Users | Mandatory |
| CONSOLE LOGON | Mandatory |
| Everyone | Mandatory |
| LOCAL | Mandatory |
| Logon SID (S-1-5-5-0-5071873) | Mandatory |
| Mandatory Label\Medium Mandatory Level | Integrity |
| NT AUTHORITY\Authenticated Users | Mandatory |

| Privilege | Flags |
|-------------------------------|-----------------|
| SeChangeNotifyPrivilege | Default Enabled |
| SeIncreaseWorkingSetPrivilege | Disabled |
| SeShutdownPrivilege | Disabled |
| SeTimeZonePrivilege | Disabled |
| SeUndockPrivilege | Disabled |


Resource Access Check



Mandatory Integrity Level Check



Owner Check



Kernel DACL Check


Token User and Groups

| |
|---------------|
| User SID |
| BUILTIN\Users |
| Logon SID |

DACL

| | |
|------------------------|----|
| Everyone | RO |
| BUILTIN\Administrators | RW |
| BUILTIN\Users | RW |

Kernel Access Check




Token User and Groups

| |
|---------------|
| User SID |
| BUILTIN\Users |
| Logon SID |

DACL


| | |
|------------------------|----|
| Everyone | RO |
| BUILTIN\Administrators | RW |
| BUILTIN\Users | RW |

Kernel Access Check



Current Granted Access: Read Only

Kernel Access Check




Final Granted Access: Read/Write

Quick and Dirty Sandbox

- Reduce IL of Token from Medium to Low
- Used for IEProtected Mode
- Has many problems:
 - Can create as many processes as it likes
 - Can sniff on certain Windows events
 - Can read almost any common resource, files, registry keys etc.
- Not a supported “Security Boundary”

Job Object Restrictions

- Allow us to prevent process creation
- Limit access to certain aspects of the window system
- Still not a “Security Boundary”



Restricted Access Tokens

CreateRestrictedToken function


The **CreateRestrictedToken** function creates a new [access token](#) that is a restricted version of an existing access token. The restricted token can have disabled [security identifiers](#) (SIDs), deleted privileges, and a list of restricting SIDs. For more information, see [Restricted Tokens](#).

Syntax

C++

```
BOOL WINAPI CreateRestrictedToken(
    _In_      HANDLE ExistingTokenHandle,
    _In_      DWORD Flags,
    _In_      DWORD DisableSidCount,
    _In_opt_  PSID_AND_ATTRIBUTES SidsToDisable,
    _In_      DWORD DeletePrivilegeCount,
    _In_opt_  PLUID_AND_ATTRIBUTES PrivilegesToDelete,
    _In_      DWORD RestrictedSidCount,
    _In_opt_  PSID_AND_ATTRIBUTES SidsToRestrict,
    _Out_     PHANDLE NewTokenHandle
);
```

Restricted Token Access Check



Limits of Restricted Tokens

- What we CAN do:
 - Disable all group SIDs (Deny only)
 - Remove all privileges
 - Add a unused restricted SID
 - Lower the integrity level
- What we CAN'T do:
 - Change the user's identity
 - Remove any UAC linked tokens

Create Our Sandboxed Process

CreateProcessAsUser function


Creates a new process and its primary thread. The new process runs in the security context of the user represented by the specified token.

Syntax

C++

```
BOOL WINAPI CreateProcessAsUser(  
    _In_opt_      HANDLE hToken,  
    _In_opt_      LPCTSTR lpApplicationName,  
    _Inout_opt_   LPTSTR lpCommandLine,  
    _In_opt_      LPSECURITY_ATTRIBUTES lpProcessAttributes,  
    _In_opt_      LPSECURITY_ATTRIBUTES lpThreadAttributes,  
    _In_          BOOL bInheritHandles,  
    _In_          DWORD dwCreationFlags,  
    _In_opt_      LPVOID lpEnvironment,  
    _In_opt_      LPCTSTR lpCurrentDirectory,  
    _In_          LPSTARTUPINFO lpStartupInfo,  
    _Out_          LPPROCESS_INFORMATION lpProcessInformation  
);
```


Crash!



```
Pid 976 - WinDbg:6.3.9600.16384 AMD64

File Edit View Debug Window Help

Command

WARNING: Whitespace at start of path element

***** Symbol Path validation summary *****
Response                               Time (ms)      Location
Deferred                               0              srv*

***** Symbol Path validation summary *****
Response                               Time (ms)      Location
Deferred                               0              srv*

Microsoft (R) Windows Debugger Version 6.3.9600.17029 AMD64
Copyright (c) Microsoft Corporation. All rights reserved.

*** wait with pending attach

***** Symbol Path validation summary *****
Response                               Time (ms)      Location
Deferred                               0              srv*
Deferred                               0              srv*
Deferred                               0              srv*
Symbol search path is: http://chromium-browser-symsrv.commondatastorage.googleapis.com;srv*;srv*c:\Symbols*http://msdl.microsoft.com/download/symbols
Executable search path is: srv*
ModLoad: 00007ff7`16290000 00007ff7`16376000  c:\windows\system32\calc.exe
ModLoad: 00007ffc`30d40000 00007ffc`30ee6000  C:\Windows\SYSTEM32\ntdll.dll
Break-in sent, waiting 30 seconds...
WARNING: Break-in timed out, suspending.
This is usually caused by another thread holding the loader lock
(3d0.198): Wake debugger - code 80000007 (first chance)
ntdll!RtlRaiseStatus+0x20:
00007ffc`30e2c0b4 488b85b800000000  mov     rax,qword ptr [rbp+0B8h] ss:000000a4`540af0f8=00007ffc30e2c0b4
0:000> k
Child-SP      RetAddr      Call Site
000000a4`540aef40 00007ffc`30df8386 ntdll!RtlRaiseStatus+0x20
000000a4`540af4e0 00007ffc`30da9c6a ntdll!LdrpInitialize+0x4e6ca
000000a4`540af550 00000000`00000000 ntdll!LdrInitializeThunk+0xe

0:000> |
```

Process Initialization




Uninitialized Process


The diagram illustrates the components of process initialization. On the left is a large orange rounded rectangle labeled 'Uninitialized Process'. To its right is a gray cylinder labeled 'External Resources'. There are no lines or arrows connecting these two elements, suggesting they are separate but related concepts in the context of process initialization.

External
Resources


Process Initialization



Process Initialization




Attack Surface



Kernel Attack Surface


~300 Syscalls



Kernel Attack Surface

~300 Syscalls

~400 Syscalls






Kernel Attack Surface

~300 Syscalls

~400 Syscalls



~1000 Win32k



Other Platforms Have it Easy?



SECure COMPUting with filters

=====

Introduction

A large number of system calls are exposed to every userland process with many of them going unused for the entire lifetime of the process. As system calls change and mature, bugs are found and eradicated. A certain subset of userland of available system call surface exposed to the use with those applicat

SANDBOX(7)

BSD Miscellaneous Information Manual

SANDBOX(7)

NAME

sandbox -- overview of the sandbox facility

SYNOPSIS

#include <sandbox.h>

DESCRIPTION

The **sandbox** facility allows applications to voluntarily restrict their access to operating system resources. This safety mechanism is intended to limit potential damage in the event that a vulnerability is exploited. It is not a replacement for other operating system access controls.

New processes inherit the **sandbox** of their parent. Restrictions are generally enforced upon acquisition of operating system resources only. For example, if file system writes are restricted, an application will not be able to **open(2)** a file for writing. However, if the application already has a file descriptor opened for writing, it may use that file descriptor regardless of restrictions.


SEE ALSO

sandbox-exec(1), **sandbox_init(3)**, **sandboxd(8)**


Mac OS X

January 29, 2010

Mac OS X



Device Drivers




Opening a Device Name


```
\Device\Harddisk1\SomeName
```

Native NT Path

Opening a Device Name



Opening a Device Name



Securing the Device

- So what's the problem?
 - By default security of device path enforced by kernel
 - Security of namespace IS NOT enforced by kernel
- If the driver doesn't do its own checking or sets appropriate flags there's NO security

Example: Windows Sockets

- Would like to block network access, so let's do a quick test:

```
WORD wVersionRequested = MAKEWORD(2, 2);  
WSADATA wsaData;  
  
if (WSAStartup(wVersionRequested, &wsaData) != 0)  
    return 1;  
}  
  
/* Do socket stuff*/  
WSACleanup();
```

Example: Windows Sockets

- Would like to block network access, so let's do a quick test:

```
WORD wVersionRequested = MAKEWORD(2, 2);  
WSADATA wsaData;  
  
if (WSAStartup(wVersionRequested, &wsaData) != 0)  
    return 1;  
}  
  
/* Do socket stuff*/  
WSACleanup();
```



Example: Windows Sockets

- On Linux/OSX sockets implemented as system calls
- Implemented in the Ancillary Function Driver
- You interact with it via `\Device\Afd`, open the device namespace such as `\Device\Afd\Endpoint`
- No security on the namespace :(
- Further interaction via `DeviceIoControl`

Native Sockets

```
BOOL ConnectSocket(HANDLE hSocket, u_short srcport,
                   const SOCKADDR_IN& inaddr)
{
    ConnectData data = { 0 };
    data.sin_family = AF_INET;
    data.sin_port = htons(srcport);
    data.inaddr = inaddr;

    DWORD dwSize;

    return DeviceIoControl(hSocket, 0x00012007,
                           &data, sizeof(data), nullptr,
                           0, &dwSize, nullptr);
}
```


Demo

Enumerating Unrestricted Device Drivers

Accessing Resources

- Two schools of thought
 - Ensure the sandboxed token can access the resources you need
 - Heavily restrict and handle all access through the broker
- Each has pros and cons:
 - Direct access is going to have a slightly better performance
 - Broker access means you can meditate what is accessed with a finer grain of control

Direct Resource Access




Sharing Resource Access

- Adding appropriate entries to security descriptor is easy to allow shared access
- Has advantage that everything can be done in the sandboxed process
- No overhead
- Trouble is any “supported” operation can be performed

Bad Registry


- The registry supports symbolic links
- This isn't very well documented
- No permissions required to create these links other than being able to create a registry
- Surely not an issue?
 - It is if a higher privileged process also accesses those keys

IE EPM Escape / Audio Server




<https://code.google.com/p/google-security-research/issues/detail?id=99>

IE EPM Escape / Audio Server



<https://code.google.com/p/google-security-research/issues/detail?id=99>

IE EPM Escape / Audio Server



<https://code.google.com/p/google-security-research/issues/detail?id=99>

Lack of Documentation

- No documentation on how to defend yourself against this attack

Syntax

C++

```
LONG WINAPI RegCreateKeyEx(  
    _In_      HKEY hKey,  
    _In_      LPCTSTR lpSubKey,  
    _Reserved_ DWORD Reserved,  
    _In_opt_  LPTSTR lpClass,  
    _In_      DWORD dwOptions,  
    _In_      REGSAM samDesired,  
    _In_opt_  LPSECURITY_ATTRIBUTES lpSecurityAttributes,  
    _Out_     PHKEY phkResult,  
    _Out_opt_ LPDWORD lpdwDisposition  
);
```

Lack of Documentation

- No documentation on how to defend yourself against this attack

Syntax

C++

```
LONG WINAPI RegCreateKeyEx(  
    _In_      HKEY hKey,  
    _In_      LPCTSTR lpSubKey,  
    _Reserved_ DWORD Reserved,  
    _In_opt_  LPTSTR lpClass,  
    _In_      DWORD dwOptions,  
    _In_      REGSAM samDesired,  
    _In_opt_  LPSECURITY_ATTRIBUTES lpSecurityAttributes,  
    _Out_     PHKEY phkResult,  
    _Out_opt_ LPDWORD lpdwDisposition  
);
```

Reserved

This parameter is reserved and must be zero.

Lack of Documentation

- No documentation on how to defend yourself against this attack

Syntax

C++


```
LONG WINAPI RegCreateKeyEx(  
    _In_      HKEY hKey,  
    _In_      LPCTSTR lpSubKey,  
    _Reserved_ DWORD Reserved,
```

OpenOptions [in]

Specifies the options to apply when opening the key. Set this parameter to zero or to the bitwise OR of one or more of the following REG_OPTION_XXX flag bits:

| <i>OpenOptions</i> flag | Description |
|-------------------------|---|
| REG_OPTION_OPEN_LINK | The key is a symbolic link. This flag is not used by device and intermediate drivers. |

Broker Resource Access



Filesystem Fun

- Instead of changing security of resources instead we'll do everything through the broker
- Let's us hook calls to CreateFile and pass them to the broker

Win32 Path Support

| Path | Description |
|---------------------|------------------------------------|
| some\path | Relative path to current directory |
| c:\some\path | Absolute directory |
| \\.c:\some\path | Device path, canonicalized |
| \\?\c:\some\path | Device path, non-canonicalized |
| \\server\share\path | UNC path to share on server |

Legacy Filesystem Behaviour

- MS-DOS has a lot to answer for, these files names don't do what you expect:
 - "COM1" -> Opens the first serial port!
 - "LPT1" -> Opens the parallel port?!
 - And others

Legacy Filesystem Behaviour

- MS-DOS has a lot to answer for, these files names don't do what you expect:
 - "COM1" -> Opens the first serial port!
 - "LPT1" -> Opens the parallel port?!
 - And others
- Surely an absolute path will work?
 - c:\path\LPT1 -> Opens the parallel port!
 - \\.\c:\path\LPT1 -> Creates the file you expect
- Now got a file the user can't delete!

More edge cases

- Trailing spaces are removed from paths:
 - "c:\some\path " -> "c:\some\path"
 - "\\.\some\path " -> "c:\some\path"
 - "\\?\some\path " -> "c:\some\path "
- Congratulations you've again made a file a user can't delete

Canonicalization

- Type of Win32 path affects canonicalization behaviour

| Path | Result of Canonicalization |
|------------------------|----------------------------|
| c:\path\..\badgers | c:\badgers |
| c:\..\d:\badgers | c:\d:\badgers |
| \\.\c:\path\..\badgers | c:\badgers |
| \\.\c:\..\d:\badgers | d:\badgers (WTF!) |
| \\?\c:\path\..\badgers | c:\path\..\badgers |

Device Escape Syntax


- Paths `\\.\` and `\\?\` really escape `CreateFile` into the NT object namespace, can do fun like:

| Path | Result |
|--|----------------------------------|
| <code>\\.\GLOBALROOT\??\c:\badgers</code> | <code>c:\badgers</code> |
| <code>\\.\c:..\GLOBALROOT\??\c:\badgers</code> | <code>c:\badgers</code> |
| <code>\\.\c:..\UNC\server\share\path</code> | <code>\\server\share\path</code> |

Invalid Character Checks

- NTFS has a number of invalid characters:
 - `< > : " / \ | ? *`
- Tempting to use this to prevent things like command injection
- Use canonicalization:
 - `c:\windows\system32\calc.exe"..\..\..\some\path`
- Use alternate data streams
 - `c:\some\path\my.exe:" something`

Hybrid Resource Access



Hybrid Resource Access

- Windows uses handles to reference open resources
- We can use the *DuplicateHandle* method from the broker to copy that handle back
- Only pay penalty on resource open/create not read and write
- Any risks in doing this?

Reparse Points

- NTFS supports directory symlinks
 - Supports file symlinks as well but you need additional privileges
- Linux/OSX have a specific system call 'symlink' to create file system symbolic links
- In Windows you just a file handle to a directory

Reparse Points

- Need to open a handle to a directory
 - Pass `FILE_DIRECTORY_FILE` to `NtCreateFile`
- What if the broker doesn't allow you to specify that?
- Use the NTFS alternate data stream name instead
 - `dir::$INDEX_ALLOCATION` or
 - `dir::$I30:$INDEX_ALLOCATION`
- Just because

Mixed Semantics

- ActiveX install broker has a function to load a signed DLL

```
BOOL IsSignedFile(string path) {  
    CreateFile(path, ...);  
    ...  
}  
  
BOOL RunInstaller(string path) {  
    path = CanonicalizePath(path);  
  
    if (IsSignedFile(path)) {  
        LoadLibrary(path);  
    }  
}
```

Mixed Semantics

lpFileName [in]

The name of the module. This can be either a library module (a .dll file) or an executable module (an .exe file). The name specified is the file name of the module and is not related to the name stored in the library module itself, as specified by the **LIBRARY** keyword in the module-definition (.def) file.

If the string specifies a full path, the function searches only that path for the module.

If the string specifies a relative path or a module name without a path, the function uses a standard search strategy to find the module; for more information, see the Remarks.

If the function cannot find the module, the function fails. When specifying a path, be sure to use backslashes (\), not forward slashes (/). For more information about paths, see [Naming a File or Directory](#).

If the string specifies a module name without a path and the file name extension is omitted, the function appends the default library extension .dll to the module name. To prevent the function from appending .dll to the module name, include a trailing point character (.) in the module name string.

Mixed Semantics

lpFileName [in]

The name of the module. This can be either a library module (a .dll file) or an executable module (an .exe file). The name specified is the file name of the module and is not related to the name stored in the library module itself, as specified by the **LIBRARY** keyword in the module-definition (.def) file.

If the string specifies a full path, the function searches only that path for the module.

If the string specifies a relative path or a module name without a path, the function uses a standard search strategy to find the module; for more information, see the Remarks.

If the function cannot find the module, the function fails. When specifying a path, be sure to use backslashes (\), not forward slashes (/). For more information about paths, see [Naming a File or Directory](#).

If the string specifies a module name without a path and the file name extension is omitted, the function appends the default library extension .dll to the module name. To prevent the function from appending .dll to the module name, include a trailing point character (.) in the module name string.

Mixed Semantics

| IpFileName Parameter | Path loaded |
|----------------------|---------------------|
| c:\my\path\test.dll | c:\my\path\test.dll |


Mixed Semantics

| IpFileName Parameter | Path loaded |
|----------------------|---------------------|
| c:\my\path\test.dll | c:\my\path\test.dll |
| c:\my\path\test | c:\my\path\test.dll |

Mixed Semantics

| IpFileName Parameter | Path loaded |
|----------------------|---------------------|
| c:\my\path\test.dll | c:\my\path\test.dll |
| c:\my\path\test | c:\my\path\test.dll |
| c:\my\path\test. | c:\my\path\test |

Sharing Sections



Unnamed Resources

- Certain classes of Windows resources opt out of security when they have no names
- Section objects are just one such type
- Leads to problems.

IPC Technologies

- Three main ways of doing IPC on Windows
 - Named Pipes
 - Local RPC (ALPC)
 - Sockets
- Already seen sockets aren't securabled resources
- What problems would these come with?

Named Pipes

- Named pipe servers are created using *CreateNamedPipe* method (really *NtCreateNamedPipeFile*)
- Named pipe clients are created using the normal *NtCreateFile* API

Supporting Creating Pipes

C++

```
HANDLE WINAPI CreateNamedPipe(  
    _In_      LPCTSTR lpName,  
    _In_      DWORD dwOpenMode,  
    _In_      DWORD dwPipeMode,  
    _In_      DWORD nMaxInstances,  
    _In_      DWORD nOutBufferSize,  
    _In_      DWORD nInBufferSize,  
    _In_      DWORD nDefaultTimeout,  
    _In_opt_  LPSECURITY_ATTRIBUTES lpSecurityAttributes  
);
```

Parameters

lpName [in]

The unique pipe name. This string must have the following form:

\\.\pipe\pipename

The pipename part of the name can include any character other than a backslash, including numbers and special characters. The entire pipe name string can be up to 256 characters long. Pipe names are not case sensitive.

Chrome CreateNamedPipe IPC

```
HANDLE CreateNamedPipeAction(string name, ...) {  
    // Name is lowercase already  
    if (name.startsWith("\\\\.\\pipe\\chrome.") {  
        return CreateNamedPipe(name, ...);  
    } else {  
        return NULL;  
    }  
}
```

Chrome CreateNamedPipe IPC

- Intention was to only allow named pipes with a prefix
- Even though the function should only ever open named pipes it's using the `\\.\` syntax.
- Canonicalize!
 - `\\.\pipe\chrome.xxx\..\mypipe`

Is Windows Getting Better?

Reducing Kernel Attack Surface

SetProcessMitigationPolicy function

Sets the mitigation policy for the calling process.


Syntax

C++


```
BOOL WINAPI SetProcessMitigationPolicy(  
    _In_  PROCESS_MITIGATION_POLICY MitigationPolicy,  
    _In_  PVOID lpBuffer,  
    _In_  SIZE_T dwLength  
);
```

Kernel Attack Surface


~300 Syscalls



~400 Syscalls



~1000 Win32k




Bring Forth the LowBox Token

```
NTSTATUS NtCreateLowBoxToken(  
    PHANDLE LowBoxTokenHandle,  
    HANDLE TokenHandle,  
    ACCESS_MASK DesiredAccess,  
    OBJECT_ATTRIBUTES * ObjectAttributes,  
    PSID PackageSid,  
    ULONG CapabilityCount,  
    PSID_AND_ATTRIBUTES Capabilities,  
    ULONG HandleCount,  
    PHANDLE Handles  
);
```

The Good Parts


- LowBox tokens work much like restricted tokens
 - Replace restricted SIDs with capability SIDs
- Built in firewall rules to restrict sockets based on capabilities
- Makes it easy to restrict access to user files without having to worry as much about configuration

LowBox Token Access Check




Integrity Level Check

- LowBox tokens are always marked as having Low Integrity
- So it works as before?
- NO!



Mandatory Integrity Level Check



Drawbridge / PicoProcess

- Isolation/sandbox technologies developed by Microsoft
- Uses process isolation to secure an application
- Can be completely isolated from the kernel, including system call filtering
- Currently not available in consumer versions of Windows :(

Questions?