

## NAME

CPANPLUS::Shell::Default::Plugins::Source

## SYNOPSIS

```
CPAN Terminal> /source /tmp/list_of_commands /tmp/more_commands
```

## DESCRIPTION

This is a `CPANPLUS::Shell::Default` plugin that works just like your unix shells `source(1)` command; it reads in a file that has commands in it to execute, and then executes them.

A sample file might look like this:

```
# first, update all the source files
x --update_source

# find all of my modules that are on the CPAN
# test them, and store the error log
a ^KANE$'
t *
p /home/kane/cpan-autotest/log

# and inform us we're good to go
! print "Autotest complete, log stored; please enter your commands!"
```

Note how empty lines, and lines starting with a '#' are being skipped in the execution.

## BUG REPORTS

Please report bugs or other issues to [bug-cpanplus@rt.cpan.org](mailto:bug-cpanplus@rt.cpan.org).

## AUTHOR

This module by Jos Boumans [kane@cpan.org](mailto:kane@cpan.org).

## COPYRIGHT

The CPAN++ interface (of which this module is a part of) is copyright (c) 2001 - 2007, Jos Boumans [kane@cpan.org](mailto:kane@cpan.org). All rights reserved.

This library is free software; you may redistribute and/or modify it under the same terms as Perl itself.

## SEE ALSO

*CPANPLUS::Shell::Default*, *CPANPLUS::Shell*, *cpanp*