

NAME

CPANPLUS::Internals::Utils

SYNOPSIS

```
my $bool = $cb->_mkdir( dir => 'blah' );
my $bool = $cb->_chdir( dir => 'blah' );
my $bool = $cb->_rmdir( dir => 'blah' );

my $bool = $cb->_move( from => '/some/file', to => '/other/file' );
my $bool = $cb->_move( from => '/some/dir', to => '/other/dir' );

my $cont = $cb->_get_file_contents( file => '/path/to/file' );

my $version = $cb->_perl_version( perl => $^X );
```

DESCRIPTION

CPANPLUS::Internals::Utils holds a few convenience functions for CPANPLUS libraries.

METHODS

\$cb->_mkdir(dir => '/some/dir')

_mkdir creates a full path to a directory.

Returns true on success, false on failure.

\$cb->_chdir(dir => '/some/dir')

_chdir changes directory to a dir.

Returns true on success, false on failure.

\$cb->_rmdir(dir => '/some/dir');

Removes a directory completely, even if it is non-empty.

Returns true on success, false on failure.

\$cb->_perl_version (perl => 'some/perl/bin');

_perl_version returns the version of a certain perl binary. It does this by actually running a command.

Returns the perl version on success and false on failure.

\$cb->_version_to_number(version => \$version);

Returns a proper module version, or '0.0' if none was available.

\$cb->_whoami

Returns the name of the subroutine you're currently in.

_get_file_contents(file => \$file);

Returns the contents of a file

Moves a file or directory to the target.

Returns true on success, false on failure.

Moves a file or directory to the target.

Returns true on success, false on failure.

\$cb->_mode_plus_w(file => '/path/to/file');

Sets the +w bit for the file.

Returns true on success, false on failure.

\$uri = \$cb->_host_to_uri(scheme => SCHEME, host => HOST, path => PATH);

Turns a CPANPLUS::Config style host entry into an URI string.

Returns the uri on success, and false on failure

\$cb->_vcmp(VERSION, VERSION);

Normalizes the versions passed and does a '<=>' on them, returning the result.

\$cb->_home_dir

Returns the user's homedir, or cwd if it could not be found

\$path = \$cb->_safe_path(path => \$path);

Returns a path that's safe to us on Win32 and VMS.

Only cleans up the path on Win32 if the path exists.

On VMS, it encodes dots to _ using VMS::Filespec::vmsify

(\$pkg, \$version, \$ext) = \$cb->_split_package_string(package => PACKAGE_STRING);

Splits the name of a CPAN package string up into its package, version and extension parts.

For example, Foo-Bar-1.2.tar.gz would return the following parts:

```
Package:      Foo-Bar
Version:      1.2
Extension:    tar.gz
```