

NAME

TAP::Parser::Result::Plan - Plan result token.

VERSION

Version 3.23

DESCRIPTION

This is a subclass of *TAP::Parser::Result*. A token of this class will be returned if a plan line is encountered.

```
1..1
ok 1 - woo hooo!
```

1..1 is the plan. Gotta have a plan.

OVERRIDDEN METHODS

Mainly listed here to shut up the pitiful screams of the pod coverage tests. They keep me awake at night.

- * `as_string`
- * `raw`

Instance Methods

`plan`

```
if ( $result->is_plan ) {
    print $result->plan;
}
```

This is merely a synonym for `as_string`.

`tests_planned`

```
my $planned = $result->tests_planned;
```

Returns the number of tests planned. For example, a plan of `1..17` will cause this method to return `'17'`.

`directive`

```
my $directive = $plan->directive;
```

If a SKIP directive is included with the plan, this method will return it.

```
1..0 # SKIP: why bother?
```

`has_skip`

```
if ( $result->has_skip ) { ... }
```

Returns a boolean value indicating whether or not this test has a SKIP directive.

`explanation`

```
my $explanation = $plan->explanation;
```

If a SKIP directive was included with the plan, this method will return the explanation, if any.

todo_list

```
my $todo = $result->todo_list;
for ( @$todo ) {
    ...
}
```