

NAME

ExtUtils::MakeMaker::FAQ - Frequently Asked Questions About MakeMaker

DESCRIPTION

FAQs, tricks and tips for ExtUtils::MakeMaker.

Module Installation

How do I install a module into my home directory?

If you're not the Perl administrator you probably don't have permission to install a module to its default location. Then you should install it for your own use into your home directory like so:

```
# Non-unix folks, replace ~ with /path/to/your/home/dir
perl Makefile.PL INSTALL_BASE=~
```

This will put modules into `~/lib/perl5`, man pages into `~/man` and programs into `~/bin`.

To ensure your Perl programs can see these newly installed modules, set your `PERL5LIB` environment variable to `~/lib/perl5` or tell each of your programs to look in that directory with the following:

```
use lib "$ENV{HOME}/lib/perl5";
```

or if `$ENV{HOME}` isn't set and you don't want to set it for some reason, do it the long way.

```
use lib "/path/to/your/home/dir/lib/perl5";
```

How do I get MakeMaker and Module::Build to install to the same place?

Module::Build, as of 0.28, supports two ways to install to the same location as MakeMaker.

1) Use `INSTALL_BASE` / `--install_base`

MakeMaker (as of 6.31) and Module::Build (as of 0.28) both can install to the same locations using the "install_base" concept. See "`INSTALL_BASE`" in *ExtUtils::MakeMaker* for details. To get MM and MB to install to the same location simply set `INSTALL_BASE` in MM and `--install_base` in MB to the same location.

```
perl Makefile.PL INSTALL_BASE=/whatever
perl Build.PL    --install_base /whatever
```

2) Use `PREFIX` / `--prefix`

Module::Build 0.28 added support for `--prefix` which works like MakeMaker's `PREFIX`.

```
perl Makefile.PL PREFIX=/whatever
perl Build.PL    --prefix /whatever
```

How do I keep from installing man pages?

Recent versions of MakeMaker will only install man pages on Unix like operating systems.

For an individual module:

```
perl Makefile.PL INSTALLMAN1DIR=none INSTALLMAN3DIR=none
```

If you want to suppress man page installation for all modules you have to reconfigure Perl and tell it 'none' when it asks where to install man pages.

How do I use a module without installing it?

Two ways. One is to build the module normally...

```
perl Makefile.PL
make
make test
```

...and then set the PERL5LIB environment variable to point at the blib/lib and blib/arch directories.

The other is to install the module in a temporary location.

```
perl Makefile.PL INSTALL_BASE=~/.tmp
make
make test
make install
```

And then set PERL5LIB to `~/tmp/lib/perl5`. This works well when you have multiple modules to work with. It also ensures that the module goes through its full installation process which may modify it.

PREFIX vs INSTALL_BASE from Module::Build::Cookbook

The behavior of PREFIX is complicated and depends closely on how your Perl is configured. The resulting installation locations will vary from machine to machine and even different installations of Perl on the same machine. Because of this, its difficult to document where prefix will place your modules.

In contrast, INSTALL_BASE has predictable, easy to explain installation locations. Now that Module::Build and MakeMaker both have INSTALL_BASE there is little reason to use PREFIX other than to preserve your existing installation locations. If you are starting a fresh Perl installation we encourage you to use INSTALL_BASE. If you have an existing installation installed via PREFIX, consider moving it to an installation structure matching INSTALL_BASE and using that instead.

Philosophy and History

Why not just use <insert other build config tool here>?

Why did MakeMaker reinvent the build configuration wheel? Why not just use autoconf or automake or ppm or Ant or ...

There are many reasons, but the major one is cross-platform compatibility.

Perl is one of the most ported pieces of software ever. It works on operating systems I've never even heard of (see perlport for details). It needs a build tool that can work on all those platforms and with any wacky C compilers and linkers they might have.

No such build tool exists. Even make itself has wildly different dialects. So we have to build our own.

What is Module::Build and how does it relate to MakeMaker?

Module::Build is a project by Ken Williams to supplant MakeMaker. Its primary advantages are:

- * pure perl. no make, no shell commands
- * easier to customize
- * cleaner internals
- * less cruft

Module::Build is the official heir apparent to MakeMaker and we encourage people to work on M::B rather than spending time adding features to MakeMaker.

Module Writing

How do I keep my \$VERSION up to date without resetting it manually?

Often you want to manually set the \$VERSION in the main module distribution because this is the version that everybody sees on CPAN and maybe you want to customize it a bit. But for all the other modules in your dist, \$VERSION is really just bookkeeping and all that's important is it goes up every time the module is changed. Doing this by hand is a pain and you often

forget. Simplest way to do it automatically is to use your version control system's revision number (you are using version control, right?).

In CVS, RCS and SVN you use `$Revision$` (see the documentation of your version control system for details). Every time the file is checked in the `$Revision$` will be updated, updating your `$VERSION`.

SVN uses a simple integer for `$Revision$` so you can adapt it for your `$VERSION` like so:

```
( $VERSION ) = q$Revision$ =~ /(\d+)/;
```

In CVS and RCS version 1.9 is followed by 1.10. Since CPAN compares version numbers numerically we use a `sprintf()` to convert 1.9 to 1.009 and 1.10 to 1.010 which compare properly.

```
$VERSION = sprintf "%d.%03d", q$Revision$ =~ /(\d+)\.(\d+)/g;
```

If branches are involved (ie. `$Revision: 1.5.3.4$`) its a little more complicated.

```
# must be all on one line or MakeMaker will get confused.
$VERSION = do { my @r = (q$Revision$ =~ /\d+/g); sprintf
"%d."."%03d" x $#r, @r };
```

In SVN, `$Revision$` should be the same for every file in the project so they would all have the same `$VERSION`. CVS and RCS have a different `$Revision$` per file so each file will have a different `$VERSION`. Distributed version control systems, such as SVK, may have a different `$Revision$` based on who checks out the file leading to a different `$VERSION` on each machine! Finally, some distributed version control systems, such as darcs, have no concept of revision number at all.

What's this *META.yml* thing and how did it get in my *MANIFEST*?!

META.yml is a module meta-data file pioneered by `Module::Build` and automatically generated as part of the 'distdir' target (and thus 'dist'). See "*Module Meta-Data*" in *ExtUtils::MakeMaker*.

To shut off its generation, pass the `NO_META` flag to `WriteMakefile()`.

How do I delete everything not in my *MANIFEST*?

Some folks are surprised that `make distclean` does not delete everything not listed in their *MANIFEST* (thus making a clean distribution) but only tells them what they need to delete. This is done because it is considered too dangerous. While developing your module you might write a new file, not add it to the *MANIFEST*, then run a `distclean` and be sad because your new work was deleted.

If you really want to do this, you can use `ExtUtils::Manifest::manifold()` to read the *MANIFEST* and `File::Find` to delete the files. But you have to be careful. Here's a script to do that. Use at your own risk. Have fun blowing holes in your foot.

```
#!/usr/bin/perl -w

use strict;

use File::Spec;
use File::Find;
use ExtUtils::Manifest qw(maniread);

my %manifest = map { ( $_ => 1 ) }
    grep { File::Spec->canonpath($_) }
    keys %{ maniread() };

if( !keys %manifest ) {
    print "No files found in MANIFEST. Stopping.\n";
}
```

```

        exit;
    }

    find({
        wanted => sub {
            my $path = File::Spec->canonpath($_);

            return unless -f $path;
            return if exists $manifest{ $path };

            print "unlink $path\n";
            unlink $path;
        },
        no_chdir => 1
    },
    ".");

```

Which tar should I use on Windows?

We recommend ptar from Archive::Tar not older than 1.66 with '-C' option.

Which zip should I use on Windows for '[nd]make zipdist'?

We recommend InfoZIP: <http://www.info-zip.org/Zip.html>

XS

How to I prevent "object version X.XX does not match bootstrap parameter Y.YY" errors?

XS code is very sensitive to the module version number and will complain if the version number in your Perl module doesn't match. If you change your module's version # without rerunning Makefile.PL the old version number will remain in the Makefile causing the XS code to be built with the wrong number.

To avoid this, you can force the Makefile to be rebuilt whenever you change the module containing the version number by adding this to your WriteMakefile() arguments.

```
depend => { '$(FIRST_MAKEFILE)' => '$(VERSION_FROM)' }
```

How do I make two or more XS files coexist in the same directory?

Sometimes you need to have two and more XS files in the same package. One way to go is to put them into separate directories, but sometimes this is not the most suitable solution. The following technique allows you to put two (and more) XS files in the same directory.

Let's assume that we have a package Cool::Foo, which includes Cool::Foo and Cool::Bar modules each having a separate XS file. First we use the following *Makefile.PL*:

```

use ExtUtils::MakeMaker;

WriteMakefile(
    NAME      => 'Cool::Foo',
    VERSION_FROM => 'Foo.pm',
    OBJECT    => q/$(O_FILES)/,
    # ... other attrs ...
);

```

Notice the OBJECT attribute. MakeMaker generates the following variables in *Makefile*:

```

# Handy lists of source code files:
XS_FILES= Bar.xs \
          Foo.xs

```

```
C_FILES = Bar.c \  
    Foo.c  
O_FILES = Bar.o \  
    Foo.o
```

Therefore we can use the `O_FILES` variable to tell MakeMaker to use these objects into the shared library.

That's pretty much it. Now write *Foo.pm* and *Foo.xs*, *Bar.pm* and *Bar.xs*, where *Foo.pm* bootstraps the shared library and *Bar.pm* simply loading *Foo.pm*.

The only issue left is to how to bootstrap *Bar.xs*. This is done from *Foo.xs*:

```
MODULE = Cool::Foo PACKAGE = Cool::Foo  
  
BOOT:  
# boot the second XS file  
boot_Cool__Bar(aTHX_ cv);
```

If you have more than two files, this is the place where you should boot extra XS files from.

The following four files sum up all the details discussed so far.

```
Foo.pm:  
-----  
package Cool::Foo;  
  
require DynaLoader;  
  
our @ISA = qw(DynaLoader);  
our $VERSION = '0.01';  
bootstrap Cool::Foo $VERSION;  
  
1;  
  
Bar.pm:  
-----  
package Cool::Bar;  
  
use Cool::Foo; # bootstraps Bar.xs  
  
1;  
  
Foo.xs:  
-----  
#include "EXTERN.h"  
#include "perl.h"  
#include "XSUB.h"  
  
MODULE = Cool::Foo PACKAGE = Cool::Foo  
  
BOOT:  
# boot the second XS file  
boot_Cool__Bar(aTHX_ cv);  
  
MODULE = Cool::Foo PACKAGE = Cool::Foo PREFIX = cool_foo_  
  
void  
cool_foo_perl_rules()
```

```
CODE:
    fprintf(stderr, "Cool::Foo says: Perl Rules\n");
```

```
Bar.xs:
-----
#include "EXTERN.h"
#include "perl.h"
#include "XSUB.h"

MODULE = Cool::Bar  PACKAGE = Cool::Bar  PREFIX = cool_bar_

void
cool_bar_perl_rules()
```

```
CODE:
    fprintf(stderr, "Cool::Bar says: Perl Rules\n");
```

And of course a very basic test:

```
t/cool.t:
-----
use Test;
BEGIN { plan tests => 1 };
use Cool::Foo;
use Cool::Bar;
Cool::Foo::perl_rules();
Cool::Bar::perl_rules();
ok 1;
```

This tip has been brought to you by Nick Ing-Simmons and Stas Bekman.

PATCHING

If you have a question you'd like to see added to the FAQ (whether or not you have the answer) please send it to makemaker@perl.org.

AUTHOR

The denizens of makemaker@perl.org.

SEE ALSO

ExtUtils::MakeMaker