

**NAME**

perldebbugs - Guts of Perl debugging

**DESCRIPTION**

This is not *perldebug*, which tells you how to use the debugger. This manpage describes low-level details concerning the debugger's internals, which range from difficult to impossible to understand for anyone who isn't incredibly intimate with Perl's guts. Caveat lector.

**Debugger Internals**

Perl has special debugging hooks at compile-time and run-time used to create debugging environments. These hooks are not to be confused with the *perl -Dxxx* command described in *perlrun*, which is usable only if a special Perl is built per the instructions in the *INSTALL* podpage in the Perl source tree.

For example, whenever you call Perl's built-in `caller` function from the package `DB`, the arguments that the corresponding stack frame was called with are copied to the `@DB::args` array. These mechanisms are enabled by calling Perl with the `-d` switch. Specifically, the following additional features are enabled (cf. "*\$^P*" in *perlvar*):

- Perl inserts the contents of `$ENV{PERL5DB}` (or `BEGIN {require 'perl5db.pl'}` if not present) before the first line of your program.
- Each array `@{"_<$filename"}` holds the lines of `$filename` for a file compiled by Perl. The same is also true for `eval`d strings that contain subroutines, or which are currently being executed. The `$filename` for `eval`d strings looks like `(eval 34)`.  
Values in this array are magical in numeric context: they compare equal to zero only if the line is not breakable.
- Each hash `%{"_<$filename"}` contains breakpoints and actions keyed by line number. Individual entries (as opposed to the whole hash) are settable. Perl only cares about Boolean true here, although the values used by *perl5db.pl* have the form `"$break_condition\0$action"`.  
The same holds for `eval`uated strings that contain subroutines, or which are currently being executed. The `$filename` for `eval`d strings looks like `(eval 34)`.
- Each scalar `${"_<$filename"}` contains `"_<$filename"`. This is also the case for `eval`uated strings that contain subroutines, or which are currently being executed. The `$filename` for `eval`d strings looks like `(eval 34)`.
- After each `required` file is compiled, but before it is executed, `DB::postponed(*{"_<$filename"})` is called if the subroutine `DB::postponed` exists. Here, the `$filename` is the expanded name of the `required` file, as found in the values of `%INC`.
- After each subroutine `subname` is compiled, the existence of `$DB::postponed{subname}` is checked. If this key exists, `DB::postponed(subname)` is called if the `DB::postponed` subroutine also exists.
- A hash `%DB::sub` is maintained, whose keys are subroutine names and whose values have the form `filename:startline-endline`. `filename` has the form `(eval 34)` for subroutines defined inside `eval`s.
- When the execution of your program reaches a point that can hold a breakpoint, the `DB::DB()` subroutine is called if any of the variables `$DB::trace`, `$DB::single`, or `$DB::signal` is true. These variables are not localizable. This feature is disabled when executing inside `DB::DB()`, including functions called from it unless `$^D & (1<<30)` is true.
- When execution of the program reaches a subroutine call, a call to `&DB::sub(args)` is made

instead, with `$DB:::sub` holding the name of the called subroutine. (This doesn't happen if the subroutine was compiled in the `DB` package.)

Note that if `&DB:::sub` needs external data for it to work, no subroutine call is possible without it. As an example, the standard debugger's `&DB:::sub` depends on the `$DB:::deep` variable (it defines how many levels of recursion deep into the debugger you can go before a mandatory break). If `$DB:::deep` is not defined, subroutine calls are not possible, even though `&DB:::sub` exists.

## Writing Your Own Debugger

### Environment Variables

The `PERL5DB` environment variable can be used to define a debugger. For example, the minimal "working" debugger (it actually doesn't do anything) consists of one line:

```
sub DB::DB {}
```

It can easily be defined like this:

```
$ PERL5DB="sub DB::DB {}" perl -d your-script
```

Another brief debugger, slightly more useful, can be created with only the line:

```
sub DB::DB {print ++$i; scalar <STDIN>}
```

This debugger prints a number which increments for each statement encountered and waits for you to hit a newline before continuing to the next statement.

The following debugger is actually useful:

```
{
  package DB;
  sub DB {}
  sub sub {print ++$i, " $sub\n"; &$sub}
}
```

It prints the sequence number of each subroutine call and the name of the called subroutine. Note that `&DB:::sub` is being compiled into the package `DB` through the use of the `package` directive.

When it starts, the debugger reads your rc file (`./perldb` or `~/.perldb` under Unix), which can set important options. (A subroutine (`&afterinit`) can be defined here as well; it is executed after the debugger completes its own initialization.)

After the rc file is read, the debugger reads the `PERLDB_OPTS` environment variable and uses it to set debugger options. The contents of this variable are treated as if they were the argument of an `o` . . . debugger command (q.v. in "Configurable Options" in *perldebug*).

### Debugger Internal Variables

In addition to the file and subroutine-related variables mentioned above, the debugger also maintains various magical internal variables.

- `@DB:::dbline` is an alias for `@{":::_<current_file">}`, which holds the lines of the currently-selected file (compiled by Perl), either explicitly chosen with the debugger's `f` command, or implicitly by flow of execution.

Values in this array are magical in numeric context: they compare equal to zero only if the line is not breakable.

- `%DB:::dbline` is an alias for `%{":::_<current_file">}`, which contains breakpoints and actions keyed by line number in the currently-selected file, either explicitly chosen with the

debugger's `f` command, or implicitly by flow of execution.

As previously noted, individual entries (as opposed to the whole hash) are settable. Perl only cares about Boolean true here, although the values used by *perl5db.pl* have the form `"$break_condition\0$action"`.

### Debugger Customization Functions

Some functions are provided to simplify customization.

- See "*Configurable Options*" in *perldebug* for a description of options parsed by `DB::parse_options(string)`.
- `DB::dump_trace(skip[, count])` skips the specified number of frames and returns a list containing information about the calling frames (all of them, if `count` is missing). Each entry is reference to a hash with keys `context` (either `.`, `$`, or `@`), `sub` (subroutine name, or info about `eval`), `args` (`undef` or a reference to an array), `file`, and `line`.
- `DB::print_trace(FH, skip[, count[, short]])` prints formatted info about caller frames. The last two functions may be convenient as arguments to `<`, `<<` commands.

Note that any variables and functions that are not documented in this manpages (or in *perldebug*) are considered for internal use only, and as such are subject to change without notice.

### Frame Listing Output Examples

The `frame` option can be used to control the output of frame information. For example, contrast this expression trace:

```
$ perl -de 42
Stack dump during die enabled outside of evals.

Loading DB routines from perl5db.pl patch level 0.94
Emacs support available.

Enter h or 'h h' for help.

main::(-e:1): 0
  DB<1> sub foo { 14 }

  DB<2> sub bar { 3 }

  DB<3> t print foo() * bar()
main::((eval 172):3): print foo() + bar();
main::foo((eval 168):2):
main::bar((eval 170):2):
42
```

with this one, once the option `frame=2` has been set:

```
DB<4> o f=2
          frame = '2'
DB<5> t print foo() * bar()
3:      foo() * bar()
entering main::foo
  2:      sub foo { 14 };
exited main::foo
entering main::bar
  2:      sub bar { 3 };
```

```
exited main::bar
42
```

By way of demonstration, we present below a laborious listing resulting from setting your `PERLDB_OPTS` environment variable to the value `f=n N`, and running `perl -d -V` from the command line. Examples using various values of `n` are shown to give you a feel for the difference between settings. Long though it may be, this is not a complete listing, but only excerpts.

```
1      entering main::BEGIN
        entering Config::BEGIN
          Package lib/Exporter.pm.
          Package lib/Carp.pm.
          Package lib/Config.pm.
          entering Config::TIEHASH
          entering Exporter::import
            entering Exporter::export
          entering Config::myconfig
            entering Config::FETCH
            entering Config::FETCH
            entering Config::FETCH
            entering Config::FETCH

2      entering main::BEGIN
        entering Config::BEGIN
          Package lib/Exporter.pm.
          Package lib/Carp.pm.
          exited Config::BEGIN
          Package lib/Config.pm.
          entering Config::TIEHASH
          exited Config::TIEHASH
          entering Exporter::import
            entering Exporter::export
            exited Exporter::export
            exited Exporter::import
          exited main::BEGIN
          entering Config::myconfig
            entering Config::FETCH
            exited Config::FETCH
            entering Config::FETCH
            exited Config::FETCH
            entering Config::FETCH

3      in $=main::BEGIN() from /dev/null:0
        in $=Config::BEGIN() from lib/Config.pm:2
          Package lib/Exporter.pm.
          Package lib/Carp.pm.
          Package lib/Config.pm.
          in $=Config::TIEHASH('Config') from lib/Config.pm:644
          in $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
            in $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from li
          in @=Config::myconfig() from /dev/null:0
            in $=Config::FETCH(ref(Config), 'package') from lib/Config.pm:574
            in $=Config::FETCH(ref(Config), 'baserev') from lib/Config.pm:574
```

```

    in $=Config::FETCH(ref(Config), 'PERL_VERSION') from
lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'PERL_SUBVERSION') from
lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'osname') from lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'osvers') from lib/Config.pm:574

4    in $=main::BEGIN() from /dev/null:0
    in $=Config::BEGIN() from lib/Config.pm:2
    Package lib/Exporter.pm.
    Package lib/Carp.pm.
    out $=Config::BEGIN() from lib/Config.pm:0
    Package lib/Config.pm.
    in $=Config::TIEHASH('Config') from lib/Config.pm:644
    out $=Config::TIEHASH('Config') from lib/Config.pm:644
    in $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
    in $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/
    out $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/
    out $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
    out $=main::BEGIN() from /dev/null:0
    in @=Config::myconfig() from /dev/null:0
    in $=Config::FETCH(ref(Config), 'package') from lib/Config.pm:574
    out $=Config::FETCH(ref(Config), 'package') from lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'baserev') from lib/Config.pm:574
    out $=Config::FETCH(ref(Config), 'baserev') from lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'PERL_VERSION') from
lib/Config.pm:574
    out $=Config::FETCH(ref(Config), 'PERL_VERSION') from
lib/Config.pm:574
    in $=Config::FETCH(ref(Config), 'PERL_SUBVERSION') from
lib/Config.pm:574

5    in $=main::BEGIN() from /dev/null:0
    in $=Config::BEGIN() from lib/Config.pm:2
    Package lib/Exporter.pm.
    Package lib/Carp.pm.
    out $=Config::BEGIN() from lib/Config.pm:0
    Package lib/Config.pm.
    in $=Config::TIEHASH('Config') from lib/Config.pm:644
    out $=Config::TIEHASH('Config') from lib/Config.pm:644
    in $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
    in $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/E
    out $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/E
    out $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
    out $=main::BEGIN() from /dev/null:0
    in @=Config::myconfig() from /dev/null:0
    in $=Config::FETCH('Config=HASH(0x1aa444)', 'package') from

```

```

lib/Config.pm:574  out $=Config::FETCH('Config=HASH(0x1aa444)',
'package') from lib/Config.pm:574
  in $=Config::FETCH('Config=HASH(0x1aa444)', 'baserev') from
lib/Config.pm:574
    out $=Config::FETCH('Config=HASH(0x1aa444)', 'baserev') from
lib/Config.pm:574

6      in $=CODE(0x15eca4)() from /dev/null:0
      in $=CODE(0x182528)() from lib/Config.pm:2
      Package lib/Exporter.pm.
      out $=CODE(0x182528)() from lib/Config.pm:0
      scalar context return from CODE(0x182528): undef
      Package lib/Config.pm.
      in $=Config::TIEHASH('Config') from lib/Config.pm:628
      out $=Config::TIEHASH('Config') from lib/Config.pm:628
      scalar context return from Config::TIEHASH:  empty hash
      in $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
        in $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/Exporter.pm:171
          out $=Exporter::export('Config', 'main', 'myconfig',
'config_vars') from lib/Exporter.pm:171
            scalar context return from Exporter::export: ''
          out $=Exporter::import('Config', 'myconfig', 'config_vars') from
/dev/null:0
            scalar context return from Exporter::import: ''

```

In all cases shown above, the line indentation shows the call tree. If bit 2 of `frame` is set, a line is printed on exit from a subroutine as well. If bit 4 is set, the arguments are printed along with the caller info. If bit 8 is set, the arguments are printed even if they are tied or references. If bit 16 is set, the return value is printed, too.

When a package is compiled, a line like this

```
Package lib/Carp.pm.
```

is printed with proper indentation.

## Debugging Regular Expressions

There are two ways to enable debugging output for regular expressions.

If your perl is compiled with `-DDEBUGGING`, you may use the `-Dr` flag on the command line.

Otherwise, one can use `re 'debug'`, which has effects at compile time and run time. Since Perl 5.9.5, this pragma is lexically scoped.

## Compile-time Output

The debugging output at compile time looks like this:

```

Compiling REx '[bc]d(ef*g)+h[ij]k$'
size 45 Got 364 bytes for offset annotations.
first at 1
rarest char g at 0
rarest char d at 0
  1: ANYOF[bc](12)
 12: EXACT <d>(14)
 14: CURLYX[0] {1,32767}(28)

```

```

16:  OPEN1(18)
18:  EXACT <e>(20)
20:  STAR(23)
21:  EXACT <f>(0)
23:  EXACT <g>(25)
25:  CLOSE1(27)
27:  WHILEM[1/1](0)
28:  NOTHING(29)
29:  EXACT <h>(31)
31:  ANYOF[ij](42)
42:  EXACT <k>(44)
44:  EOL(45)
45:  END(0)
anchored 'de' at 1 floating 'gh' at 3..2147483647 (checking floating)
      stclass 'ANYOF[bc]' minlen 7
Offsets: [45]
1[4] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 5[1]
0[0] 12[1] 0[0] 6[1] 0[0] 7[1] 0[0] 9[1] 8[1] 0[0] 10[1] 0[0]
11[1] 0[0] 12[0] 12[0] 13[1] 0[0] 14[4] 0[0] 0[0] 0[0] 0[0]
0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 18[1] 0[0] 19[1] 20[0]
Omitting $` $& $' support.

```

The first line shows the pre-compiled form of the regex. The second shows the size of the compiled form (in arbitrary units, usually 4-byte words) and the total number of bytes allocated for the offset/length table, usually  $4+size*8$ . The next line shows the label *id* of the first node that does a match.

The

```

anchored 'de' at 1 floating 'gh' at 3..2147483647 (checking floating)
      stclass 'ANYOF[bc]' minlen 7

```

line (split into two lines above) contains optimizer information. In the example shown, the optimizer found that the match should contain a substring *de* at offset 1, plus substring *gh* at some offset between 3 and infinity. Moreover, when checking for these substrings (to abandon impossible matches quickly), Perl will check for the substring *gh* before checking for the substring *de*. The optimizer may also use the knowledge that the match starts (at the *first id*) with a character class, and no string shorter than 7 characters can possibly match.

The fields of interest which may appear in this line are

```

anchored STRING at POS
floating STRING at POS1..POS2

```

See above.

```

matching floating/anchored
      Which substring to check first.

```

```

minlen
      The minimal length of the match.

```

```

stclass TYPE
      Type of first matching node.

```

```

noscan
      Don't scan for the found substrings.

```

`isall`

Means that the optimizer information is all that the regular expression contains, and thus one does not need to enter the regex engine at all.

`GPOS`

Set if the pattern contains `\G`.

`plus`

Set if the pattern starts with a repeated char (as in `x+y`).

`implicit`

Set if the pattern starts with `.*`.

`with eval`

Set if the pattern contain eval-groups, such as `(?{ code })` and `(??{ code })`.

`anchored(TYPE)`

If the pattern may match only at a handful of places, with `TYPE` being `BOL`, `MBOL`, or `GPOS`. See the table below.

If a substring is known to match at end-of-line only, it may be followed by `$`, as in `floating 'k'$`.

The optimizer-specific information is used to avoid entering (a slow) regex engine on strings that will not definitely match. If the `isall` flag is set, a call to the regex engine may be avoided even when the optimizer found an appropriate place for the match.

Above the optimizer section is the list of *nodes* of the compiled form of the regex. Each line has format

*id*: *TYPE* *OPTIONAL-INFO* (*next-id*)

## Types of Nodes

Here are the possible types, with short descriptions:

```
# TYPE arg-description [num-args] [longjump-len] DESCRIPTION
```

```
# Exit points
```

```
END                no          End of program.
SUCCEED            no          Return from a subroutine, basically.
```

```
# Anchors:
```

```
BOL                no          Match "" at beginning of line.
MBOL               no          Same, assuming multiline.
SBOL               no          Same, assuming singleline.
EOS                no          Match "" at end of string.
EOL                no          Match "" at end of line.
MEOL               no          Same, assuming multiline.
SEOL               no          Same, assuming singleline.
BOUND              no          Match "" at any word boundary using
native charset semantics for non-utf8
BOUNDL             no          Match "" at any locale word boundary
BOUNDU             no          Match "" at any word boundary using
Unicode semantics
BOUNDA             no          Match "" at any word boundary using ASCII
```

```

                                semantics
NBOUND          no             Match "" at any word non-boundary using
                                native charset semantics for non-utf8
NBOUNDL         no             Match "" at any locale word non-boundary
NBOUNDU         no             Match "" at any word non-boundary using
                                Unicode semantics
NBOUNDA         no             Match "" at any word non-boundary using
                                ASCII semantics
GPOS            no             Matches where last m//g left off.

# [Special] alternatives:

REG_ANY         no             Match any one character (except newline).
SANY            no             Match any one character.
CANY            no             Match any one byte.
ANYOF           sv             Match character in (or not in) this
                                class, single char match only
ANYOF_WARN_SUPER sv           Match character in (or not in) this
                                class, warn (if enabled) upon matching a
                                char above Unicode max;
ANYOF_SYNTHETIC sv           Synthetic start class

POSIXD          none          Some [[:class:]] under /d; the FLAGS
                                field gives which one
POSIXL          none          Some [[:class:]] under /l; the FLAGS
                                field gives which one
POSIXU          none          Some [[:class:]] under /u; the FLAGS
                                field gives which one
POSIXA          none          Some [[:class:]] under /a; the FLAGS
                                field gives which one
NPOSIXD         none          complement of POSIXD, [[:^class:]]
NPOSIXL         none          complement of POSIXL, [[:^class:]]
NPOSIXU         none          complement of POSIXU, [[:^class:]]
NPOSIXA         none          complement of POSIXA, [[:^class:]]

CLUMP           no             Match any extended grapheme cluster
                                sequence

# Alternation

# BRANCH        The set of branches constituting a single choice are
#               hooked together with their "next" pointers, since
#               precedence prevents anything being concatenated to
#               any individual branch. The "next" pointer of the last
#               BRANCH in a choice points to the thing following the
#               whole choice. This is also where the final "next"
#               pointer of each individual branch points; each branch
#               starts with the operand node of a BRANCH node.
#
BRANCH          node          Match this alternative, or the next...

# Back pointer

```

```

# BACK          Normal "next" pointers all implicitly point forward;
#              BACK exists to make loop structures possible.
# not used
BACK           no           Match "", "next" ptr points backward.

# Literals

EXACT          str          Match this string (preceded by length).
EXACTF         str          Match this non-UTF-8 string (not
                           guaranteed to be folded) using /id rules
                           (w/len).
EXACTFL        str          Match this string (not guaranteed to be
                           folded) using /il rules (w/len).
EXACTFU        str          Match this string (folded iff in UTF-8,
                           length in folding doesn't change if not
                           in UTF-8) using /iu rules (w/len).
EXACTFA        str          Match this string (not guaranteed to be
                           folded) using /iaa rules (w/len).
EXACTFU_SS     str          Match this string (folded iff in UTF-8,
                           length in folding may change even if not
                           in UTF-8) using /iu rules (w/len).
EXACTFU_TRICKYFOLD str      Match this folded UTF-8 string using /iu
                           rules

# Do nothing types

NOTHING        no           Match empty string.
# A variant of above which delimits a group, thus stops optimizations
TAIL           no           Match empty string. Can jump here from
                           outside.

# Loops

# STAR, PLUS   '?', and complex '*' and '+', are implemented as
#              circular BRANCH structures using BACK. Simple cases
#              (one character per match) are implemented with STAR
#              and PLUS for speed and to minimize recursive plunges.
#
STAR           node         Match this (simple) thing 0 or more
                           times.
PLUS           node         Match this (simple) thing 1 or more
                           times.

CURLY          sv 2         Match this simple thing {n,m} times.
CURLYN         no 2         Capture next-after-this simple thing
CURLYM         no 2         Capture this medium-complex thing {n,m}
                           times.
CURLYX         sv 2         Match this complex thing {n,m} times.

# This terminator creates a loop structure for CURLYX
WHILEM         no           Do curly processing and see if rest
                           matches.

```

```

# Buffer related

# OPEN,CLOSE,GROUPP ...are numbered at compile time.
OPEN          num 1      Mark this point in input as start of #n.
CLOSE         num 1      Analogous to OPEN.

REF           num 1      Match some already matched string
REFF          num 1      Match already matched string, folded
                  using native charset semantics for non-
                  utf8
REFFL         num 1      Match already matched string, folded in
                  loc.
REFFU         num 1      Match already matched string, folded
                  using unicode semantics for non-utf8
REFFA         num 1      Match already matched string, folded
                  using unicode semantics for non-utf8, no
                  mixing ASCII, non-ASCII

# Named references. Code in regcomp.c assumes that these all are after
# the numbered references
NREF          no-sv 1     Match some already matched string
NREFF         no-sv 1     Match already matched string, folded
                  using native charset semantics for non-
                  utf8
NREFFL        no-sv 1     Match already matched string, folded in
                  loc.
NREFFU        num 1      Match already matched string, folded
                  using unicode semantics for non-utf8
NREFFA        num 1      Match already matched string, folded
                  using unicode semantics for non-utf8, no
                  mixing ASCII, non-ASCII

IFMATCH       off 1 2     Succeeds if the following matches.
UNLESSM       off 1 2     Fails if the following matches.
SUSPEND       off 1 1     "Independent" sub-RE.
IFTHEN        off 1 1     Switch, should be preceded by switcher.
GROUPP        num 1      Whether the group matched.

# Support for long RE

LONGJMP        off 1 1     Jump far away.
BRANCHJ        off 1 1     BRANCH with long offset.

# The heavy worker

EVAL           evl 1      Execute some Perl code.

# Modifiers

MINMOD         no        Next operator is not greedy.
LOGICAL        no        Next opcode should set the flag only.

```

```

# This is not used yet
RENUM                off 1 1    Group with independently numbered parens.

# Trie Related

# Behave the same as A|LIST|OF|WORDS would. The '..C' variants
# have inline charclass data (ascii only), the 'C' store it in the
# structure.

TRIE                  trie 1     Match many EXACT(F[ALU]?)? at once.
                        flags==type
TRIEC                 trie       Same as TRIE, but with embedded charclass
                        charclass data

AHOCORASICK           trie 1     Aho Corasick stclass. flags==type
AHOCORASICKC          trie       Same as AHOCORASICK, but with embedded
                        charclass charclass data

# Regex Subroutines
GOSUB                 num/ofs 2L  recurse to paren arg1 at (signed) ofs
                        arg2
GOSTART               no         recurse to start of pattern

# Special conditionals
NGROUPP               no-sv 1    Whether the group matched.
INSUBP                num 1      Whether we are in a specific recurse.
DEFINEP               none 1     Never execute directly.

# Backtracking Verbs
ENDLIKE               none       Used only for the type field of verbs
OPFAIL                none       Same as (!)
ACCEPT                parno 1     Accepts the current matched string.

# Verbs With Arguments
VERB                  no-sv 1     Used only for the type field of verbs
PRUNE                  no-sv 1     Pattern fails at this startpoint if no-
                                backtracking through this
MARKPOINT              no-sv 1     Push the current location for rollback by
                                cut.
SKIP                   no-sv 1     On failure skip forward (to the mark)
                                before retrying
COMMIT                 no-sv 1     Pattern fails outright if backtracking
                                through this
CUTGROUP               no-sv 1     On failure go to the next alternation in
                                the group

# Control what to keep in $&.
KEEPS                  no         $& begins here.

# New charclass like patterns
LNBREAK                none       generic newline pattern

```

```
# SPECIAL REGOPS

# This is not really a node, but an optimized away piece of a "long"
# node. To simplify debugging output, we mark it as if it were a node
OPTIMIZED          off          Placeholder for dump.

# Special opcode with the property that no opcode in a compiled program
# will ever be of this type. Thus it can be used as a flag value that
# no other opcode has been seen. END is used similarly, in that an END
# node cant be optimized. So END implies "unoptimizable" and PSEUDO
# mean "not seen anything to optimize yet".
PSEUDO             off          Pseudo opcode for internal use.
```

Following the optimizer information is a dump of the offset/length table, here split across several lines:

```
Offsets: [45]
1[4] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 5[1]
0[0] 12[1] 0[0] 6[1] 0[0] 7[1] 0[0] 9[1] 8[1] 0[0] 10[1] 0[0]
11[1] 0[0] 12[0] 12[0] 13[1] 0[0] 14[4] 0[0] 0[0] 0[0] 0[0]
0[0] 0[0] 0[0] 0[0] 0[0] 0[0] 18[1] 0[0] 19[1] 20[0]
```

The first line here indicates that the offset/length table contains 45 entries. Each entry is a pair of integers, denoted by `offset[length]`. Entries are numbered starting with 1, so entry #1 here is 1[4] and entry #12 is 5[1]. 1[4] indicates that the node labeled 1: (the 1: ANYOF[bc]) begins at character position 1 in the pre-compiled form of the regex, and has a length of 4 characters. 5[1] in position 12 indicates that the node labeled 12: (the 12: EXACT <d>) begins at character position 5 in the pre-compiled form of the regex, and has a length of 1 character. 12[1] in position 14 indicates that the node labeled 14: (the 14: CURLYX[0] {1,32767}) begins at character position 12 in the pre-compiled form of the regex, and has a length of 1 character---that is, it corresponds to the + symbol in the precompiled regex.

0[0] items indicate that there is no corresponding node.

## Run-time Output

First of all, when doing a match, one may get no run-time output even if debugging is enabled. This means that the regex engine was never entered and that all of the job was therefore done by the optimizer.

If the regex engine was entered, the output may look like this:

```
Matching '[bcd](ef*g)+h[ij]k$' against 'abcdefg__gh__'
Setting an EVAL scope, savestack=3
 2 <ab> <cdefg__gh__> | 1: ANYOF
 3 <abc> <defg__gh__> | 11: EXACT <d>
 4 <abcd> <efg__gh__> | 13: CURLYX {1,32767}
 4 <abcd> <efg__gh__> | 26: WHILEM
0 out of 1..32767 cc=effff31c
 4 <abcd> <efg__gh__> | 15: OPEN1
 4 <abcd> <efg__gh__> | 17: EXACT <e>
 5 <abcde> <fg__gh__> | 19: STAR
    EXACT <f> can match 1 times out of 32767...
Setting an EVAL scope, savestack=3
 6 <bcdef> <g__gh__> | 22: EXACT <g>
 7 <bcdefg> <__gh__> | 24: CLOSE1
 7 <bcdefg> <__gh__> | 26: WHILEM
    1 out of 1..32767 cc=effff31c
```

```
Setting an EVAL scope, savestack=12
7 <bcdefg> <__gh__> | 15:      OPEN1
7 <bcdefg> <__gh__> | 17:      EXACT <e>
  restoring \1 to 4(4)..7
  failed, try continuation...
7 <bcdefg> <__gh__> | 27:      NOTHING
7 <bcdefg> <__gh__> | 28:      EXACT <h>
  failed...
failed...
```

The most significant information in the output is about the particular *node* of the compiled regex that is currently being tested against the target string. The format of these lines is

```
STRING-OFFSET <PRE-STRING> <POST-STRING> |ID: TYPE
```

The *TYPE* info is indented with respect to the backtracking level. Other incidental information appears interspersed within.

## Debugging Perl Memory Usage

Perl is a profligate wastrel when it comes to memory use. There is a saying that to estimate memory usage of Perl, assume a reasonable algorithm for memory allocation, multiply that estimate by 10, and while you still may miss the mark, at least you won't be quite so astonished. This is not absolutely true, but may provide a good grasp of what happens.

Assume that an integer cannot take less than 20 bytes of memory, a float cannot take less than 24 bytes, a string cannot take less than 32 bytes (all these examples assume 32-bit architectures, the result are quite a bit worse on 64-bit architectures). If a variable is accessed in two of three different ways (which require an integer, a float, or a string), the memory footprint may increase yet another 20 bytes. A sloppy `malloc(3)` implementation can inflate these numbers dramatically.

On the opposite end of the scale, a declaration like

```
sub foo;
```

may take up to 500 bytes of memory, depending on which release of Perl you're running.

Anecdotal estimates of source-to-compiled code bloat suggest an eightfold increase. This means that the compiled form of reasonable (normally commented, properly indented etc.) code will take about eight times more space in memory than the code took on disk.

The `-DL` command-line switch is obsolete since circa Perl 5.6.0 (it was available only if Perl was built with `-DDEBUGGING`). The switch was used to track Perl's memory allocations and possible memory leaks. These days the use of malloc debugging tools like *Purify* or *valgrind* is suggested instead. See also "*PERL\_MEM\_LOG*" in *perlhacktips*.

One way to find out how much memory is being used by Perl data structures is to install the `Devel::Size` module from CPAN: it gives you the minimum number of bytes required to store a particular data structure. Please be mindful of the difference between the `size()` and `total_size()`.

If Perl has been compiled using Perl's malloc you can analyze Perl memory usage by setting `$ENV{PERL_DEBUG_MSTATS}`.

## Using `$ENV{PERL_DEBUG_MSTATS}`

If your perl is using Perl's malloc() and was compiled with the necessary switches (this is the default), then it will print memory usage statistics after compiling your code when

`$ENV{PERL_DEBUG_MSTATS} > 1`, and before termination of the program when `$ENV{PERL_DEBUG_MSTATS} >= 1`. The report format is similar to the following example:

```
$ PERL_DEBUG_MSTATS=2 perl -e "require Carp"
```

```

Memory allocation statistics after compilation: (buckets 4(4)..8188(8192)
 14216 free:   130  117  28   7   9  0  2   2  1  0  0
437   61   36   0   5
 60924 used:  125  137  161  55   7  8  6  16  2  0  1
 74  109  304  84  20
Total sbrk(): 77824/21:119. Odd ends: pad+heads+chain+tail: 0+636+0+2048.
Memory allocation statistics after execution: (buckets 4(4)..8188(8192)
 30888 free:   245   78   85  13   6  2  1   3  2  0  1
315  162   39   42  11
 175816 used:  265  176 1112  111  26 22 11  27  2  1  1
196  178 1066  798  39
Total sbrk(): 215040/47:145. Odd ends: pad+heads+chain+tail:
0+2192+0+6144.

```

It is possible to ask for such a statistic at arbitrary points in your execution using the `mstat()` function out of the standard `Devel::Peek` module.

Here is some explanation of that format:

```
buckets SMALLEST(APPROX) .. GREATEST(APPROX)
```

Perl's `malloc()` uses bucketed allocations. Every request is rounded up to the closest bucket size available, and a bucket is taken from the pool of buckets of that size.

The line above describes the limits of buckets currently in use. Each bucket has two sizes: memory footprint and the maximal size of user data that can fit into this bucket. Suppose in the above example that the smallest bucket were size 4. The biggest bucket would have usable size 8188, and the memory footprint would be 8192.

In a Perl built for debugging, some buckets may have negative usable size. This means that these buckets cannot (and will not) be used. For larger buckets, the memory footprint may be one page greater than a power of 2. If so, the corresponding power of two is printed in the APPROX field above.

#### Free/Used

The 1 or 2 rows of numbers following that correspond to the number of buckets of each size between `SMALLEST` and `GREATEST`. In the first row, the sizes (memory footprints) of buckets are powers of two--or possibly one page greater. In the second row, if present, the memory footprints of the buckets are between the memory footprints of two buckets "above".

For example, suppose under the previous example, the memory footprints were

```

free:   8   16   32   64   128  256 512 1024 2048 4096
8192
 4   12   24   48   80

```

With a non-`DEBUGGING` perl, the buckets starting from 128 have a 4-byte overhead, and thus an 8192-long bucket may take up to 8188-byte allocations.

```
Total sbrk(): SBRKed/SBRKs:CONTINUOUS
```

The first two fields give the total amount of memory perl `sbrk(2)`ed (ess-broken? :-) and number of `sbrk(2)`s used. The third number is what perl thinks about continuity of returned chunks. So long as this number is positive, `malloc()` will assume that it is probable that `sbrk(2)` will provide continuous memory.

Memory allocated by external libraries is not counted.

```
pad: 0
```

The amount of `sbrk(2)`ed memory needed to keep buckets aligned.

```
heads: 2192
```

Although memory overhead of bigger buckets is kept inside the bucket, for smaller buckets, it is kept in separate areas. This field gives the total size of these areas.

`chain: 0`

`malloc()` may want to subdivide a bigger bucket into smaller buckets. If only a part of the deceased bucket is left unsubdivided, the rest is kept as an element of a linked list. This field gives the total size of these chunks.

`tail: 6144`

To minimize the number of `sbrk(2)`s, `malloc()` asks for more memory. This field gives the size of the yet unused part, which is `sbrk(2)`ed, but never touched.

## SEE ALSO

*perldebug*, *perlguts*, *perlrun re*, and *Devel::DProf*.