

NAME

Encode::Alias - alias definitions to encodings

SYNOPSIS

```
use Encode;
use Encode::Alias;
define_alias( newName => ENCODING);
```

DESCRIPTION

Allows *newName* to be used as an alias for *ENCODING*. *ENCODING* may be either the name of an encoding or an encoding object (as described in *Encode*).

Currently *newName* can be specified in the following ways:

As a simple string.

As a `qr//` compiled regular expression, e.g.:

```
define_alias( qr/^iso8859-(\d+)\$/i => "iso-8859-$1" );
```

In this case, if *ENCODING* is not a reference, it is `eval`-ed in order to allow `$1` etc. to be substituted. The example is one way to alias names as used in X11 fonts to the MIME names for the iso-8859-* family. Note the double quotes inside the single quotes.

(or, you don't have to do this yourself because this example is predefined)

If you are using a regex here, you have to use the quotes as shown or it won't work. Also note that regex handling is tricky even for the experienced. Use this feature with caution.

As a code reference, e.g.:

```
define_alias( sub {shift =~ /^iso8859-(\d+)\$/i ? "iso-8859-$1" :
undef } );
```

The same effect as the example above in a different way. The `coderef` takes the alias name as an argument and returns a canonical name on success or `undef` if not. Note the second argument is not required. Use this with even more caution than the regex version.

Changes in code reference aliasing

As of Encode 1.87, the older form

```
define_alias( sub { return /^iso8859-(\d+)\$/i ? "iso-8859-$1" : undef }
);
```

no longer works.

Encode up to 1.86 internally used "local `$_`" to implement this older form. But consider the code below;

```
use Encode;
$_ = "eeee" ;
while (/(e)/g) {
    my $utf = decode('aliased-encoding-name', $_);
    print "position:",pos,"\n";
}
```

Prior to Encode 1.86 this fails because of "local `$_`".

Alias overloading

You can override predefined aliases by simply applying `define_alias()`. The new alias is always evaluated first, and when necessary, `define_alias()` flushes the internal cache to make the new

definition available.

```
# redirect SHIFT_JIS to MS/IBM Code Page 932, which is a
# superset of SHIFT_JIS

define_alias( qr/shift.*jis$/i => "cp932" );
define_alias( qr/sjis$/i       => "cp932" );
```

If you want to zap all predefined aliases, you can use

```
Encode::Alias->undef_aliases;
```

to do so. And

```
Encode::Alias->init_aliases;
```

gets the factory settings back.

SEE ALSO

Encode, *Encode::Supported*