

## NAME

piconv -- iconv(1), reinvented in perl

## SYNOPSIS

```
piconv [-f from_encoding] [-t to_encoding] [-s string] [files...]  
piconv -l  
piconv [-C N|-c|-p]  
piconv -S scheme ...  
piconv -r encoding  
piconv -D ...  
piconv -h
```

## DESCRIPTION

**piconv** is perl version of **iconv**, a character encoding converter widely available for various Unixen today. This script was primarily a technology demonstrator for Perl 5.8.0, but you can use **piconv** in the place of **iconv** for virtually any case.

**piconv** converts the character encoding of either STDIN or files specified in the argument and prints out to STDOUT.

Here is the list of options. Each option can be in short format (-f) or long (--from).

-f,--from *from\_encoding*

Specifies the encoding you are converting from. Unlike **iconv**, this option can be omitted. In such cases, the current locale is used.

-t,--to *to\_encoding*

Specifies the encoding you are converting to. Unlike **iconv**, this option can be omitted. In such cases, the current locale is used.

Therefore, when both -f and -t are omitted, **piconv** just acts like **cat**.

-s,--string *string*

uses *string* instead of file for the source of text.

-l,--list

Lists all available encodings, one per line, in case-insensitive order. Note that only the canonical names are listed; many aliases exist. For example, the names are case-insensitive, and many standard and common aliases work, such as "latin1" for "ISO-8859-1", or "ibm850" instead of "cp850", or "winlatin1" for "cp1252". See *Encode::Supported* for a full discussion.

-C,--check *N*

Check the validity of the stream if  $N = 1$ . When  $N = -1$ , something interesting happens when it encounters an invalid character.

-c

Same as -C 1.

-p,--perlqq

Same as -C -1.

-h,--help

Show usage.

-D,--debug

Invokes debugging mode. Primarily for Encode hackers.

`-S,--scheme scheme`

Selects which scheme is to be used for conversion. Available schemes are as follows:

`from_to`

Uses `Encode::from_to` for conversion. This is the default.

`decode_encode`

Input strings are `decode()`d then `encode()`d. A straight two-step implementation.

`perlio`

The new perLIO layer is used. NI-S' favorite.

Like the `-D` option, this is also for Encode hackers.

## SEE ALSO

*"1" in iconv "3" in locale Encode Encode::Supported Encode::Alias PerLIO*