

RSA®Conference2015

San Francisco | April 20-24 | Moscone Center

SESSION ID: HTA-W04


Tools of the Hardware Hacking Trade

Joe Grand

Principal Engineer
Grand Idea Studio
@joegrand


CHANGE

Challenge today's security thinking




Finding the Right Tools for the Job

- ◆ Tools can help for design or "undesign"
- ◆ Access to tools is no longer a hurdle
- ◆ Can outsource to those with capabilities/equipment you don't have
- ◆ The key is knowing what tools are available and which one(s) are needed for a particular goal/attack




Hardware Hacking

- ◆ Information Gathering
 - ◆ Obtaining information about the target
- ◆ Teardown
 - ◆ Product disassembly, component/subsystem ID
- ◆ Interfaces
 - ◆ Protocol monitoring/analysis/emulation
- ◆ Firmware
 - ◆ Extract/modify/reprogram code or data
- ◆ Chip-Level
 - ◆ Silicon die modification/data extraction



Tools of the Hardware Hacking Trade


- ◆ Signal Monitoring/Analysis
- ◆ Manipulation/Injection
- ◆ Imaging



RSAC®Conference2015

San Francisco | April 20-24 | Moscone Center



Signal Monitoring / Analysis



 #RSAC



Oscilloscope

- ◆ Provides a visual display of electrical signals and how they change over time
- ◆ Introductory guides: www.tek.com/learning/oscilloscope-tutorial
- ◆ Range of hobbyist (low end) and professional (high end) tools
 - ◆ Analog/digital/mixed signal, # of channels (~1-4), bandwidth, sampling rate, resolution, buffer memory, trigger capabilities, math functions, protocol decoding, probe types, accessories
- ◆ Standalone: HP/Agilent, Tektronix, Rohde & Schwarz, LeCroy, Rigol
- ◆ PC-based: PropScope, USBee, PicoScope, BitScope




Oscilloscope: Example

- ◆ SFMTA Smart Parking Meter (2009)
 - ◆ Joe Grand, Chris Tarnovsky, Jake Appelbaum
 - ◆ Monitored meter/card communication w/ oscilloscope
 - ◆ Slight variation in signal voltage determined direction of data
 - ◆ Created custom Microchip PIC-based smartcard emulator
 - ◆ www.grandideastudio.com/portfolio/smart-parking-meters





Logic Analyzer

- ◆ Used for concurrently capturing, visualizing, and decoding large quantities of digital data
- ◆ Introductory guides: www.tek.com/learning/logic-analyzer-tutorial
- ◆ Range of hobbyist (low end) and professional (high end) tools
 - ◆ # of channels ($\sim > 4$), sampling rate, buffer memory, trigger capabilities, protocol decoding, probe types, accessories
- ◆ Standalone: HP/Agilent, Tektronix
- ◆ PC-based: Saleae Logic, LogicPort, USBee, LeCroy LogicStudio, DigiView, sigrok (open source)




Logic Analyzer: Example





Protocol Analyzer

- ◆ Real-time, non-intrusive monitoring/capturing/decoding of wired communications
 - ◆ HW "man in the middle" to avoid any OS/SW contention/overhead on host
 - ◆ Some also support data injection, measurements
- ◆ Total Phase Beagle (USB, I2C, SPI) and Komodo (CAN)
- ◆ LeCroy Voyager (USB 2.0/3.0)
- ◆ International Test Instruments (USB 2.0, PCIe 1.1)
- ◆ OpenVizsla (USB), <http://openvizsla.org>
- ◆ Daisho (Ethernet, USB 3.0, HDMI), <http://ossmann.blogspot.com/2013/05/introducing-daisho.html>




Protocol Analyzer: Example



Bus Pirate


- ◆ Open source tool to interface w/ serial devices
 - ◆ SPI, I2C, 1-Wire, LCD, MIDI, MCU/FPGA programming, bit bang
- ◆ Basic logic analyzer/digital decoding functionality (slow)
- ◆ http://dangerousprototypes.com/docs/Bus_Pirate



```



HiZ>?
General
-----
? This help
~X/|X Converts x/reverse x
# Selftest
$ Reset
&/% Jump to bootloader
a/A/@ AUXPIN (low/HI/READ)
b Set baudrate
c/C AUX assignment (aux/CS)
d/D Measure ADC (once/CONT.)
f Measure frequency
g/S Generate PWM/servo
h Commandhistory
i Versioninfo/statusinfo
l/L Bitorder (msb/LSB)
m Change mode
o Set output type
p/P Pullup resistors (off/on)
s Script engine
v Show volts/states
w/W PSU (off/on)
HiZ>

Protocol interaction
-----
? (0) List current macros
~ (x) Macro x
# Start
$ Stop
&/% Start with read
a/A/@ Stop
b "abc" Send string
c 123
d 0x123
f 0b110 Send value
g r Read
h / CLK hi
i \ CLK lo
l ^ CLK tick
m - DAT hi
o - DAT lo
p ! DAT read
s . Bit read
v : Repeat e.g. r:10
w . Bits to read/write e.g. 0x55.2
HiZ> <x>/<x= >/<0> Usermacro x/assign x/list all
    
```





USB-to-Serial Adapter

- ◆ Converts logic level asynchronous serial to USB Virtual COM Port
 - ◆ → TXD = Transmit data (to target device)
 - ◆ ← RXD = Receive data (from target device)
 - ◆ ↔ DTR, DSR, RTS, CTS, RI, DCD = Control signals (often unused)
- ◆ Easily connects to PC, Mac, Linux w/ suitable drivers
- ◆ Ex.: FTDI FT232, CP2102, PL2303, Adafruit FTDI Friend
- ◆ Many embedded systems use UART as debug output/root shell
 - ◆ Ex.: Exploitee.rs Wiki (formerly GTVHackers), www.exploitee.rs



USB-to-Serial Adapter: Example

- ◆ Apex STB236 Set Top Box
 - ◆ Visually identify connector
 - ◆ Oscilloscope to determine baud rate (115.2kbps)
 - ◆ USB-to-Serial adapter
 - ◆ Bootloader + U-Boot



USB-to-Serial Adapter: Example 2


```
-----
-- STB222 Lite Primary Bootloader 0.1-3847, NI (04:00:34, Feb 17 2009)
-- Andre McCurdy, NXP Semiconductors
-----
```

```
Device: PNX8335 M1
Secure boot: disabled, keyset: 0, vid: 0 (expecting 2)
Poly10: 0x00000000
RNG: enabled
RSA keyhide: enabled
UID: 0000000000000000
AES key: 00000000000000000000000000000000
KC status: 0x00000000
Flash config: 7 (omni: 8bit NAND), timing: 0x0C
CPU clock: 320 MHz
DRAM: 200 MHz, 1 x 1 64MByte 16bit device (SIF0): 64 MBytes
NAND: RDY polling disabled
NAND: (AD76) Hynix SLC, pagesize 512, blocksize 16k, 64 MBytes
NAND 0x00020000: valid header
NAND 0x00020000: valid image
aboot exec time: 179602 uSec
```

U-Boot 1.2.0.dev (Secondary Bootloader) (Jul 31 2009 - 02:53:01)


```
CPU: PNX????
Secure boot: disabled
DRAM: 64 MB
NAND: nCS0 (force asserted legacy mode)
NAND: Hynix 64MiB 3,3V 8-bit
NAND 0x02a3c000: bad block
NAND 0x030bc000: bad block
NAND 0x03478000: bad block
NAND 0x0385c000: bad block
Board Opts: SCART PAL
Splash: done
u-boot startup time so far: 1012 msec
Hit any key to stop autoboot: 1 ... 0
```

STB225v1 nand#




Software Defined Radio

- ◆ Communication system where digital signal processing is used to implement radio/RF functions
 - ◆ Ex.: Mixers, filters, amplifiers, modulators/demodulators, detectors
 - ◆ RF front end + general purpose computer to receive/transmit arbitrary radio signals
- ◆ Primary toolset for RF/radio hacking
 - ◆ Visualize RF spectrum (spectrum analyzer)
 - ◆ Modulate/demodulate/filter raw signal
 - ◆ Decode/inject data
- ◆ Ex.: RTL-SDR, HackRF One, Blade RF, RFIDler






Software Defined Radio: Example

- ◆ Verisure Wireless Home Alarm
 - ◆ Discover frequency and modulation scheme using GQRX and HackRF
 - ◆ Capture raw signal and import into Baudline for visualization
 - ◆ Create custom flowgraph using GNU Radio to capture, filter, demodulate, and slice signal into binary data
 - ◆ <https://funoverip.net/2014/11/reverse-engineer-a-verisure-wireless-alarm-part-1-radio-communications/>




Software Defined Radio: Example 2



RSA[®]Conference2015

San Francisco | April 20-24 | Moscone Center



Manipulation / Injection



 #RSAC


Soldering Iron

- ◆ Provides heat to melt solder that physically holds components on a circuit board
- ◆ Range from a simple stick iron to a full-fledged rework station
 - ◆ Interchangeable tips, adjustable temperature, hot air reflow
- ◆ Weller, Metcal, Hakko, Radio Shack (!)




Soldering Accessories

- ◆ Solder: Thin gauge (0.032" or 0.025" diameter), ~60/40 Rosin core or lead-free alloy
- ◆ Desoldering Tool ("Solder Sucker"): Manual vacuum device that pulls up molten solder into its chamber
- ◆ Desoldering Braid: Wicks molten solder up into braid
- ◆ Flux: Assists in heat transfer and removal of surface oxides
- ◆ Tip cleaner: Helps to keep the solder tip clean for even heat distribution. Ex.: Sponge, tip tinner




ChipQuik

- ◆ Allows the quick and easy removal of surface mount (and some through hole) components
- ◆ Primary component is a low-melting temperature alloy (less than 200°F)
 - ◆ Reduces the overall melting temperature of the solder
 - ◆ Enables you to just lift/slide the part easily off of the board
- ◆ www.chipquik.com




Rework Station

- ◆ Hot air convection, infrared, laser
- ◆ Allows easier removal and reflow of individual SMD components
 - ◆ Especially BGA (Ball Grid Array) & CSP (Chip Scale Package)
- ◆ Nozzles for different package types/mechanical footprints
- ◆ Weller, Metcal, Hakko, ZEVAC, Zephyrtronics




Device Programmer

- ◆ Used to read/write most devices that contain memory
 - ◆ Standalone or internal to MCU
 - ◆ Ex.: Flash, E(E)PROM, ROM, RAM, PLD/CPLD, FPGA
- ◆ Some devices can be manipulated in-circuit
- ◆ Many support > 90k (!) different devices
- ◆ Few extraction/read-out/access mechanisms exist
 - ◆ Security bit/fuse, password protection
- ◆ EE Tools, Xeltek, BP Microsystems, Data I/O




Debug Tools

- ◆ Off-the-shelf HW tools designed for interaction w/ target device
 - ◆ Can provide chip-level control (single step, access registers)
 - ◆ Extract program code or data
 - ◆ Modify memory contents
 - ◆ Affect device operation on-the-fly
- ◆ Either vendor-specific or industry standard (JTAG)
- ◆ Many different types available
 - ◆ Ensure tool supports your target architecture
 - ◆ Find out what vendor recommends for legitimate engineers




Debug Tools: JTAG

- ◆ Bus Blaster (open source)
 - ◆ http://dangerousprototypes.com/docs/Bus_Blaster
- ◆ SEGGER J-Link
 - ◆ www.segger.com/debug-probes.html
- ◆ H-JTAG
 - ◆ www.hjtag.com/en
- ◆ RIFF Box
 - ◆ www.jtagbox.com
- ◆ Many Others
 - ◆ <http://openocd.sourceforge.net/doc/html/Debug-Adapter-Hardware.html>







Debug Tools: Example

- ◆ Ford Electronic Control Units (ECUs) (2013)
 - ◆ For Charlie Miller & Chris Valasek
 - ◆ Complete firmware extraction to help understand typical CAN traffic/ functionality
 - ◆ http://illmatics.com/car_hacking.pdf
 - ◆ Used standard, off-the-shelf development tools
 - ◆ Freescale CodeWarrior for S12(X) v5.1 + P&E Multilink USB Rev. C






Debug Tools: Example 2




JTAGulator

- ◆ Joe Grand
- ◆ Assisted discovery of on-chip debug interfaces (JTAG & UART)
- ◆ Supports up to 24 connections to unknown points on target circuit board, adjustable target voltage (1.2V-3.3V), input protection, firmware upgradable
- ◆ www.jtagulator.com



JTAGulator: Example

- ◆ Linksys WRT54G v2
 - ◆ Broadcom BCM4712
 - ◆ IDCODE = 0x1471217F



```

JTAGulator v1.0
File Edit View Gpio Transfer Help

U Identify UART pinout
P UART passthrough

General Commands:
V Set target system voltage (1.2V to 3.3V)
R Read all channels (input)
W Write all channels (output)
J Display version information
H Display available commands
:b
Enter number of channels to use (4 - 24): 6
Ensure connections are on CH5..CH0.
Possible permutations: 360
Press spacebar to begin (any other key to abort)...
JTAGulating! Press any key to abort.....
TDI: 3
TDO: 4
TCK: 1
TMS: 5
TRST#: 2
Number of devices detected: 1
BYPASS scan complete!
:~
Connected 0:11:52 Auto detect 115200 B-N-1 SCROLL CAPS NUM Capture Print gcho

```

```

JTAGulator v1.0
File Edit View Gpio Transfer Help


U Identify UART pinout
P UART passthrough

General Commands:
V Set target system voltage (1.2V to 3.3V)
R Read all channels (input)
W Write all channels (output)
J Display version information
H Display available commands
:d
IDI not needed to retrieve Device ID.
Enter new TDO pin [0]: 4
Enter new TCK pin [0]: 1
Enter new TMS pin [0]: 5
Enter number of devices in JTAG chain [0]: 1
All other channels set to output HIGH.

Device ID: 0001 0100011100010010 00010111111 1` (0x1471217F)
-> Manufacturer ID: 0x0BF
-> Part Number: 0x4712
-> Version: 0x1



IDCODE listing complete!
:~
Connected 0:00:47 Auto detect 115200 B-N-1 SCROLL CAPS NUM Capture Print gcho

```



GoodFET

- ◆ Travis Goodspeed
- ◆ Open source tool for interfacing/hacking chips & target devices
- ◆ Different FW and Python scripts for different functionality
 - ◆ Ex.: JTAG, SPI, I2C, AVR, PIC, Chipcon/Nordic/Atmel RF
- ◆ <http://goodfet.sourceforge.net>




GoodFET: Example

- ◆ Travis Goodspeed & Michael Ossmann
- ◆ Reprogram firmware in Chipcon C1110 MCU (8051)
- ◆ Change IM-Me from \$16 toy to a pocket spectrum analyzer
- ◆ <https://jbremnant.wordpress.com/2010/11/23/flashing-ucs-with-goodfet/>



```
$ goodfet.cc flash specan.hex
Flashing specan.hex
Buffering 0000 toward 000000
Buffering 0100 toward 000000
Buffering 0200 toward 000000
Buffering 0300 toward 000000
Flashing buffer to 0x000000
Flashed page at 000000
...
```




Facedancer

- ◆ Travis Goodspeed
- ◆ Emulate USB devices for host-based testing/fuzzing/analysis
 - ◆ <http://goodfet.sourceforge.net/hardware/facedancer21/>





```
# Finds devices supported by the OS
$ python3 umap.py -P /dev/ttyUSB3 -i
# Fuzz a HID device class
$ python3 umap.py -P /dev/ttyUSB3 -f 03:00:00:C
# Try to identify the operating system
$ python3 umap.py -P /dev/ttyUSB3 -O
# Run a single fuzz test case
$ python3 umap.py -P /dev/ttyUSB3 -s 03:00:00:C:16
```





Die Datenkrake

- ◆ Dmitry Nedospasov & Thorsten Schroeder
- ◆ Low cost, open source development & attack platform
 - ◆ ARM Cortex-M3 + FPGA
- ◆ Fuzzing, glitching, protocol analysis
- ◆ Requires off-the-shelf IDEs for FW & FPGA development
- ◆ www.datenkrake.org



ChipWhisperer

- ◆ Colin O'Flynn
- ◆ Collection of open source HW/SW tools for side channel, timing, and glitching attacks
- ◆ Supports AES-128/256 key extraction via EM/power analysis
- ◆ www.chipwhisperer.com



RSA[®]Conference2015




San Francisco | April 20-24 | Moscone Center

Imaging






Acoustic Microscopy

- ◆ Target placed into bath of DI water or alcohol
 - ◆ Serves as liquid coupling medium to transfer sound waves to target
- ◆ Ultrasound emitted into target (15-300MHz)
- ◆ Return echoes are captured (reflection)
- ◆ Transmission through the target is measured (thru scan)





Acoustic Microscopy 2

- ◆ Typically used for non-destructive failure analysis & reliability testing/verification of ICs, components, packaging, wafers
 - ◆ Can identify air gaps/voids, delamination, cracks/mechanical stress, counterfeits
- ◆ We can use it for examining through epoxy encapsulation
 - ◆ Identify key components, connections, or locations




X-Ray (2D)

- ◆ X-rays passed through target and received on detector
 - ◆ All materials absorb radiation differently depending on density, atomic number, and thickness
- ◆ Provides a composite image of all layers in target








X-Ray (2D) 2

- ◆ Typically used during PCB assembly (component placement/solder quality) or failure analysis (troubleshooting defective features)
- ◆ We can use it for general PCB inspection and examining through epoxy encapsulation
 - ◆ Can get clues of PCB fabrication techniques, component location, layer count, hidden/embedded features




X-Ray (2D): Examples






X-Ray (3D/CT)

- ◆ Computed Tomography (CT)
 - ◆ A series of 2D X-ray images post-processed to create cross-sectional slices of the target
 - ◆ X-ray beam rotated 360° in a single axis around the target
 - ◆ Post-processing results in 2D slices that can be viewed in any plane (X, Y, Z)
 - ◆ Can be manipulated with 3D modeling software





X-Ray (3D/CT) 2

- ◆ Typically used for complex inspection and failure analysis of PCBs, component packaging, solder ball/joint quality
- ◆ We can use it to extract individual layers of a PCB
 - ◆ Results may vary based on layer count, inter-layer thickness, copper weight, substrate composition






X-Ray (3D/CT): Example

- ◆ PCB layer extraction, www.grandideastudio.com/portfolio/pcbdt/





Scanning Electron Microscope

- ◆ Uses electrons instead of light to form an image
 - ◆ Wide range of magnifications, better quality than optical microscope
- ◆ Provides an entire chip-level and gate-level view of the device
 - ◆ May need to remove other layers before access to gate structures
- ◆ Voltage contrast microscopy
 - ◆ Gate charges and voltage levels shown as brightness variations
 - ◆ Useful for failure analysis/comparisons and signal/bus monitoring



FIB (Focused Ion Beam)


- ◆ Send a focused stream of ions onto the surface of the chip
- ◆ Beam current/velocity and optional use of gas/vapor changes the function:
 - ◆ Imaging
 - ◆ Cutting
 - ◆ Deposition



RSA®Conference2015


San Francisco | April 20-24 | Moscone Center

Now What?



Now What?

- ◆ Create a hardware hacking lab (if you haven't already)
- ◆ Keep an eye out for new tools by hackers and industry
- ◆ Collaborate with others who may have complementary skills/tools
- ◆ Use these tools to validate your product's security or to better understand attack techniques



RSA[®]Conference2015

San Francisco | April 20-24 | Moscone Center

Questions?

